



MATERIAL SAFETY DATA SHEET

The Sherwin-Williams Company
THE SPECIALTY DIVISION
6830 Cochran Rd.
Solon, OH 44139-3908

Emergency Telephone
216-292-7400

For ordering information, additional copies of MSDS, etc., 1-800-832-2541
For technical information only, 216-292-7400

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

DESCRIPTION: **KRYLON INT./EXT. ENAMEL**
PRODUCT TYPE: **SPARY PAINT "AEROSOL"**
APPLICATION: **ITEMS 1604 THRU 2505 — 1604 SHADOW GRAY, 1605 DOVE GRAY, 1606 PEWTER GRAY, 1608 SMOKE GRAY, 1617 PEARL GRAY 1801 CHROME**

10-Apr-89

YELLOW, 1811 HARVEST GOLD, 1813 DAISY YELLOW (OSHA SAFETY YELLOW), 1902 BABY BLUE, 1904 TEAL BLUE, 1905 COLONIAL BLUE, 1910 TRUE BLUE, 2002 PASTEL AQUA, 2003 JADE GREEN, 2008 AQUA TURQUOISE, 2009 AVOCADO, 2010 JUNGLE GREEN, 2012 CLOVER GREEN (SAFETY GREEN), 2110 HOT PINK, 2116 SCARLET (OSHA SAFETY RED), 2117 BONFIRE, 2406 BURNT ORANGE, 2411 BRICK, 2412 LIGHT PEACH, 2414 MAUVE, 2504 BEIGE, 2505 CHIPPEWA

SIGNAL WORD DANGER!

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

CHEMICAL HAZARD RATING

HEALTH=2(MODERATE)
FIRE=4(EXTREME)
REACTIVITY=0(LEAST)
CHRONIC=*
29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS

CAS/REGISTRY NO. MATERIAL DESCRIPTION % RANGE

THE INGREDIENTS LISTED BELOW HAVE BEEN ASSOCIATED WITH ONE OR MORE OF THE LISTED IMMEDIATE AND/OR DELAYED (*) HEALTH HAZARDS. RISK OF DAMAGE AND EFFECTS DEPENDS UPON DURATION AND LEVEL OF EXPOSURE. BEFORE USING OR HANDLING, READ AND UNDERSTAND THE MSDS.

67-64-1 ACETONE 30-50

NOTE REVISED OSHA PEL

CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.
—SEE FOOTNOTE C.
ACGIH TLV: 750 PPM(1780 MG/M3) TWA; 1000 PPM(2375 MG/M3) STEL
OSHA PEL: 750 PPM(1800 MG/M3) TWA; 1000 PPM(2400 MG/M3) STEL
NIOSH DOCUMENT NUMBER: 78-173

71-36-3 1-BUTANOL 1-5

CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.
—SEE FOOTNOTE C.
ACGIH TLV: SKIN - 50 PPM (150 MG/M3) CEILING
OSHA PEL: SKIN - 50 PPM (150 MG/M3) CEILING

74-98-6 PROPANE 10-30

THIS MATERIAL IS A SIMPLE ASPHYXIANT. SIGNS AND SYMPTOMS OF OVEREXPOSURE INCLUDE CYANOSIS, RESPIRATORY DISTRESS, HEADACHE, DIZZINESS, DROWSINESS, UNCONSCIOUSNESS AND ASPHYXIATION. CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.
—SEE FOOTNOTE C.
ACGIH TLV: SIMPLE ASPHYXIANT - SEE ACGIH TLVS, APPENDIX E
OSHA PEL: 1000 PPM (1800 MG/M3) TWA

78-93-3 *METHYL ETHYL KETONE 5-10

NOTE REVISED OSHA PEL

SUSPECT REPRODUCTIVE HAZARD. MAY CAUSE REPRODUCTIVE DISORDERS BASED ON ANIMAL DATA.
METHYL ETHYL KETONE MAY POTENTIATE (SHORTEN THE TIME OF ONSET) PERIPHERAL NEUROPATHY CAUSED BY METHYL N-BUTYL KETONE OR N-HEXANE. METHYL ETHYL KETONE BY ITSELF HAS NOT BEEN SHOWN TO CAUSE PERIPHERAL NEUROPATHY.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND ASPHYXIATION.
REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY LEAD TO ADDICTION AND MAY BE HARMFUL OR FATAL.
—SEE FOOTNOTE C.
ACGIH TLV: 200 PPM (590 MG/M3) TWA; 300 PPM (885 MG/M3) STEL
OSHA PEL: 200 PPM (590 MG/M3) TWA; 300 PPM (885 MG/M3) STEL
NIOSH DOCUMENT NUMBER: 78-173

108-10-1 METHYL ISOBUTYL KETONE 1-5

NOTE REVISED OSHA PEL

CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.
—SEE FOOTNOTE C.
ACGIH TLV: 50 PPM (205 MG/M3) TWA; 75 PPM (300 MG/M3) STEL
OSHA PEL: 50 PPM (205 MG/M3) TWA; 75 PPM (300 MG/M3) STEL
NIOSH DOCUMENT NUMBER: 78-173

—SEE FOOTNOTE C. 5-10

ACGIH TLV: NONE ESTABLISHED
OSHA PEL: NONE ESTABLISHED

108-88-3 *TOLUENE 1-5

NOTE REVISED OSHA PEL

CAN CAUSE LIVER DAMAGE.
CAN CAUSE KIDNEY DAMAGE.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND ASPHYXIATION.
REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY LEAD TO ADDICTION AND MAY BE HARMFUL OR FATAL.
—SEE FOOTNOTE C.
ACGIH TLV: 100 PPM (375 MG/M3) TWA; 150 PPM (560 MG/M3) STEL
OSHA PEL: 100 PPM (375 MG/M3) TWA; 150 PPM (560 MG/M3) STEL
NIOSH DOCUMENT NUMBER: 73-11023

1330-20-7 *XYLENE 10-30

NOTE REVISED OSHA PEL

CAN CAUSE LIVER DAMAGE.
CAN CAUSE KIDNEY DAMAGE.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.
—SEE FOOTNOTE C.
ACGIH TLV: 100 PPM (435 MG/M3) TWA; 150 PPM (655 MG/M3) STEL
OSHA PEL: 100 PPM (435 MG/M3) TWA; 150 PPM (655 MG/M3) STEL
NIOSH DOCUMENT NUMBER: 75-168

13463-67-7 *TITANIUM DIOXIDE 1-5

NOTE REVISED OSHA PEL

CAN CAUSE LUNG FIBROSIS. PRE-EXISTING RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE.
—SEE FOOTNOTE C.
ACGIH TLV: TOTAL DUST 10 MG/M3 TWA
OSHA PEL: RESPIRABLE FRACTION/TOTAL DUST 5/10 MG/M3 TWA

FOOTNOTE C: AS OF THE DATE OF ISSUANCE OF THIS DOCUMENT, THIS MATERIAL HAS NOT BEEN LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

PHYSICAL DATA

VAPOR PRESSURE — SEE CAN PRESSURE
VAPOR DENSITY HEAVIER THAN AIR
SOLUBILITY IN WATER SLIGHT
SPECIFIC GRAVITY LIGHTER THAN WATER
EVAP RATE FASTER THAN BUTYL ACETATE
SEE REVERSE SIDE

BOILING POINT: APPEARANCE: ODOR N.A.
PERCENT VOLATILE BY WEIGHT 81 TO 89
PERCENT NON-VOLATILE BY WEIGHT 11 TO 19
PRESSURE IN CONTAINER, PSIG @ 70 F. APPROX. 60

IMMEDIATE HEALTH HAZARD DATA

SKIN ABSORPTION: NO HAZARDS KNOWN TO BORDEN.
INGESTION: NOT EXPECTED TO BE HARMFUL UNDER NORMAL CONDITIONS OF USE.
IF ACCIDENTALLY SWALLOWED, BURNS OR IRRITATION TO MUCOUS MEMBRANES, ESOPHAGUS OR GI TRACT CAN RESULT.
INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR MAY CAUSE IRRITATION OF NOSE, THROAT AND LUNGS.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.
SKIN: CAUSES IRRITATION.
EYES: CAUSES IRRITATION.

HANDLING PRECAUTIONS

INHALATION: AVOID BREATHING VAPOR OR MIST.
USE WITH ADEQUATE VENTILATION.
SKIN: AVOID CONTACT WITH SKIN.
EYES: AVOID CONTACT WITH EYES.
HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND CLOTHING.
WASH THOROUGHLY AFTER HANDLING.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: IF ACCIDENTALLY SWALLOWED, DILUTE BY DRINKING LARGE QUANTITIES OF WATER. IMMEDIATELY CONTACT POISON CONTROL CENTER OR HOSPITAL EMERGENCY ROOM FOR ANY OTHER ADDITIONAL TREATMENT DIRECTIONS.
INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH.
SKIN CONTACT: FLUSH SKIN WITH PLENTY OF WATER.
REMOVE CONTAMINATED CLOTHING. CALL A PHYSICIAN IF IRRITATION PERSISTS.
EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. EYELIDS SHOULD BE HELD APART DURING IRRIGATION TO INSURE WATER CONTACT WITH ENTIRE SURFACE OF EYES AND LIDS. CALL A PHYSICIAN.

FIRE AND EXPLOSION HAZARD DATA

EXTREMELY FLAMMABLE.
DO NOT INCINERATE (BURN) CONTAINER.
AVOID HEAT. KEEP CONTAINER BELOW 120 F. HIGH TEMPERATURES MAY CAUSE BURSTING. DO NOT PLACE CONTAINER ON RADIATOR, STOVE, IN DIRECT SUNLIGHT OR NEAR OTHER HEAT SOURCES. **DO NOT PUNCTURE CONTAINER.** CONTENTS UNDER PRESSURE WILL DISCHARGE. **AVOID OPEN FLAMES, SPARKS, PILOT LIGHTS. DO NOT SMOKE.** VAPOR MAY IGNITE EXPLOSIVELY. SPRAY MIST OR VAPOR EVAPORATING FROM A DEPOSITED FILM IS HEAVIER THAN AIR AND MAY SETTLE IN LOW PLACES OR TRAVEL OUTWARD TO A SOURCE OF IGNITION AND FLASHBACK.
IN CASE OF FIRE, USE DRY CHEMICAL, FOAM OR CO₂. WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.

REACTIVITY DATA

NORMALLY STABLE AS DEFINED IN NFPA 704-12 (4-3.1).
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.
DECOMPOSITION PRODUCTS MAY INCLUDE: OXIDES OF CARBON.

CONTROL MEASURES

IF AIRBORNE CONTAMINANTS ARE GENERATED WHEN THE MATERIAL IS

HEATED OR HANDLED, SUFFICIENT VENTILATION IN VOLUME AND AIR FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT CONCENTRATION LEVELS BELOW ACCEPTABLE CRITERIA.

ENGINEERING CONTROLS: THE FOLLOWING EXPOSURE CONTROL TECHNIQUES MAY BE USED TO EFFECTIVELY MINIMIZE EMPLOYEE EXPOSURE: LOCAL EXHAUST VENTILATION, ENCLOSED SYSTEM DESIGN, PROCESS ISOLATION AND REMOTE CONTROL IN COMBINATION WITH APPROPRIATE USE OF PERSONAL PROTECTIVE EQUIPMENT AND PRUDENT WORK PRACTICES. THESE TECHNIQUES MAY NOT NECESSARILY ADDRESS ALL ISSUES PERTAINING TO YOUR OPERATIONS. WE, THEREFORE, RECOMMEND THAT YOU CONSULT WITH EXPERTS OF YOUR CHOICE TO DETERMINE WHETHER OR NOT YOUR PROGRAMS ARE ADEQUATE.

PERSONAL PROTECTION INFORMATION

WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT. RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANTS IN AIR IN ACCORDANCE WITH OSHA 29 CFR 1910.134 OR OTHER APPLICABLE STANDARDS OR GUIDELINES. USE GOGGLES IF CONTACT IS LIKELY.
WEAR IMPERVIOUS GLOVES AS REQUIRED TO PREVENT SKIN CONTACT.

SPILL OR LEAK PROCEDURES

ELIMINATE ALL IGNITION SOURCES.
SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA.
PREVENT ENTRY INTO NATURAL BODIES OF WATER.

WASTE DISPOSAL

DISPOSE OF ACCORDING TO LOCAL, STATE/PROVINCIAL, AND FEDERAL REQUIREMENTS.
EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY.
INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.

STORAGE PRECAUTIONS

DO NOT STORE AT TEMPERATURES ABOVE 120 F.

DOT CLASSIFICATION

ORM-D CONSUMER COMMODITY.

**SARA TITLE III SECTION 313
AND 40 CFR PART 372
TOXIC CHEMICAL NOTIFICATION SHEET**

KRYLON INT./EXT. ENAMEL

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986, AND SUBPART C-SUPPLIER NOTIFICATION REQUIREMENT OF 40 CFR PART 372.

CAS REGISTRY NUMBER	CHEMICAL NAME	PCT. BY WEIGHT
67-64-1	ACETONE	36.71
71-36-3	N-BUTYL ALCOHOL	1.00
78-93-3	METHYL ETHYL KETONE	8.34
108-10-1	METHYL ISOBUTYL KETONE	1.00
108-65-6	2-PROPANOL, 1-METHOXY-, ACETATE	7.51
108-88-3	TOLUENE	1.68
1330-20-7	XYLENE (MIXED ISOMERS)	10.66

THIS TOXIC CHEMICAL NOTIFICATION SHEET MUST NOT BE DETACHED FROM THE MATERIAL SAFETY DATA SHEET (MSDS). ANY COPYING AND REDISTRIBUTION OF THE MSDS SHALL INCLUDE COPYING AND REDISTRIBUTION OF THIS NOTIFICATION SHEET ATTACHED TO COPIES OF THE MSDS SUBSEQUENTLY REDISTRIBUTED.