

MATERIAL SAFETY DATA**MANUFACTURER:** Mautz Paint Co.**ADDRESS:** 939 E. Washington Ave. Madison, WI.
EMERGENCY TEL. (608) 262-3702 or (608) 255-1661
PRODUCT CLASS: Water Based Latex Paint
TRADE NAME: Latex Exterior Flat Line
MFG. CODE ID: 4466-S through 4469-SSTOCK NO.COMMODITY CODE

7342

73-200-10003

HAZARDOUS INGREDIENTS

INGREDIENT	% WEIGHT	TLV-PPM	mg/m3
Ethylene Glycol (CAS 107-21-1)	1.6	50 (Ceiling)	
Silica/Silicates (CAS 14464-46-1) CAS 14807-96-6)	12.7-28.2	10 OSHA Pel 2.0 ACGIH TLV	
Phenyl Mercuric Acetate (CAS 62-38-40)	.01	.10	

PHYSICAL DATA**BOILING RANGE:** 212 ° F **VAPOR DENSITY:** Heavier than air **EVAPORATION RATE:** Slower than ether **PERCENT VOLATILE BY VOLUME:** 58.2-62.1 **WEIGHT PER GALLON:** 11.07 - 11.42 lbs**FIRE AND EXPLOSION HAZARD DATA**

This Section Not Applicable

HEALTH HAZARD DATA**THRESHOLD LIMIT VALUE:** See Hazardous Ingredients **EFFECTS OF OVEREXPOSURE:** Not known. Some irritation of eyes, respiratory tract and skin may occur. Ingestion may result in nausea or abdominal pain. **EMERGENCY AND FIRST AID PROCEDURES:** Ingestion: Induce vomiting. Notify a physician. Eye Contact: Flush with water. Notify a physician. Skin Contact: Wash with soap and water. Contaminated clothing should be removed and washed prior to reuse. Inhalation: Remove to fresh air. Restore breathing if necessary. Contact physician.**REACTIVITY DATA****STABILITY:** Stable **INCOMPATIBILITY:** None **HAZARDOUS DECOMPOSITION PRODUCTS:** None **HAZARDOUS POLYMERIZATION:** Will not occur. **CONDITIONS TO AVOID:** None**SPILL OR LEAK PROCEDURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Ventilate area. Soak up spill with absorbent material (sawdust). Smaller spills may be flushed with water and drained in a manner acceptable to local, state, and federal laws. **WASTE DISPOSAL METHOD:** Dispose in accordance with local, state, and federal laws.**SPECIAL PROTECTION INFORMATION****RESPIRATORY PROTECTION:** None usually required. Concentrated areas or spray application may require NIOSH approved chemical respirator (TC23C) to remove airborne particles and vapors during application. **VENTILATION:** Local exhaust to maintain TLV of most hazardous ingredient (SEE HAZARDOUS INGREDIENTS) below acceptable limit. **PROTECTIVE GLOVES:** Yes, **EYE PROTECTION:** Safety glasses designed to protect eyes from liquid splash. **OTHER PROTECTIVE EQUIPMENT:** Eye Bath/Safety Shower.**SPECIAL PRECAUTIONS****PRECAUTIONS TO BE TAKEN WHEN HANDLING AND STORING:** Keep from Freezing. **OTHER PRECAUTIONS:** None.