

Diamond Liqui-Tool Chemicals/Rawn Chemicals

Material Safety Data Sheet



IDENTITY Liqui-Tool®	1414-12, F	reon*	22 Dus	t-Λ-Way			
Section I							
Manufacturer's Name RAWN COMPANY, INC.				Emergency Telephone Number Daytime (715) 635-8711 After Hours (715) 635-8102			
Address (Number, Street, City, State, and ZIP Code) P.O. Box 9				Telephone Number for Information (715) 635-8711			
Hwy. 53 South				Date Prepared 5-21-90, Revised			
Spooner, WI 54801				Signature of Preparer Nobert Michon			
Section II — Hazardous Ingredient	s/Identity Info	ormatio	n	_			
Hazardous Components	CAS#	OSHA PEL .		ACGIA LV	Other Limits Recommended (STEL)		
Chlorodifluoromethane	75-45-6	1000	ppm	.3 3500 mg/m	not establ	•	
						· · · · · · · · · · · · · · · · · · ·	
					:		
						•	
Section III — Physical/Chemical Chara	teristics						
Boiling Point *F	-41.4	Specific Gravity (H ₂ O = 1) (at 77° F.) 1.194			1.194		
Vapor Pressure (mm Hg.) (at 77° F.)	7046	Melting I	Melting Point n/a				
Vapor Density (AIR = 1) (at 77° F.)	3.03	Evaporation Rate (KXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX					
Solubility in Water 0.30% at 77° F.							
Appearance and Odor Clear, colorle	ess, liqui	fied o	as, sl	ight ether	eal odor.		
Section IV — Fire and Explosion Hazard			· · · · · · · · · · · · · · · · · · ·				
Flash Point (Method Used) None (TOC)			Flammable Limits LEL UEL n/a			uEL n/a	
Extinguishing Media As appropriate	for surr	oundir	a comb	ustibles.		·	
Special Fire Fighting Procedures					red if contai	ners	
rupture and release cont					ainers with w		
Have and Evaluation Hazards				ainer failure			
and flame may cause deco							

Section V	- Reactivity Data	
Stability	Unstable	Conditions to Avoid
	Stable	X Avoid high temperatures, open flame.
Incompatibili	ty (Materials to Avoid) AVO:	id contact with alkali or alkaline earth metals, powdered Al, Zn,
	Be and so forth.	
Hazardous Do	ecomposition or By products	Hydrochloric and hydrofluoric acids, possibly carbonyl halides.
Hazardous	May Occur	Conditions to Avoid
Polymenzation	Will Not Occur	X n/a
Section VI	— Health Hazard Data	
See Attachme	en!	
	This product of	does not contain any ingredients classified as carcinogenic
	by NTP, LARC,	
	- Precautions for Safe	
Steps to Be Ta	aken in Case Material is Releas	Remove open flames, ventilate area, especially low
	places. Product ev	aporates rapidly.
	•	
Waste Dispos	at Method Comply with	all Federal, State and local regulations.
	,	
Precautions to	Be Taken in Handling and Sto	Store away from high temperatures, open flames, and
	incompatibles. Sto	re out of direct sunlight. Store under 125° F.
Other Precaut	ions Avoid prolonged	breathing of vapors, contact with skin and eyes. Use with
	adequate ventilation	
Section VIII	- Control Measures	
		required with normal use. Wear a NIOSH approved self-contained
	respirator for orga	nic vapors if TLV is exceeded, an air-supplied respirator
		or extreme concentrations.
/entilation		ge amounts are released Special n/a
	Mechanical (General)	in low places Other n/a
rotective Glov	es Lined butyl gl	Fire Protection
Other Protectiv		Wear as needed to prevent prolonged or repeated skin contact
	during use.	
Work/Hygienic		enic practices include washing hands after use, before eating,
		with coan and water

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS.

HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

EYE

Irritant - frostbite is possible.

SKIN

Frostbite is possible.

INHALATION

Inhalation of high concentrations of vapors is harmful and can cause heart irregularities, unconsciousness, or death. Intentional misuse can be fatal. Vapor reduces oxygen available for breathing and is heavier than air.

INGESTION

Not considered a likely route for exposure.

SUBCHRONIC AND CHRONIC EFFECTS OF OVEREXPOSURE

Toxic effects described in animals from exposure by inhalation, ingestion or skin contact include central nervous system effects, anesthetic effects, cardiovascular effects, lung effects, liver effects, kidney effects, and spleen effects. In a 2 year inhalation study, a significantly increased incidence of salivary gland tumors was observed in male rats exposed to a 5% concentration of Freon® 22. Tests for mutagenic activity in bacterial or mammilian cell structures have been inconclusive, with positive results in some studies, and negative results in others. Tests in some animals indicate that the compound may have embryotoxic activity, but only at maternally toxic concentrations. Tests in animals demonstrate no reproductive toxicity.

Human health effects of overexposure by inhalation, ingestion, skin or eye contact may initially include central nervous system effects. Higher exposures may lead to temporary alteration of the heart's electrical activity with irregular pulse, palpitations, or inadequate circulation; or fatality from gross overexposure. Freon® 22 vaporized quickly at ambient temperatures; therefor, data available to evaluate the skin permeation hazard of this compound are insufficient. There are no reports of human sensitation.

CARCINOGENICITY

This product is not listed as a carcinogen by MTP, IARC, OSHA or ACGIH.

FIRST AID AND EMERGENCY PROCEDURES

ΤΝΉΑΤ.ΑΥΤΟΝ

Remove victim to fresh air. If not breathing, administer artificial respiration, preferably mouth-to-mouth. If breathing is difficult, call a physician.

SKIN CONTACT

Flush effected area with water. Treat for frostbite if necessary.

EYE CONTACT

Immediately flush eyes with plenty of water. Call a physician.

INGESTION

Not considered a likely route for exposure.

NOTE TO PHYSICIAN

Because of possible disturbances of cardiac rythm, catecholamine drugs such as epinephrine should be used with special caution in situations of emergency life support.

Note: Inhalation 0.25 hour IC50 - 350,000 ppm for rats.