

Material Safety Data Sheet  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910, 1200, Standard must be  
 consulted for specific requirements.

OCT 18 1991

U.S. Department of Labor  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

NJ/PA/US

IDENTITY (As Used on Label and List)	Note: Blank spaces not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--------------------------------------	---


**LIQUID DEFOAMER**

<b>Section I</b>	
Manufacturer's Name <b>PALMER COMPANY</b>	Emergency Telephone Number <b>800-843-6174</b>
Address (Number, Street, City, State, and ZIP Code) <b>1201 Sentry</b>	Telephone Number for information <b>(414) 547-2246</b>
<b>Waukesha, WI 53186</b>	Date Prepared <b>January, 1991</b>
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information	N.A. = Not Applicable	N.E. = Not Established	Other Limits Recommended	% (optional)
Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV		
<b>Water</b>	<b>CAS #7732-18-5</b>	<b>N.E.</b>	<b>N.E.</b>	<b>N.A.</b>
<b>Silicone emulsion</b>	<b>CAS # N/A</b>	<b>N.A.</b>	<b>N.A.</b>	<b>N.A.</b>

This mixture does not contain components which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR, Part 372.

<b>Section III - Physical/Chemical Characteristics</b>			
Boiling Point	<b>212°F</b>	Specific Gravity (H <sub>2</sub> O = 1)	<b>1.013</b>
Vapor Pressure (mm Hg.)	<b>&lt;37</b>	Melting Point	<b>N.A.</b>
Vapor Density (AIR = 1)	<b>&lt; 1</b>	Evaporation Rate (Butyl Acetate = 1)	<b>&lt;0.4</b>
Solubility in Water <b>Miscible emulsion</b>			
Appearance and Odor <b>Milky Liquid</b>			

<b>Section IV - Fire and Explosion Hazard Data</b>									
Flash Point (Method Used) <b>None</b>	Flammable Limits <b>N.A.</b>	LEL <b>N.A.</b>	UEL <b>N.A.</b>						
Extinguishing Media <b>Use media proper to primary cause of fire</b>									
Special Fire Fighting Procedures <b>None</b>									
Unusual Fire and Explosion Hazards <b>None</b>		<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;">HAZARD RATING</td> <td style="width: 50%; border: none;">4 = Extreme</td> </tr> <tr> <td style="border: none;">3 = High</td> <td style="border: none;">2 = Moderate</td> </tr> <tr> <td style="border: none;">1 = Slight</td> <td style="border: none;">0 = Insignificant</td> </tr> </table>		HAZARD RATING	4 = Extreme	3 = High	2 = Moderate	1 = Slight	0 = Insignificant
HAZARD RATING	4 = Extreme								
3 = High	2 = Moderate								
1 = Slight	0 = Insignificant								

**DOT HAZARD CLASSIFICATION: Non-Hazardous**  
 (Reproduce locally)

OSHA 174, Sept. 19

