



Gillette Medical Evaluation Laboratories

401 Professional Drive
Gaithersburg, Maryland 20879
301-590-9781

Handwritten: H. J. ...
C. ...

MATERIAL SAFETY DATA SHEET

NAME: LIQUID PAPER JUST FOR COPIES CORRECTION FLUID

CAS NO: NA

Effective Date: 8/22/90 Rev: 4

A. - IDENTIFICATION

Composition* Titanium Dioxide (13463-67-7) Water (7732-18-5) Polymer Ethyl Alcohol (64-17-5) Methyl Alcohol (67-56-1) Colorants, Dispersants	%	Formula: Mixture
		Molecular Weight: NA
		Synonyms: Just for Copies

B. - PHYSICAL DATA

Boiling Point NA °F NA °C	Melting Point NA °F NA °C	Freezing Point NA °F NA °C
Specific Gravity (H ₂ O=1) ~1.5	Vapor Density (air=1) NA	Vapor Pressure @ _____ °F NA mmHg
Evaporation (_____ =1) NA	Saturation in Air (by volume @ _____ °F) NA %	Autoignition Temperature NA °F NA °C
% Volatiles (by volume) ~40	Solubility in Water NA	pH NA

Appearance/Odor White fluid with a slight alcohol odor

Flash Point and Test Method(s) 86°F (Closed Cup)

Flammable Limits in Air (% by volume) Lower NA % Upper NA %

C. - REACTIVITY

Stability	Conditions to Avoid	Polymerization	Conditions to Avoid
stable X	Open flame. High temperature sources.	may occur	NA
unstable		will not occur X	
Incompatible Materials Strong oxidizers		Hazardous Decomposition Products Thermal degradation, e.g. open flame, can produce oxides of carbon and nitrogen.	

*IF MULTIPLE INGREDIENTS INCLUDE CAS NUMBERS FOR EACH NA=NOT AVAILABLE

Footnotes:

NA

D. — HEALTH HAZARD DATA

Occupational Exposure Limits (PEL'S, TLV'S, etc.)

8 Hour TWA's: Ethyl Alcohol - 1000 ppm (OSHA/ACGIH)
Methyl Alcohol - 200 ppm (OSHA/ACGIH - skin notation)
Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

Routes, Effects of Exposure

1. Inhalation

No adverse effects anticipated from normal use.

2. Ingestion

No adverse effects anticipated from normal use. Ingestion may produce gastric irritation, as well as other symptoms of alcohol toxicity.

3. Skin

a. Contact

Mild irritation may occur if contact is prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use.

4. Eye Contact

Irritation

5. Other

NA

E. — ENVIRONMENTAL IMPACT

1. Applicable Regulations

2. DOT Hazard Class —

NA

3. DOT Shipping Name —

Environmental Effects

NA

F. — EXPOSURE CONTROL METHODS

Engineering Controls

None under normal use conditions.

Eye Protection

None under normal use conditions.

Skin Protection

None under normal use conditions.

Respiratory Protection

None under normal use conditions.

Other

Product is non-hazardous when used as directed in an office/room with normal air circulation.

G. — WORK PRACTICES

Handling and Storage

No unusual handling or storage when used as directed. When stored in large quantities (as in warehouse), it should be in a well ventilated, cool area.

Normal Clean Up

Pick up spills with towels, tissues, etc.

Waste Disposal Methods

Dispose in accordance with applicable federal, state and local laws.

H. — EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area

Not applicable

Fire and Explosion Hazard

As with dilute alcohol

Extinguishing Media

Carbon dioxide, dry chemical, foam, water fog.

Firefighting Procedures

In fires involving large quantities of product, self-contained breathing apparatus should be used.

I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use.

Ingestion

Consult physician.

Notes to Physician

Ethyl alcohol contains t-butyl alcohol and brucine sulfate as denaturants.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.