VENUU55



MATERIAL SAFETY DATA SHEET LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 1 • Product and Company Identification

Product Name:

LPS[®] PF[®] Solvent

Part Number:

61400, 61410, 61432, 61401, 61405, 61420 (aerosol), 61455, 61456, C61400, C61410,

C61432, C61401, C61405, C61420 (aerosol), C61455, C61456

Chemical Name:

Petroleum Hydrocarbon

Product Use:

A solvent agent designed for removing grease, oil and other residues from metal, power

cable and fiber optic cable surfaces.

Manufacturer Information:

LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084

TEL:

1 770-243-8800

Emergency Telephone

Number:

1-800-424-9300 Chemtrec; Outside U.S.: (703) 527-3887

1 770-243-8899

FAX: Website:

http://www.lpslabs.com.

Section 2 • Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Emergency Overview: DANGER: Combustible Liquid. Harmful or fatal if swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Potential Acute Health Effects:

Eyes Irritating to eyes

Skin Repeated exposure may cause skin dryness or cracking.

Inhalation: Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

Ingestion: Ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if

aspirated into lungs.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No

Mutagenic Effects: None Teratogenic Effects: None

Medical conditions aggravated by exposure: Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.



LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 3 • Composition / Information on Ingredients

Component	CASRN	Percent by Weight
Isoparaffinic hydrocarbon	64742-48-9	80 - 100
d-limonene	5989-27-5	5 - 10
Carbon dioxíde (aerosol only)	124-38-9	1 - 5

Section 4 · First Aid Measures

Eyes:

Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.

Skin:

Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do

not use ointments. Seek medical attention if irritation persists.

Inhalation:

Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical

attention immediately.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended.

Seek medical attention immediately.

Section 5 • Fire Fighting Measures

Products of Combustion: Carbon monoxide and carbon dioxide.

Firefighting media: SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to

prevent pressure build-up, autoignition or explosions.

Sensitivity to Impact: None. Sensitivity to Static Discharge: None.

Protection Clothing (Fire): Firefighters must use full bunker gear including NIOSH-approved positive pressure selfcontained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

Special Remarks on Explosion Hazards: High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers. Aerosols may explode upon heating, spread fire and overcome sprinkler systems.



LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 6 • Accidental Release Measures

Containment Procedures Contain and recover spilled liquid when possible.

Clean-Up Procedures

Small Spill and Leak:

Absorb with an inert material and dispose of properly.

Large Spill and Leak:

Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for

later disposal.

Evacuation Procedures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away.

Special Procedures

Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment during

cleanup.

Section 7 • Handling and Storage

Handling: DO NOT spray into or around ignition sources. Do not allow material to come into contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Do not breathe vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

Precautions to be taken in handling and storage: Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in dry, well-ventilated area. Avoid breathing vapors.

Section 8 • Exposure Controls / Personal Protection

Exposure Guidelines:

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH-TLV	ACGIH-STEL	NIOSH REL
Isoparaffinic hydrocarbon	64742-48-9	171 ppm*	Not Established	Not Established	Not Established	Not Established
d-limonene	5989-27-5	Not Established	Not Established	Not Established	Not Established	Not Established
Carbon Dioxide (aerosol only)	124-38-9	5000 ppm	30000 ppm	5000 ppm	30000 ppm	5000 ppm TWA 30000 ppm STEL

^{*} Supplier Recommendation



LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Engineering measures

Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines

listed above.

Personal protective equipment

Eye protection

Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and

emergency shower facilities are recommended.

Hand protection

Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, use chemical resistant gloves (i.e., nitrile) conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough

time that are provided by the supplier of the gloves.

Respiratory protection

Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above),

use NIOSH approved respiratory protection (i.e., organic vapor cartridge).

General Hygiene Considerations

Wash throughly after handling. Have eye-wash facilities immediately available.

Section 9 • Physical and Chemical Properties					
Appearance:	Liquid.	Color:	Colorless / water-white		
Odor/Taste:	Orange	Vapor Pressure:	0.48 mmHg at 20°C		
Solubility Description:	Negligible	Evaporation Rate:	<0.1 (BuAc=1)		
Boiling Point:	185°C (365°F)	Flash Point:	>61°C (142°F)		
Specific Gravity (Water=1):	@ 760mmHg 0.74-0.78 @ 20°C	Flash Point Method:	Tag-Closed Cup.		
Vapor Density (air=1):	>1	Auto Ignition Temperature (°C):	335°C(635°F)		
V.O.C. Content:	100%, 760 g/L, 6.34 #/gal. Per C.A.R.B / O.T.C. and S.C.A.Q.M.D. Rule 102	Partition Coefficient (octanol/water):	Not Determined		
Flammable limits (estimated):	LOWER: 0.7% UPPER: 5.3%	Volatiles:	100%		
Viscosity:	1,5 cSt @ 25°C	pH:	Not applicable		



MATERIAL SAFETY DATA SHEET LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 10 • Stability and Reactivity

Chemical Stability:

Product is stable under recommended storage conditions.

Conditions to Avoid:

Keep away from heat and ignition sources.

Incompatibility:

Reactive or incompatible with oxidizing agents.

Hazardous Decomposition:

These products are carbon oxides (CO, CO2)

Hazardous Polymerization:

Will not occur.

Section 11 • Toxicological Information

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

Component	CASRN	LC-50	LD-50
Isoparaffinic hydrocarbon	64742-48-9	Not established	Not Established
d-limonene	5989-27-5	Not established	>5000 mg/kg (oral, rabbit) >5000 mg/kg (demal, rabbit)
Carbon Dioxide (aerosol only)	124-38-9	Not established	Not Appropriate

Section 12 • Ecological Information

Mobility:

algae

fish

Bioaccumulation in

Highly volatile. Not expected to partition to sediment.

Persistence and degradability:

Readily biodegradable

Bioaccumulative potential:

No bioaccumulation potential

Other adverse effects:

None known.

Ecotoxicology:

Effect on Organisms	Component	CASRN	Test	Species	Results
	d-limonene	5989-27-5	4-day LC50	Oncorhynchus mykiss	35,000 µg/L
Acute Toxicity on Fishes d-limonene		5989-27-5	96-hour ECso	Pimephales promelas	1,490,000 µg/L
Acute Toxicity on Daphnia					
Bacterial inhibition			No Data Ava	ilable	
Growth inhibition of			NO Data Ava	ili mara	



MATERIAL SAFETY DATA SHEET LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 13 • Disposal Considerations

Waste Status:

In its purchased form, non-aerosol material does not meet the definition of a RCRA hazardous waste. Aerosol products, if depressurized and emptied to less than 2.5 cm of fluid contents are classified as non-hazardous waste under 40 CFR 261.7 (U.S.). However, if disposed of in its received form, an

aerosol carries waste code D003. (U.S.)

Disposal:

Waste must be disposed of in accordance with federal, state, provincial, and local environmental

control regulations.

Note:

Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and

local waste disposal requirements may be more restrictive than federal laws and regulations.

Section 14 • Transport Information

<u>Aerosol</u>

	Shipping Name:	Consumer Commodity	UN Number:	NA
D.O.T. Ground	Hazard Class:	ORM-D	Technical Name:	NA
	Subclass:	NA NA	Hazard Label:	ORM-D Already on box
	UN no:	1950	ADR Class:	2
	Packing group:	NA	Classification code:	5F
Road/Rail - ADR/RID :	Name and Description:	AEROSOLS, Flammable	Hazard ID no:	NA
	Labeling:	2.1		
16BIMDG-IMO	UN no:	1950	Class:	2.1
	Shipping Name:	AEROSOLS	Subsidiary Risk:	2.1
	Packing instructions:	P003, LP02	Packing group:	NA
	Marine pollutant:	NO	EmS:	F-D, S-U
IATA-ICAO:	UN no:	1950	Class:	2.1
	Shipping Name:	AEROSOLS, Flammable	Subclass	NA
	Packing instructions:	203, Y203 (Ltd. Qty.)	Packing group:	NA
	Labeling:	Flammable Gas		

Bulk versions of this product are not regulated by any mode of transportation.



I PS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 15 • Regulatory information

U.S. Federal Regulations RCRA Hazardous Waste No.: None.

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): None

Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title IIISARA Section 311/312 (40 CFR 370) Hazard Categories: Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): No individual section 313 component is present at or above 1%

Section 112 Hazardous Air Pollutants (HAPs): None

State Regulations

New Jersey RTK:

Aerosol: Isoparaffinic Hydrocarbon 64742-48-9 ● d-Iimonene 5989-27-5 ● Carbon Dioxide 124-38-9

Bulk: Isoparaffinic Hydrocarbon 64742-48-9 • d-limonene 5989-27-5

California: This product does not contain chemical(s) known to the State of California to cause cancer, birth defects or reproductive harm.

California and OTC States: This product conforms to consumer regulations.

International Regulations

Canadian Environmental Protection Act: All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System (WHMIS):

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification: Aerosol Class A, Class B5, Class D2B







WHMIS Classification: Bulk Class B3, Class D2B





Other Regulations

Montreal Protocol listed ingredients: Stockholm Convention listed ingredients: Rotterdam Convention listed ingredients: RoHS Compliant:

None.

None.

None.

Yes.



LPS® PF® Solvent

Revision 5

Revision Date: 3/12/2009

Supercedes: 11/25/08

Section 16 • Other Information

	HMIS 1996		HMIS III		NFPA	
MSDS# 161420 Responsible Name:	Health:	1	Health:	[/]1	Flammability	
Clea Johnson Regulatory Affairs Coordinator	Flammability:	2	Flammability: aerosol Flammability: bulk	2	Health 1 0 Reactivity	
	Reactivity 0	0	Physical Hazard: aerosol Physical Hazard: bulk	0		

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea Johnson, Regulatory Affairs Coordinator LPS Laboratories, A division of Illinois Tool Works