

Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

Product Division:

IPG

LUBE-ALL (AEROSOL) Product Number: 6730

1110 Spartan Drive

Spartan Chemical Company, Inc.

Product/Technical I-(800)-537-8990 Information:

Medical Emergency:1-(888)-314-6171 (24 hours)

Chemical Leak/Spil CHEMTREC 1-(800) 424-9300 (24 hours)
Emergency:

Maumee, OH 43537

	Emergency.			
Shipping Description: ORM-D, Consumer commodity, cleaning compounds, aerosol, n.o.s.				
NFPA Ratings:		HMIS Ratings:		
Health:	1- Slight	Health:	*1 - Slight; Chronic Hazard	
Fire:	3 - Serious	Fire:	3 - Serious	
Reactivity:	1- Slight	Reactivity:	1- Slight	
		Pers. Prot. Equip.:	See Section VIII	

**SECTION II: HAZARDOUS INGREDIENTS
(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from

listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z- 1 - A			NTP, IARC
		CAS Registry	_		CELING	or OSHA
Chemical Name(s)	% W	No.	TWA mg/m ³	STEL mg/m ³	mg/m ³	Carcinogen
Petroleum distillate	20-30	64741-89-5	5 (oil mist)	Not Established	Not Established	No
Petroleum distillate	20-30	64741-88-4	5 (oil mist)	Not Established	Not Established	No
Petroleum distillate	10-15	64742-47-8	Not Established	Not Established	Not Established	No
Petroleum distillate	10-15	64742-52-5	5 (oil mist)	Not Established	Not Established	No
Propane	10-15	74-98-6	1800	Not Established	Not Established	No
Isobutane	10-15	75-28-5	1800 (ACGIH)	Not Established	Not Established	No
Petroleum distillate	1-5	64742-65-0	5 (oil mist)	Not Established	Not Established	No
Polytetrafluorethylene	< 1.0	9002-84-0	5 (respirable dust - Dupont)	Not Established	Not Established	No

▼ SECTION III: PHYSICAL DATA

Boiling Point:	> 200 °F	Vapor Pressure:	Unknown	
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Negligible	
pH:		Specific Gravity (H ₂ O=1):		
Evaporation Rate (but.ace.=1):		Percent Solid by Weight:	1-5	
Physical State:	Aerosol can (pressurized liquid)			
Appearance & Odor: Oily liquid, negligible fragrance				

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	Propellant: < 0 °F	Method Used:	Estimate
	Not established Lower Explosive Limit: 0.6 % Upper Explosive Limit: 9.5%		> 28 Inches NFPA 30B Level 3 Aerosol
	Carbon dioxide, Dry chemical,		
Special Fire Fighting Procedures	Water may be used to cool clos autoignition or explosion when pressure self contained breathin	exposed to extreme heat. V	Vear a full face positive
Unusual Fire & Explosive Hazards	Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electrical motors, static discharge or other ignition sources at locations distant from material handling point.		

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established		Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure- Conditions to Avoid: Harmful or Fatal if Swallowed. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. Harmful if Inhaled. Inhalation of vapors may cause central nervous system effects including dizziness, weakness, fatigue, nausea & headache. Prolonged exposure to propellant vapors above the OSHA permissible exposure limits may result in kidney liver damage. The intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Causes Eye & Skin Irritation. Symptoms include pain, redness, swelling of the conjunctiva and tearing. Avoid breathing product vapors or mists. Avoid contact with eyes and skin. Do not swallow. Wash thoroughly after handling. Conditions Aggravated by Use: Use of this product may aggravate preexisting skin; eye and respiratory disorders		ral nervous system effects e. Prolonged exposure to limits may result in kidney and entrating and inhaling the a, redness, swelling of the ors or mists. Avoid contact after handling.	
Conditions Aggravated by Use:	Use of this product may aggraincluding asthma and dermatit	vate preexisting skin; eye ar is.	nd respiratory disorders

Emergency & First Aid Procedures:

11	Flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Wash thoroughly with soap and water. Get medical attention if irritation persists.
Ingestion:	Do not induce vomiting. Call a physician immediately.
Inhalation:	Move person to fresh air. Get medical attention if irritation persists.

SECTION VI: REACTIVITY DATA

Stability:	Stable		Avoid contact with strong oxidizing agents; strong alkalis and strong mineral acids.
Products:	Burning can produce carbon monoxide, carbon dioxide and phosgene gas	1	Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Ventilate area. Remove all sources of ignition. Clean up with inert materials and dispose of in accordance with all local, state and federal regulations.
	Do not puncture or incinerate aerosol containers. Empty containers may be disposed of through normal channels. Full or partially filled containers are considered hazardous waste.

SECTION VIII: SPECIAL PROTECTION INFORMATION

	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered.
	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Wear impervious gloves for prolonged or repeated contact.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further reference.

SECTION IX: SPECIAL PRECAUTIONS

Storing:	Do not puncture or incinerate container. Do not use or store product near heat, sparks or open flame. Do not store in direct sunlight or above 120 F. High temperatures may cause container to burst. Wash thoroughly after handling.
Other Precautions:	Keep out of reach of children.

© SCC 01/25/2005

Name:

Ronald T. Cook

Title:

Manager, Regulatory Affairs

LUBE-ALL (AEROSOL)

Effective Date:

01/25/2005

Supercedes: 10/04/2001

Ref: 29 CFR 1910.1200 (OSHA) Changes:

Revised formulation

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.