PAGE: 1

DATE: 04/25/91 INDEX: N/A

ACCT: 888328-01 CAT NO: M49500

PO NBR: N/A

\*\*MAGNESIUM OXIDE\*\* \*\*MAGNESIUM OXIDE\*\*
\*\*MAGNESIUM OXIDE\*\*

MATERIAL SAFETY DATA SHEET

FISHER SCIENTIFIC CHEMICAL DIVISION 1 REAGENT LANE FAIR LAWN NJ 07410 (201) 796-7100 EMERGENCY NUMBER: (201) 796-7100 CHEMTREC ASSISTANCE: (800) 424-9300

THIS INFORMATION IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES.

SUBSTANCE IDENTIFICATION

SUBSTANCE: \*\*MAGNESIUM OXIDE\*\*

CAS-NUMBER 1309-48-4

TRADE NAMES/SYNONYMS:
MAGNESIUM OXIDE (MGO); MAGNESIA; MAGNESIUM MONOXIDE; MAGLITE 4; ANSCOR-PE;
CALCINED MAGNESIA; ELASTO MAG 20; ELASTO MAG 170SIA; MAGNESIA (MGO);
M51; M3494; M300; MG0; ACC13450

CHEMICAL FAMILY: METAL OXIDE

MOLECULAR FORMULA: MG-0

MOLECULAR WEIGHT: 40.31

CERCLA RATINGS (SCALE 0-3): HEALTH=3 FIRE=0 REACTIVITY=0 PERSISTENCE=0 NFPA RATINGS (SCALE 0-4): HEALTH=U FIRE=0 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: MAGNESIUM OXIDE CAS# 1309-48-4

PERCENT: 100.0

EXPOSURE LIMITS:

MAGNESIUM OXIDE (FUME):
10 MG/M3 OSHA TWA (TOTAL PARTICULATE)
10 MG/M3 ACGIH TWA

PHYSICAL DATA

DESCRIPTION: ODORLESS, FINE WHITE POWDER. BOILING POINT: 6512 F (3600 C)

MELTING POINT: 5160 F (2852 C) SPECIFIC GRAVITY: 3.58 @ 25 C

SOLUBILITY IN WATER: SLIGHTLY SOLUBLE PH: 10.3 @ SATURATED SOL

SOLVENT SOLUBILITY: SOLUBLE IN DILUTE ACIDS AND AMMONIUM SALT SOLUTIONS, INSOLUBLE IN ALCOHOL

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD:
NEGLIGIBLE FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

FIREFIGHTING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR FOAM FOR LARGER FIRES. USE WATER SPRAY, FOG OR ALCOHOL FOAM

NO ACUTE HAZARD. MOVE CONTAINER FROM FIRE AREA IF POSSIBLE. AVOID BREATHING VAPORS OR DUSTS; KEEP UPWIND.

## TOXICITY

MAGNESIUM OXIDE:
TOXICITY DATA: 400 MG/M3 INHALATION-HUMAN TCLO; TUMORIGENIC DATA (RTECS).
CARCINOGEN STATUS: NONE. CARTINGEN STAIDS: NONE., ACUTE TOXICITY LEVEL: INSUFFICIENT DATA.

TARGET EFFECTS: NO DATA AVAILABLE.

AT INCREASED RISK FROM EXPOSURE: PERSONS WITH A HISTORY OF CHRONIC RESPIRATORY DISEASE.



DATE . 04/25/91 INDEX: N/A

ACCT: 888328-01 CAT NO: M49500

PO NBR: N/A

PAGE: 2

ADDITIONAL DATA: INTERACTIONS WITH MEDICATIONS HAVE BEEN REPORTED.

HEALTH EFFECTS AND FIRST AID

INHALATION: MAGNESIUM OXIDE:

IAĞNESIUM OXIDE:

ACUTE EXPOSURE- THE DUST MAY CAUSE RESPIRATORY TRACT IRRITATION. METAL FUME
FEVER, AN INFLUENZA-LIKE ILLNESS, MAY OCCUR IF FRESHLY FORMED MAGNESIUM
OXIDE FUMES COMPOSED OF PARTICLES SIZED BETWEEN O.02-0.05 MICRONS ARE
INHALED IN SUFFICIENT AMOUNTS. SYMPTOMS MAY BE DELAYED 4-12 HOURS AND
BEGIN WITH A SUDDEN ONSET OF THIRST, AND A SWEET, METALLIC OR FOUL TASTE
IN THE MOUTH. OTHER SYMPTOMS MAY INCLUDE UPPER RESPIRATORY TRACT
IRRITATION ACCOMPANIED BY COUGHING AND A DRYNESS OF THE MUCOUS MEMBRANES,
LASSITUDE AND A GENERALIZED FEELING OF MALAISE. FEVER CHILLS, MUSCULAR
PAIN, MILD TO SEVERE HEADACHE, NAUSEA, OCCASIONAL VOMITING, EXAGGERATED
MENTAL ACTIVITY, PROFUSE SWEATING, EXCESSIVE URINATION, DIARRHEA,
PROSTRATION AND LEUKOCYTOSIS MAY ALSO OCCUR. TOLERANCE TO FUMES DEVELOPS
RAPIDLY, BUT IS QUICKLY LOST. ALL SYMPTOMS USUALLY SUBSIDE WITHIN 24-36
HOURS. HOURS

CHRONIC EXPOSURE- MAY CAUSE RESPIRATORY TRACT IRRITATION, NASAL CATARRH AND COUGHING UP OF DISCOLORED SPUTUM. THERE IS NO EVIDENCE OF LUNG INJURY FROM INHALATION OF MAGNESIUM DUST.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

MAGNESIUM OXIDE: ACUTE EXPOSURE- NO DATA AVAILABLE. CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

ACUTE EXPOSURE- MAY CAUSE SLIGHT IRRITATION, REDNESS AND PAIN. CHRONIC EXPOSURE- REPEATED OR PROLONGED EXPOSURE MAY CAUSE CONJUNCTIVITIS.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: MAGNESIUM OXIDE:

AGNESIUM OXIDE:
ACUTE EXPOSURE- MAY CAUSE DIARRHEA. MAGNESIUM SALTS ARE GENERALLY SO SLOWLY
ABSORBED THAT ORAL ADMINISTRATION CAUSES NOTHING MORE THAN PURGING. IF
EVACUATION FAILS, MUCOSAL IRRITATION AND ABSORPTION MAY OCCUR.
SYSTEMICALLY, MAGNESIUM MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION,
ABOLITION OF REFLEXES AND DEATH FROM RESPIRATORY PARALYSIS.
CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD LOWER THAN HIPS TO PREVENT ASPIRATION.

ANTIDOTE

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

MAGNESIUM OXIDE: ABSORBS MOISTURE AND CARBON DIOXIDE FROM THE AIR.

INCOMPATIBILITIES:

MAGNESIUM OXIDE: AGNESIUM OXIDE:
ACIDS (STRONG): VIOLENT REACTION.
ACIDS (STRONG): VIOLENT REACTION.
ALUMINUM POWDER: MAY IGNITE OR EXPLODE WHEN HEATED.
BROMINE PENTAFLUORIDE: VIOLENT REACTION.
CHLORINE TRIFLUORIDE: MAY IGNITE.
INTERHALOGENS: INCOMPATIBLE.
MAGNESIUM POWDER: MAY IGNITE OR EXPLODE WHEN HEATED.
PHOSPHORUS PENTACHLORIDE: INCANDESCES BRILLIANTLY ON HEATING.
SULFUR (SUBLIMED): MAY IGNITE OR EXPLODE WHEN HEATED.

THERMAL DECOMPOSITION MAY RELEASE TOXIC AND/OR HAZARDOUS GASES.

POLYMERIZATION: HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL DATE: 04/25/91 INDEX: N/A

ACCT: 888328-01 CAT NO: M49500

PAGE: 3

PO NBR: N/A

TEMPERATURES AND PRESSURES.

STORAGE AND DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE, FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

\*\*STORAGE\*\*

STORE AWAY FROM INCOMPATIBLE SUBSTANCES

CONDITIONS TO AVOID

NONE REPORTED.

\* SPILL AND LEAK PROCEDURES

SWEEP UP AND PLACE IN SUITABLE CLEAN, DRY CONTAINERS FOR RECLAMATION OR LATER DISPOSAL. DO NOT FLUSH SPILLED MATERIAL INTO SEWER. KEEP UNNECESSARY PEOPLE

PROTECTIVE EQUIPMENT

PROVIDE LOCAL EXHAUST VENTILATION SYSTEM TO MEET PUBLISHED EXPOSURE LIMITS.

THE FOLLOWING RESPIRATORS AND MAXIMUM USE CONCENTRATIONS ARE RECOMMENDATIONS BY THE U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES, NIOSH POCKET GUIDE TO CHEMICAL HAZARDS; NIOSH CRITERIA DOCUMENTS OR BY THE U.S. DEPARTMENT OF

CHEMICAL HAZARDS; NIOSH CRITENIA DOCUMENTS OR BY THE U.S. DEPARTMENT UPLABOR, 29 CFR 1910 SUBPART Z.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

FOR MAGNESIUM OXIDE FUME:

100 MG/M3- ANY DUST, MIST AND FUME RESPIRATOR WITH A FULL FACEPIECE.
ANY SUPPLIED-AIR RESPIRATOR.
ANY SELF-CONTAINED BREATHING APPARATUS.

250 MG/M3- ANY SUPPLIED-AIR RESPIRATOR OPERATED IN A CONTINUOUS FLOW MODE.

ANY POWERED AIR-PURIFYING RESPIRATOR WITH A DUST, MIST AND FUME FILTER.

500 MG/M3- ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

PARTICULATE FILLER.
ANY SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE.
ANY SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE.
ANY POWERED AIR-PURIFYING RESPIRATOR WITH A TIGHT-FITTING
FACEPIECE AND A HIGH-EFFICIENCY PARTICULATE.

7500 MG/M3- ANY SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE AND OPERATED IN A PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

ESCAPE- ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER. ANY APPROPRIATE ESCAPE-TYPE SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

ANY SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

ANY SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. CLOTHING: EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY

PAGE: 4

JATE: 04/25/91 INDEX: N/A ACCT: 888328-01 CAT NO: M49500

PO NBR: N/A

PU NBR: N/A

BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED - FISHER SCIENTIFIC, INC.
CREATION DATE: 10/10/84 REVISION DATE: 01/08/91

-ADDITIONAL INFORMATIONTHIS INFORMATION IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST
INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF
MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO
SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS
SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE
INFORMATION FOR THEIR PARTICULAR PURPOSES.