

damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Hazmat Sorbents

Page 5 of 5
Revision Date: 06/01/01
MSDS No. 3

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, KOLLECT-A-KEM®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of NPS Corporation
AQUALOCKIT™, TRUK-KIT™, DRAINGUARD™, GAPSEAL™, MEDICLEAN™, and TIDYMAT™, are all trademarks of NPS Corporation

Copyright 2001, NPS Corporation

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
MERCORB® Mercury Amalgamation Powder

Page 1 of 5
Revision Date: 10/01/01
MSDS No. 64

Section 1. Chemical Product and Company Identification

Product Number: 5200 Series
Product Name: MERCORB® Mercury Amalgamation Powder

Manufacturer:
NPS Corporation
3303 Spirit Way
Green Bay, WI 54304

Emergency Telephone Numbers:
CHEMTREC--Domestic (800)424-9300 24 hours
--International (202)483-7616 24 hours
Information (800) 558-5066 7:30am-4:30pm CDT M-F

Section 2. Composition/Information on Ingredients

CAS Registry #	Component
7440-66-6	Zinc Dust
77-92-9	Citric Acid

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

Section 3. Hazards Identification

☆☆☆☆☆☆☆☆☆☆ Emergency Overview ☆☆☆☆☆☆☆☆☆☆
☆Odorless, very fine, blue, gray, or white powder. Zinc dust reacts with water ☆
☆evolving hydrogen. The heat of the reaction may ignite the hydrogen. ☆
☆☆

Potential Health Effects

Eye: May cause irritation.
Skin: May cause irritation. Repeated skin contact may aggravate an existing dermatitis (skin condition) and/or sensitivity of the skin.
Inhalation: Exposure to dust levels exceeding the PEL (see Section 8) may irritate the nose, throat, and upper respiratory system.
Signs and Symptoms:

- Eyes: Redness, Tearing, Possible burns
- Skin: Redness, Swelling, Possible burns
- Inhalation: Discomfort of the nose and throat, headache, fever, chills, muscle aches, nausea, and tiredness. These symptoms may persist for 6 to 24 hours.

Section 4. First Aid Measures

Eyes: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.
Skin: Remove contaminated clothing. Brush off excess powder with a dry towel. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion: If swallowed, call a physician or poison control center immediately.

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Sorbent Powder

Page 2 of 5
Revision Date: 06/01/01
MSDS No. 64

Section 5. Fire Fighting Measures

Flash Point: Not Tested
Flammable Limits: Lower Explosive Limit (LEL): 13.6 g/ft³ Upper Explosive Limit: NA
Auto-ignition Temperature: NA
Extinguishing Media: Rock dust or dry sand
Special Fire Fighting Procedures: For large fires or fires in confined areas, full emergency equipment with self-contained breathing apparatus and full protective clothing should be used. Dry zinc dust will not ignite spontaneously, but once ignited, it may burn readily in air. Thermal decomposition of this product may produce carbon monoxide and carbon dioxide.

Section 6. Accidental Release Measures

Avoid breathing or generating airborne dust. Avoid contact with skin and eyes. If unused material is spilled, collect by sweeping, shoveling or vacuuming and recycle the material for use. If this product is mixed with other materials, see Section 13.

Section 7. Handling and Storage

Store in a cool, dry, and well ventilated area. Keep container tightly closed. Avoid contact with materials listed in Section 10. Keep away from flammable materials and sources of heat or flame.

Section 8. Exposure Controls/Personal Protection

Exposure Limits: None specifically established for this product; treat as a nuisance dust as defined in 29 CFR 1910.1000.

OSHA PEL: Total Zinc Dust is 15 mg/M³.
Respirable Fraction, Zinc Dust, is 5mg/M³.

ACGIH TLV is 10mg/M³.

The end-user must determine the specific types of personal protective equipment needed according to 29 CFR 1910.132—Personal Protective Equipment (PPE) for General Industry. The following are only suggestions:

- Eyes: Safety glasses or goggles
- Skin: Suitable chemically resistant gloves and protective clothing
- Inhalation: Air purifying respirator with appropriate chemical cartridge or canister

Adequate ventilation should be provided to limit the threat of inhalation.

Section 9. Physical and Chemical Properties

Appearance: Very fine blue, gray, or white powder
Odor: Odorless
Boiling Point: 1666 °F
Vapor Pressure (mmHg): NA
Vapor Density: NA
Solubility in Water: Reacts with water
Specific Gravity (H₂O=1): 7.11
Melting Point: 787 °F
pH: 1.18—1% aqueous solution

Evaporation Rate (Butyl Acetate=1): NA
% Vaporizable by volume (H₂O=100): NA

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Sorbent Powder

Page 3 of 5
Revision Date: 06/01/01
MSDS No. 64

Section 10. Stability and Reactivity

Stable: Yes
Conditions to Avoid: Contact with water or damp air due to the evolution of hydrogen.
Incompatibility (Materials to Avoid): Liquid acids and bases, cyanides, sulfides, and hypochlorites.
Hazardous Decomposition or Byproducts: Thermal decomposition of this material may produce carbon monoxide and carbon dioxide.
Hazardous Polymerization: Will not occur

Section 11. Toxicological Information

This product is not listed by NTP or IARC. See Section 15.

Section 12. Ecological Information

No data available. See Section 15.

Section 13. Disposal Considerations

This product in itself is considered to be non-hazardous as defined by RCRA (40 CFR 261). Once used, this product may take on the characteristics of the chemical(s) it was used with and should be disposed of accordingly. Disposal of this product (used or unused) must be in compliance with all local, state, and federal regulations.

Section 14. Transport Information

DOT:
Proper Shipping Name: Corrosive solids, n.o.s. (contains Citric Acid)
Hazard Class: 8
Packing Group: III
Identification Number: 1759

Section 15. Regulatory Information

The zinc dust in this product is considered to be non-hazardous by the Office of Hazardous Materials Management (49 CFR Sections 172.101 and 173.124).

TSCA Inventory Status: All components are listed on the TSCA list.
SARA Title III

Section 302 Extreme Hazardous Substance List: Not listed

Section 311/312 Hazard Classification:

Immediate (acute): Yes

Delayed (chronic): Yes

Fire: No

Sudden Release of Pressure: No

Reactive: No

Section 313 Toxic Chemicals: Listed—Zinc Powder or Dust—1%

USEPA CERCLA—Reportable Quantity (RQ): Not listed

RCRA Hazardous Waste: Not listed

State/Int'l Right-to-Know Regulations: Canada's WHMIS—Citric Acid 1%

Section 16. Other Information

Abbreviations:
CFR: Code of Federal Regulations
OSHA: Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Sorbent Powder

Page 4 of 5
Revision Date: 06/01/01
MSDS No. 64

Abbreviations (cont.):

MSDS: Material Safety Data Sheet
PEL: Permissible Exposure Limit
NA: Not Applicable
ACGIH: American Conference of Governmental Industrial Hygienists
TLV: Threshold Limit Value
NTP: National Toxicology Program
IARC: International Agency for Research on Cancer
RCRA: Resource Conservation and Recovery Act
TSCA: Toxic Substances Control Act
SARA: Superfund Amendments and Reauthorization Act
USEPA: United States Environmental Protection Agency
CERCLA: Comprehensive Response, Compensation, and Liability Act
DOT: Department of Transportation
WHMIS: Workplace Hazardous Materials Information System
n.o.s.: Not Otherwise Specified
NFPA: National Fire Protection Association
HMIS: Hazardous Material Information System

NFPA Ratings:

Health: 0
Fire: 1
Reactivity: 1
Special Hazard: Avoid Water

HMIS Ratings:

Health: 0
Flammability: 1
Reactivity: 1
Personal Protection: X

NOTE: This MSDS has been prepared only for the Mercury Sorbent Powder (5200 Series) of SPILFYTER® Products. The MSDS's of the chemicals used with this product must be reviewed completely, and precautions taken as described.

The information accumulated herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, NPS Corporation cannot give guarantees regarding the information from sources, and expressly does not make any warranties, nor assumes any liability for its uses of this product.

Disclaimer

You have purchased SPILFYTER® products from NPS Corporation
You have been provided data, product labels, MSDS's, and other information about SPILFYTER® Products.

Some SPILFYTER® Products are hazardous. Information about SPILFYTER® Products that are hazardous is furnished without guarantee. NPS Corporation does not guarantee the accuracy of the information about hazardous SPILFYTER® Products.

Those products are only to be used by people having expertise in using the hazardous products.

The information provided about the hazardous products is believed to be correct. You must perform your investigation as to the safety, toxicity, suitability, and proper shipping method for any hazardous SPILFYTER® Product.

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Sorbent Powder

Page 5 of 5
Revision Date: 06/01/01
MSDS No. 64

No guarantee, expressed or implied, is made by NPS Corporation about the results of use of its products. No guarantee is made as to the safety and toxicity of any SPILFYTER® Product.

NPS Corporation does not assume any liability arising out of use of SPILFYTER® Products. Additional information and research may be necessary before you use the SPILFYTER® Products. NPS Corporation is not responsible for damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, KOLLECT-A-KEM®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of NPS Corporation
AQUALOCKIT™, TRUK-KIT™, DRAINGUARD™, GAPSEAL™, MEDICLEAN™, and TIDYMAT™ are all trademarks of NPS Corporation

Copyright 2001, NPS Corporation