

MATERIAL SAFETY DATA SHEET

FEB 18 2003

SPILFYTER® Products
Mercury Indicator Powder

Page 1 of 5
Revision Date: 07/07/00
MSDS No. 14

Section 1. Chemical Product and Company Identification

18999949

Product Number: 5230 Series
Product Name: Mercury Indicator Powder

Manufacturer:
J.V. Manufacturing Co., Inc.
963 Ashwaubenon Street
Green Bay, WI 54304

Emergency Telephone Numbers:
CHEMTREC--Domestic (800)424-9300 24 hours
--International (202)483-7616 24 hours
Information (800)334-9092 7am-5pm CDT M-F

Section 2. Composition/Information on Ingredients

CAS Registry #	Component
7704-34-9	Sulfur
112926-00-8	Silicon Dioxide
-- NA --	Proprietary Ingredient

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

Section 3. Hazards Identification

☆☆☆☆☆☆☆☆☆☆ Emergency Overview ☆☆☆☆☆☆☆☆☆☆☆

☆Odorless, yellowish-tan to gray powder. Dust may form a flammable or ☆

☆explosive mixture in air. When heated to decomposition, toxic fumes of sulfur☆

☆oxides are produced. ☆

☆☆

Potential Health Effects

- Eye: May cause irritation.
- Skin: May cause irritation.
- Inhalation: May cause irritation to the upper respiratory system.
- Signs and Symptoms:
 - Eyes: Redness, Tearing
 - Skin: Redness
 - Inhalation: Discomfort of the nose and throat, Dry cough.

Section 4. First Aid Measures

- Eyes: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.
- Skin: Remove contaminated clothing. Brush off excess powder with a dry towel. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.
- Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
- Ingestion: If swallowed, call a physician or poison control center immediately.

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Indicator Powder

Page 2 of 5
Revision Date: 07/07/00
MSDS No. 14

Section 5. Fire Fighting Measures

Flash Point: 370 °F

Flammable Limits: Not Tested

Auto-ignition Temperature: NA

Extinguishing Media: Use water spray, alcohol foam, dry chemical, or carbon dioxide.

Special Fire Fighting Procedures: For large fires or fires in confined areas, full emergency equipment with self-contained breathing apparatus and full protective clothing should be used. When heated to decomposition toxic fumes of sulfur oxides are formed. Dust may form a flammable or explosive mixture in air.

Section 6. Accidental Release Measures

Avoid breathing or generating airborne dust. Avoid contact with skin and eyes. If unused material is spilled, collect by sweeping, shoveling or vacuuming and recycle the material for use. If this product is mixed with other materials, see Section 13.

Section 7. Handling and Storage

Store in a cool, dry, and well ventilated area. Keep container tightly closed. Avoid contact with materials listed in Section 10. Keep away from flammable materials and sources of heat or flame.

Section 8. Exposure Controls/Personal Protection

Exposure Limits: Silicon Dioxide:
OSHA PEL is 20 Mppcf.
ACGIH TLV is 10 mg/M³.
Proprietary Ingredient:
OSHA PEL is 1.0 mg/ M³.
ACGIH TLV is 1.0 mg/ M³.
Sulfur:
OSHA PEL: Not Established
ACGIH TLV: Not Established

The end-user must determine the specific types of personal protective equipment needed according to 29 CFR 1910.132—Personal Protective Equipment (PPE) for General Industry. The following are only suggestions:

- Eyes: Safety glasses or goggles
- Skin: Suitable chemically resistant gloves and protective clothing
- Inhalation: Air purifying respirator with appropriate chemical cartridge or canister

Adequate ventilation should be provided to limit the threat of inhalation.

Section 9. Physical and Chemical Properties

Appearance: Yellowish-tan to gray powder

Odor: Odorless

% Vaporizable by volume (H₂O=100): NA

Boiling Point: 833 °F

Vapor Pressure (mmHg): Not Tested

Vapor Density: 8.8

Solubility in Water: Negligible (<0.1%)

Specific Gravity (H₂O=1): 2.00

Melting Point: 240 °F

pH: 5.9

Evaporation Rate (Butyl Acetate=1): NA

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Indicator Powder

Page 3 of 5
Revision Date: 07/07/00
MSDS No. 14

Section 10. Stability and Reactivity

Stable: Yes

Conditions to Avoid: Heating to decomposition.

Incompatibility (Materials to Avoid): Strong oxidizers, most common metals, hydrogen, chlorine, fluorine, and organic materials at elevated temperatures.

Hazardous Decomposition or Byproducts: Thermal decomposition produces toxic fumes of sulfur oxides.

Hazardous Polymerization: Will not occur

Section 11. Toxicological Information

This product is not listed by NTP or IARC. See Section 15.

Section 12. Ecological Information

No data available. See Section 15.

Section 13. Disposal Considerations

This product in itself is considered to be non-hazardous as defined by RCRA (40 CFR 261). Once used, this product may take on the characteristics of the chemical(s) it was used with and should be disposed of accordingly. Disposal of this product (used or unused) must be in compliance with all local, state, and federal regulations.

Section 14. Transport Information

This product is not a DOT Hazardous Material and is not regulated for all shipping purposes.

Section 15. Regulatory Information

TSCA Inventory Status: All components are listed on the TSCA list.

SARA Title III

Section 302 Extreme Hazardous Substance List: Not listed

Section 311/312 Hazard Classification:

Immediate (acute): Yes

Delayed (chronic): Yes

Fire: No

Sudden Release of Pressure: No

Reactive: No

Section 313 Toxic Chemicals: Listed—Copper—1%

USEPA CERCLA—Reportable Quantity (RQ): Listed—Copper—5000 lbs

RCRA Hazardous Waste: Not listed

State/Int'l Right-to-Know Regulations: Canada's WHMIS—Copper 1%

Section 16. Other Information

Abbreviations:

CFR: Code of Federal Regulations

OSHA: Occupational Safety and Health Administration

MSDS: Material Safety Data Sheet

PEL: Permissible Exposure Limit

NA: Not Applicable

Mppcf: Millions of particles per cubic foot

ACGIH: American Conference of Governmental Industrial Hygienists

TLV: Threshold Limit Value

NTP: National Toxicology Program

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products

Mercury Indicator Powder

Page 4 of 5

Revision Date: 07/07/00

MSDS No. 14

Abbreviations (cont.):

IARC: International Agency for Research on Cancer

RCRA: Resource Conservation and Recovery Act

TSCA: Toxic Substances Control Act

SARA: Superfund Amendments and Reauthorization Act

USEPA: United States Environmental Protection Agency

CERCLA: Comprehensive Response, Compensation, and Liability Act

DOT: Department of Transportation

WHMIS: Workplace Hazardous Materials Information System

NFPA: National Fire Protection Association

HMIS: Hazardous Material Information System

NFPA Ratings:

Health: 2

Fire: 1

Reactivity: 0

Special Hazard: None

HMIS Ratings:

Health: 2

Flammability: 1

Reactivity: 0

Personal Protection: X

NOTE: This MSDS has been prepared only for the Mercury Indicator Powder (5230 Series) of SPILFYTER® Products. The MSDS's of the chemicals used with this product must be reviewed completely, and precautions taken as described.

The information accumulated herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, J.V. Manufacturing Co., Inc. cannot give guarantees regarding the information from sources, and expressly does not make any warranties, nor assumes any liability for its uses of this product.

Disclaimer

You have purchased SPILFYTER® products from J.V. Manufacturing Co., Inc.

You have been provided data, product labels, MSDS's, and other information about SPILFYTER® Products.

Some SPILFYTER® Products are hazardous. Information about SPILFYTER® Products that are hazardous is furnished without guarantee. J.V. Manufacturing Co., Inc. does not guarantee the accuracy of the information about hazardous SPILFYTER® Products.

Those products are only to be used by people having expertise in using the hazardous products.

The information provided about the hazardous products is believed to be correct. You must perform your investigation as to the safety, toxicity, suitability, and proper shipping method for any hazardous SPILFYTER® Product.

No guarantee, expressed or implied, is made by J.V. Manufacturing Co., Inc. about the results of use of its products. No guarantee is made as to the safety and toxicity of any SPILFYTER® Product

MATERIAL SAFETY DATA SHEET

SPILFYTER® Products
Mercury Indicator Powder

Page 5 of 5
Revision Date: 07/22/99
MSDS No. 14

J.V. Manufacturing Co., Inc. does not assume any liability arising out of use of SPILFYTER® Products. Additional information and research may be necessary before you use the SPILFYTER® Products. J.V. Manufacturing Co., Inc. is not responsible for damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, ARG-DRI®, ARG-VARK®, KOLLECT-A-KEM®, LOCKIT®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of J.V. Manufacturing Co., Inc. AQUALOCKIT™, HY-PRO™, TRUK-KIT™, DRAINGUARD™, GAPSEAL™, MEDICLEAN™, TIDYMAT™, and SORB-A-STRIP™ are all trademarks of J.V. Manufacturing Co., Inc.

Copyright 1999, J.V. Manufacturing Co., Inc.
