

# MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
Mercury Indicator Powder

Page 1 of 5  
Revision Date: 10/01/01  
MSDS No. 14

## Section 1. Chemical Product and Company Identification

Product Number: 5230 Series  
Product Name: Mercury Indicator Powder

**Manufacturer:**  
NPS Corporation  
3303 Spirit Way  
Green Bay, WI 54304

**Emergency Telephone Numbers:**  
CHEMTREC--Domestic (800)424-9300 24 hours  
--International (202)483-7616 24 hours  
Information (800) 558-5066 7:30am-4:30pm CDT M-

F

## Section 2. Composition/Information on Ingredients

CAS Registry #	Component
7704-34-9	Sulfur
112926-00-8	Silicon Dioxide
-- NA --	Proprietary Ingredient

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

## Section 3. Hazards Identification

\*\*\*\*\* Emergency Overview \*\*\*\*\*  
\*Odorless, yellowish-tan to gray powder. Dust may form a flammable or \*  
\*explosive mixture in air. When heated to decomposition, toxic fumes of sulfur \*  
\*oxides are produced. \*  
\*\*\*\*\*

### Potential Health Effects

Eye: May cause irritation.

Skin: May cause irritation.

Inhalation: May cause irritation to the upper respiratory system.

Signs and Symptoms:

- Eyes: Redness, Tearing
- Skin: Redness
- Inhalation: Discomfort of the nose and throat, Dry cough.

## Section 4. First Aid Measures

Eyes: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Brush off excess powder with a dry towel. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion: If swallowed, call a physician or poison control center immediately.

# MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
Mercury Indicator Powder

Page 2 of 5  
Revision Date: 05/25/01  
MSDS No. 14

## Section 5. Fire Fighting Measures

Flash Point: 370 °F

Flammable Limits: Not Tested

Auto-ignition Temperature: NA

Extinguishing Media: Use water spray, alcohol foam, dry chemical, or carbon dioxide.

Special Fire Fighting Procedures: For large fires or fires in confined areas, full emergency equipment with self-contained breathing apparatus and full protective clothing should be used. When heated to decomposition toxic fumes of sulfur oxides are formed. Dust may form a flammable or explosive mixture in air.

## Section 6. Accidental Release Measures

Avoid breathing or generating airborne dust. Avoid contact with skin and eyes. If unused material is spilled, collect by sweeping, shoveling or vacuuming and recycle the material for use. If this product is mixed with other materials, see Section 13.

## Section 7. Handling and Storage

Store in a cool, dry, and well ventilated area. Keep container tightly closed. Avoid contact with materials listed in Section 10. Keep away from flammable materials and sources of heat or flame.

## Section 8. Exposure Controls/Personal Protection

Exposure Limits: Silicon Dioxide:

OSHA PEL is 20 Mppcf.

ACGIH TLV is 10 mg/M<sup>3</sup>.

Proprietary Ingredient:

OSHA PEL is 1.0 mg/ M<sup>3</sup>.

ACGIH TLV is 1.0 mg/ M<sup>3</sup>.

Sulfur:

OSHA PEL: Not Established

ACGIH TLV: Not Established

The end-user must determine the specific types of personal protective equipment needed according to 29 CFR 1910.132—Personal Protective Equipment (PPE) for General Industry. The following are only suggestions:

- Eyes: Safety glasses or goggles
- Skin: Suitable chemically resistant gloves and protective clothing
- Inhalation: Air purifying respirator with appropriate chemical cartridge or canister

Adequate ventilation should be provided to limit the threat of inhalation.

## Section 9. Physical and Chemical Properties

Appearance: Yellowish-tan to gray powder

Odor: Odorless

% Vaporizable by volume (H<sub>2</sub>O=100): NA

Boiling Point: 833 °F

Vapor Pressure (mmHg): Not Tested

Vapor Density: 8.8

Solubility in Water: Negligible (<0.1%)

Specific Gravity (H<sub>2</sub>O=1): 2.00

Melting Point: 240 °F  
pH: 5.9  
Evaporation Rate (Butyl Acetate=1): NA

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
Mercury Indicator Powder

Page 3 of 5  
Revision Date: 05/25/01  
MSDS No. 14

### Section 10. Stability and Reactivity

Stable: Yes  
Conditions to Avoid: Heating to decomposition.  
Incompatibility (Materials to Avoid): Strong oxidizers, most common metals, hydrogen, chlorine, fluorine, and organic materials at elevated temperatures.  
Hazardous Decomposition or Byproducts: Thermal decomposition produces toxic fumes of sulfur oxides.  
Hazardous Polymerization: Will not occur

### Section 11. Toxicological Information

This product is not listed by NTP or IARC. See Section 15.

### Section 12. Ecological Information

No data available. See Section 15.

### Section 13. Disposal Considerations

This product in itself is considered to be non-hazardous as defined by RCRA (40 CFR 261). Once used, this product may take on the characteristics of the chemical(s) it was used with and should be disposed of accordingly. Disposal of this product (used or unused) must be in compliance with all local, state, and federal regulations.

### Section 14. Transport Information

This product is not a DOT Hazardous Material and is not regulated for all shipping purposes.

### Section 15. Regulatory Information

TSCA Inventory Status: All components are listed on the TSCA list:  
SARA Title III  
Section 302 Extreme Hazardous Substance List: Not listed  
Section 311/312 Hazard Classification:  
Immediate (acute): Yes  
Delayed (chronic): Yes  
Fire: No  
Sudden Release of Pressure: No  
Reactive: No  
Section 313 Toxic Chemicals: Listed—Copper—1%  
USEPA CERCLA—Reportable Quantity (RQ): Listed—Copper—5000 lbs  
RCRA Hazardous Waste: Not listed  
State/Int'l Right-to-Know Regulations: Canada's WHMIS—Copper 1%

### Section 16. Other Information

Abbreviations:  
CFR: Code of Federal Regulations  
OSHA: Occupational Safety and Health Administration  
MSDS: Material Safety Data Sheet  
PEL: Permissible Exposure Limit  
NA: Not Applicable

Mppct: Millions of particles per cubic foot  
ACGIH: American Conference of Governmental Industrial Hygienists  
TLV: Threshold Limit Value  
NTP: National Toxicology Program

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
Mercury Indicator Powder

Page 4 of 5  
Revision Date: 05/25/01  
MSDS No. 14

### Abbreviations (cont.):

IARC: International Agency for Research on Cancer  
RCRA: Resource Conservation and Recovery Act  
TSCA: Toxic Substances Control Act  
SARA: Superfund Amendments and Reauthorization Act  
USEPA: United States Environmental Protection Agency  
CERCLA: Comprehensive Response, Compensation, and Liability Act  
DOT: Department of Transportation  
WHMIS: Workplace Hazardous Materials Information System  
NFPA: National Fire Protection Association  
HMIS: Hazardous Material Information System

### NFPA Ratings:

Health: 2  
Fire: 1  
Reactivity: 0  
Special Hazard: None

### HMIS Ratings:

Health: 2  
Flammability: 1  
Reactivity: 0  
Personal Protection: X

**NOTE:** This MSDS has been prepared only for the Mercury Indicator Powder (5230 Series) of SPILFYTER® Products. The MSDS's of the chemicals used with this product must be reviewed completely, and precautions taken as described.

The information accumulated herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, NPS Corporation cannot give guarantees regarding the information from sources, and expressly does not make any warranties, nor assumes any liability for its uses of this product.

### Disclaimer

You have purchased SPILFYTER® products from NPS Corporation.  
You have been provided data, product labels, MSDS's, and other information about SPILFYTER® Products.

Some SPILFYTER® Products are hazardous. Information about SPILFYTER® Products that are hazardous is furnished without guarantee. NPS Corporation does not guarantee the accuracy of the information about hazardous SPILFYTER® Products.

Those products are only to be used by people having expertise in using the hazardous products.

The information provided about the hazardous products is believed to be correct. You must perform your investigation as to the safety, toxicity, suitability, and proper shipping method for any hazardous SPILFYTER® Product.

No guarantee, expressed or implied, is made by NPS Corporation about the results of use of its products. No guarantee is made as to the safety and toxicity of any SPILFYTER® Product

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
Mercury Indicator Powder

Page 5 of 5  
Revision Date: 05/25/01  
MSDS No. 14

NPS Corporation does not assume any liability arising out of use of SPILFYTER® Products. Additional information and research may be necessary before you use the SPILFYTER® Products. NPS Corporation is not responsible for damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, KOLLECT-A-KEM®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of NPS Corporation  
AQUALOCKIT™, TRUK-KIT™, DRAINGUARD™, GAPSEAL™, MEDICLEAN™, and TIDYMAT™ are all trademarks of NPS Corporation

Copyright 2001, NPS Corporation

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
Vapor Suppressor

Page 1 of 5  
Revision Date: 10/01/01  
MSDS No. 55

### Section 1. Chemical Product and Company Identification

Product Number: 4600 Series  
Product Name: Vapor Suppressor

**Manufacturer:**  
NPS Corporation  
3303 Spirit Way  
Green Bay, WI 54304

**Emergency Telephone Numbers:**  
CHEMTREC--Domestic (800)424-9300 24 hours  
--International (202)483-7616 24 hours  
Information (800) 558-5066 7:30am-4:30pm CDT M-F

### Section 2. Composition/Information on Ingredients

CAS Registry #	Component
7440-44-0	Activated Carbon
7704-34-9	Sulfur

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

### Section 3. Hazards Identification

\*\*\*\*\* Emergency Overview \*\*\*\*\*  
\*Odorless, black, irregular, dry granular solid. Wet activated carbon removes \*  
\*oxygen from the air causing a severe hazard to workers inside carbon vessels \*  
\*and enclosed or confined spaces. Before entering such an area, sampling and \*  
\*work procedures for low oxygen levels should be taken to ensure ample \*  
\*oxygen availability, observing all local, state, and federal regulations. \*  
\*\*\*\*\*

#### Potential Health Effects

Eye: May cause irritation.  
Skin: May cause irritation. Repeated skin contact may aggravate an existing dermatitis (skin condition) and/or sensitivity of the skin.  
Inhalation: Exposure to dust levels exceeding the PEL (see Section 8) may cause irritation of the upper respiratory system.  
Signs and Symptoms:  
• Eyes: Redness, Tearing  
• Skin: Redness, Swelling  
• Inhalation: Dry cough

### Section 4. First Aid Measures

Eyes: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.  
Skin: Remove contaminated clothing. Brush off excess powder with a dry towel. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.  
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.