MINOLTA

MATERIAL SAFETY DATA SHEET

MSDS NO. MCR-105 DATE PREP. 05/8/92 PAGE 1 of 3

MINOLTA CORPORATION 101 WILLIAMS DRIVE RAMSEY, NJ 07446

EMERGENCY TEL. NO.

CONTACT YOUR REGIONAL

POISON CONTROL CENTER

INFORMATION TEL. NO.

201-825-4000

SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT: MT STARTER (N-P)

EQUIPMENT NO. RP600Z, RP605Z, RP606Z,

RP607Z

SECTION 2 - PRODUCT AND COMPONENT HAZARD DATA

INGREDIENT	CAS NO.	OSHA PEL-TWA	ACGIH TLV-TWA	%
Carrier				>90
Ferrite		N.AP.	N.AP.	
Polyester resin		N.AP.	N.AP.	
Carbon black	1333-86-4	3.5mg/m3	3.5mg/m3	
Amorphous silica	7631-86-9	N.AP.	N.AP.	
Toner		•		<10
Styrene acrylate copolymer (2 kinds)		N.AP.	N.AP.	
Carbon black	1333-86-4	3.5mg/m3	3.5mg/m3	
Amorphous silica	7631-86-9	N.AP.	N.AP.	
As total nuisance dust		15mg/m3	10mg/m3	
Charatan a minter	/	1 ,		

Starter, as a mixture, is considered a nuisance dust.

HMIS RATING: HEALTH: 0

FLAMMABILITY: 1

REACTIVITY: 1

SECTION 3 - EMERGENCY AND FIRST AID

INHALATION: Wash nostrils, rinse mouth.

INGESTION: Dilute stomach contents with several glasses of water.

EYES

: Flush with water for 15 minutes.

SKIN : Wash with soap and water.

PRIMARY ROUTE OF ENTRY: Inhalation

SYMPTOMS OF OVEREXPOSURE

ACUTE:

Minimal respiratory tract irritation may occur as with

exposure to large amounts of any nontoxic dust. May cause

cough and raise phlegm.

CHRONIC: None.

MINOLTA

MATERIAL SAFETY DATA SHEET

MSDS NO. MCR-105 DATE PREP. 05/8/92 PAGE 2 of 3

SECTION 4 - TOXICOLOGY AND HEALTH INFORMATION

HEALTH HAZARDS:

Toner presents a low hazard for usual occupational settings. Based on available data, human exposure to toner has been shown to cause minimal respiratory tract irritation as may occur with large amounts of any nontoxic dusts. The results of one animal study where rats inhaled toner that was ten times more respirable than commercially available toner were observed to have no lung changes at low exposures (the most relevant level to potential human exposures). At higher levels a slight degree of lung fibrosis was observed due to excessive amounts of dust retained in the lungs for a prolonged interval.

ORAL LD50

: >5.0g/kg (Rats)

DERMAL LD50 : >2.0g/kg (Rats) *t
INHALATION LC50: >9.8mg/m³ (Rats) for 4-hours

(This was the highest attainable concentration. There were no deaths

during the study.)

EYE IRRITANT

: Not an irritant. (Rabbits)

SKIN IRRITANT : Not an irritant. (Rabbits)

SKIN SENSITIZER: N.AV. MUTAGENICITY

: No mutagenicity detected in Ames Assay.

CARCINOGENICITY: NTP: Not listed IARC MONOGRAPHS: Not listed OSHA REGULATED: Not listed

SECTION 5 - PHYSICAL DATA

APPEARANCE AND ODOR : Black powder, faint odor

BOILING POINT (°C) : N.AP.

SPECIFIC GRAVITY (H₂O=1): about 3.0

VAPOR PRESSURE (mmHg): N.AP.

EVAPORATION RATE : N.AP.

VAPOR DENSITY (AIR=1): N.AP.

MELTING POINT (°C)

: N.AV.

SOLUBILITY IN WATER : Negligible

pH

: N.AP.

SECTION 6 - FIRE AND EXPLOSION DATA

FLASH POINT & METHOD: N.AP.

FLAMMABLE LIMITS IN AIR: LEL: N.AP. % UEL: N.AP. %

EXTINGUISHING MEDIA: Water, foam, dry chemical

SPECIAL FIREFIGHTING PROCEDURES: Avoid inhalation of smoke.

FIRE AND EXPLOSION HAZARDS: If dispersed in air, Starter, like most finely divided

organic powders, may form an explosive mixture.

MINOLTA

MATERIAL SAFETY DATA SHEET

MSDS NO. MCR-105 DATE PREP. 05/8/92 PAGE 3 of 3

SECTION 7 - REACTIVITY DATA

STABILITY:

UNSTABLE:

STABLE: ✓

CONDITIONS TO AVOID: None

INCOMPATIBILITIES: None

HAZARDOUS DECOMPOSITION BYPRODUCTS: Products of combustion are toxic. Avoid breathing

of smoke.

HAZARDOUS POLYMERIZATION:

MAY OCCUR:

WILL NOT OCCUR:

CONDITIONS TO AVOID: None

SECTION 8 - PERSONAL PROTECTION AND CONTROLS

VENTILATION:

LOCAL EXHAUST

: N.AP.

MECHANICAL (GENERAL): N.AP.

RESPIRATORY PROTECTION: None required when used as intended in Minolta equipment.

PROTECTIVE GLOVES

: None required when used as intended in Minolta equipment.

EYE PROTECTION

: None required when used as intended in Minolta equipment.

WORK PRACTICES

: None.

SECTION 9 - SAFE HANDLING AND USE PRECAUTIONS

HANDLING AND STORAGE: None

SECTION 10 - SPILL, LEAK, AND DISPOSAL PROCEDURES

FOR SPILLS AND LEAKAGE: If spilled, sweep up or vacuum.

WASTE DISPOSAL METHOD: Waste may be disposed or incinerated under conditions which meet

all federal, state and local environmental regulations.

SECTION 11 - TRANSPORTATION

D.O.T. SHIPPING NAME: Not regulated. HAZARD CLASSIFICATION: N.AP. I.D. NUMBER: N.AP.

*t(*c) :Based on toner (carrier) data

N.AP. :Not applicable N.AV. :Not available