S.C. Johnson Wax
Racine, Wisconsin 53403-5011
Phone: (414) 631-2777
Emergency Phone: (800) 228-5635
Extension 092
International Emergency Phone:
Extension 092

MATERIAL SAFETY DATA SHEET SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: OVER AND UNDER	DECITOR 1-PRODUCT IDENTIFICA	PRODUCT CODE: 14150-29-31 to 14154-29-31
	DATE ISSUED: SUPERSEDES: MSDS SECTIONS WITH C 07/02/92 05/04/92 No significa changes.	MANCEC. PREPARED DI

	SECTION II-INGREDIENT INFORMATION						
	INGREDIENTS	WEIGHT &	EXPOSURE LIMIT				
	Acrylic Polymers (CAS# N/ACAS)	10-20	NE				
	Diethylene Glycol Monoethyl Ether (CAS# 111-90-0CAS)	2-5	NOT ESTABLISHED				
	Tributoxyethyl Phosphate (CAS# 78-51-3)	under 2	NOT ESTABLISHED				
	[PA,NJ,MA] Ammonium Hydroxide (CAS# 1336-21-6)	1-2	25 PPM ACGIH/OSHA TWA; 35 PPM ACGIH/OSHA STEL				
	Water (CAS# 7732-18-5CAS)	75-85	NA.				
	[SARA,PA,NJ,MA] Dipropylene Glycol Methyl Ether (CAS# 34590-94-8)	1-3	100 PPM ACGIH/OSHA TWA, 150 PPM ACGIH/OSHA STEL, (SKIN)				
1	See Regulatory Information (Section KII) for explanation of bracketed information.						

HYSICAL DATA ECIFIC GRAVITY (H20=1): 1.03
RCENT VOLATILE BY VOLUME (%): NA
POR DENSITY (Air=1): NA
ILING POINT (°F): above 200
APORATION RATE (Butyl Acetate=1): ND
ORETICAL VOC (lb/gal): ND

FLASH POINT (°F) (Method Used):	ON IV-FIRE AND	EXPLOSION	INFORMATION
	TANA		
FLAMMABLE LIMITS: NA			
		·····	

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin 53403

OVER AND UNDER Product Number: 14150 Serial Number: 29-31

SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.) Foam. CO2. Dry Chemical. Water Fog. EXTINGUISHING MEDIA:

SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Cool and use caution when approaching or handling fire-exposed containers. MUSUAL FIRE AND EXPLOSION HAZARDS: Container may burst in heat of fire.

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact.

SIGHS AND SYMPTOMS: Direct contact of product with eyes may cause minor irritation. Prolonged or repeated contact of undiluted product with skin may cause minor irritation. FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. If product gets on skin, remove with soap and REDICAL COMDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

Persons with

pre-existing skin disorders may be more susceptible to irritating effects.

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

MAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

MAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contains ammonia and zinc. Do not let spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

MASTE DISPOSAL IMPORMATION: No special method. Observe all applicable Rederal/State regulations and Local ordinances regarding disposal of non-hazardous materials. Waste from normal product use may be sewered to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

MENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: If prolonged or repeated contact is possible: Any impervious material.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin

PRECAUTIONARY LABELING:

OVER AND UNDER Product Number: 14150 Serial Number: 29-31

SECTION VIII-SPECIAL PROTECTION INFORMATION (cont.) EYE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices.

SECTION IX-SPECIAL PRECAUTIONS

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Keep from freezing.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: EPA REGISTRATION #: NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Non hazardous

DOT #: NA

SHIPPING NAME: Buffing or polishing compounds, NOI.

SECTION XII-REGULATORY INFORMATION

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

- These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

SARA - These ingredients are subject to the reporting requirements under the Superfund Amendments and Reauthorization Act of 1986 Title III, Section 313 and 40 CFR Part 372.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined The information herein is given in good feith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use. R-106 (Rev 5 - 10/90)