



3661CR



Revised 10-JUN-1993

Printed 5-MAY-1994

"OXONE" MONOPERSULFATE COMPOUND

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

"OXONE" is a registered trademark of DuPont.

Corporate MSDS Number DU005614 70693-62-8 CAS Number POTASSIUM HYDROGEN PEROXYMONOSULFATE CAS Name **SULFATE TECHNICAL** Grade

Tradenames and Synonyms POTASSIUM PEROXYMONOSULFATE

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont

1007 Market Street Wilmington, DE 19898

PHONE NUMBERS

Product Information

1-800-441-9442

Transport Emergency

CHEMTREC: 1-800-424-9300

1-800-441-3637 Medical Emergency

COMPOSITION/INFORMATION ON INGREDIENTS

Components Material	CAS Number	%	
POTASSIUM PEROXYMONOSULFATE	10058-23-8	43	
POTASSIUM BISULFATE	7646-93-7	23	
POTASSIUM SULFATE	7778-80-5	32	
MAGNESIUM CARBONATE	546-93-0	2	

HAZARDS IDENTIFICATION

Potential Health Effects

Causes skin, eye, nose, and throat irritation. May cause allergic skin reactions at high concentrations in sensitive individuals. Ingestion may cause inflammation and damage to the lining of the stomach, resulting in bleeding.

HUMAN HEALTH EFFECTS:

Skin contact may cause skin irritation with discomfort or rash. Allergic skin reactions were observed at high concentrations, but at lower concentrations of 12 ppm and 150 ppm, no allergic reactions were noted. Eye contact may cause eye irritation with discomfort, tearing, or blurring of vision. Inhalation may cause irritation of the upper respiratory passages with coughing and discomfort. Ingestion may cause gastritis possibly progressing to necrosis or hemorrhage.

Individuals with preexisting diseases of the skin or gastrointestinal tract may have increased susceptibility to the toxicity of excessive exposures.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES

First Aid INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, ğive oxygen. Call a physician.

SKIN CONTACT

In case of contact, immediately wash skin with soap and water. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

FIRE FIGHTING MEASURES

Flammable Properties

Will not burn.

Fire and Explosion Hazards:

Storage of large masses of "OXONE" can trap heat and lead to ignition of paper bags. Grinding or intensive mixing may cause ignition of oxidizable material present.

Extinguishing Media

Water.

Fire Fighting Instructions

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Accidental Release Measures

Sweep up. Flush area with low pressure water.

HANDLING AND STORAGE

Handling (Personnel)

Avoid breathing dust. Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling.

Store in a cool, dry, well-ventilated area. Stack on pallets providing air space; closely stacked bags should not exceed a 4 ft. (1.2 m) cube. Keep packages dry. Do not store with combustible materials.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use sufficient ventilation to keep employee exposure below recommended limits.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses. Wear coverall chemical splash goggles and face shield when the possibility exists for eye or face contact from airborne material.

Page 3

RESPIRATORS

EXPOSURE CONTROLS/PERSONAL PROTECTION(Continued)

A NIOSH/MSHA approved air-purifying respirator with a dust/mist cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if here is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

PROTECTIVE CLOTHING

Wear impervious clothing, such as gloves, apron, boots or whole bodysuit, made of rubber, as appropriate. Leather gloves may be used when handling dry material.

Exposure Guidelines

Exposure Limits "OXONE" MONOPERSULFATE COMPOUND

PEL (OSHA) Particulates (Not Otherwise Regulated)

15 mg/m3, 8 Hr. TWA, total dust

5 mg/m3, 8 Hr. TWA, respirable dust

TLV (ACGIH) None Established AEL * (Du Pont) 1 mg/m3, 8 Hr. TWA

Other Applicable Exposure Limits

POTASSIUM SULFATE

PEL (OSHA) None Established TLV (ACGIH) None Established AEL * (Du Pont) 10 mg/m3, 8 Hr. TWA

MAGNESIUM CARBONATE

PEL (OSHA) 15 mg/m3, total dust, 8 Hr. TWA 5 mg/m3, respirable dust, 8 Hr. TWA TLV (ACGIH) 10 mg/m3, total dust, 8 Hr. TWA

AEL * (Du Pont) None Established

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Boiling Point @ 760 mm Hg Decomposes

Vapor Pressure Nil

Vapor Density Not volatile Melting Point Decomposes

Evaporation Rate (Butyl acetate = 1)

Not volatile

Solubility in Water 25.6 WT% @ 20 C (68 F)

рН 1% solution = 2.3; 3% solution = 2.0

Odor Odorless

Form Granular; free flowing solid

Color White

Specific Gravity 1.1-1.4

 $^{^{\}star}$ AEL is Du Pont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

STABILITY AND REACTIVITY

Chemical Stability

Stable.

Incompatibility with Other Materials
The mixture of "OXONE" with compounds containing halides or active halogens can cause release of the respective halogen if moisture is present. For example, mixture with sodium dichloroisocyanuride or with sodium chloride can cause release of chlorine gas; mixture with cyanides can cause release of hydrogen cyanide gas; and heavy metal salts such as those of cobalt, nickel, copper, or manganese cause the evolution of oxygen.

Decomposition

Releases oxygen gas.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION

Animal Data

Inhalation 4-hour LC50: >5 mg/l in rats

Skin absorption LD50 : >11,000 mg/kg in rabbits

: 2,000 mg/kg in rats Oral LD50

The compound is a severe skin and eye irritant, but is not a skin sensitizer in laboratory animals. Single inhalation exposures produced nonspecific effects such as weight loss and irritation. Repeated inhalation exposures produced eye irritation and reversible corneal damage. By ingestion, the administration of large single doses produced nonspecific effects such as weight loss and irritation as well as gastric ulceration, necrosis, and hemorrhage. The compound does not produce génetic damage in bacterial cell cultures.

ECOLOGICAL INFORMATION

Ecotoxicological Information

Aquatic Toxicity

Potassium Sulfate

96-hour Tlm, bluegill sunfish : 3,500 mg/L

Magnesium Carbonate

96-hour LC50, species unidentified: >1,000 ppm

(Continued)

Page 5 2661CD

DISPOSAL CONSIDERATIONS

Waste Disposal

Comply with Federal, State, and local regulations. If approved, flush to sewer or waste treatment plant. Large quantities should be neutralized with soda ash.

TRANSPORTATION INFORMATION

Shipping Information

NOT REGULATED AS A HAZARDOUS MATERIAL BY DOT OR IMO.

Shipping Containers

Multiwall Bags Fiber Pack Drums

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status Reported/Included.

TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

Acute : Yes Chronic : No Fire : No Reactivity: No Pressure : No

LISTS:

SARA Extremely Hazardous Substance - No CERCLA Hazardous Material - No SARA Toxic Chemical - No

CANADIAN WHMIS CLASSIFICATION:

D₂B

OTHER INFORMATION

NFPA, NPCA-HMIS NPCA-HMIS Rating

2 Health Flammability 0 Reactivity 1

Personal Protection rating to be supplied by user depending on use conditions.

Page 6

Additional Information

For further information, see DuPont "OXONE" Monopersulfate Compound Data Sheet.

(Continued)

3661CR

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

302-999-4946

Responsibility for MSDS Address

DuPont Chemicals Engineering & Product Safety P. O. Box 80709, Chestnut Run Wilmington, DE 19880-0709

Telephone

Indicates updated section.

End of MSDS

Page 7