



MATERIAL SAFETY DATA SHEET

<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;">Parafilm</div> <div style="display: flex; justify-content: space-between;"> <div style="width: 15%;"> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> </div> <div style="width: 80%;"> <input style="width: 95%; height: 20px;" type="text"/> <input style="width: 95%; height: 20px;" type="text"/> <input style="width: 95%; height: 20px;" type="text"/> </div> </div>	<p style="text-align: right; font-weight: bold;">JUN 28 2000</p> <div style="border: 1px solid black; width: 100px; height: 100px; margin: 0 auto; transform: rotate(45deg); display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; width: 30px; height: 30px;"></div> <div style="border: 1px solid black; width: 30px; height: 30px;"></div> </div> <p style="text-align: right; margin-top: 10px;">1337410 1337412 1337416</p>		
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%; padding: 2px;">MSDS:</td> </tr> <tr> <td style="padding: 2px;">DATE: 4-16-99</td> </tr> </table>		MSDS:	DATE: 4-16-99
MSDS:			
DATE: 4-16-99			

I. PRODUCT IDENTIFICATION

COMMON NAME: Parafilm "M"	CHEMICAL FORMULA:
SYNONYMS: See above	
TRADE NAMES:	
MANUFACTURER: PECHINEY PLASTIC PACKAGING	
SHIPPING NAME: DOT	IATA

II. HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT	%	TLV	(REMARKS)
Wax	56		
Polyolefin	44		

III. PHYSICAL DATA

BOILING POINT, 760mm Hg	Above 550°F.	MELTING POINT	65°C.
SPECIFIC GRAVITY (H ₂ O = 1)	<1	BULK DENSITY	N/A
pH (1% Soln.)	N/A	SOLUBILITY IN WATER	Negligible
% VOLATILES BY WEIGHT	N/A		
APPEARANCE & ODOR			

IV. FIRE AND EXPLOSION DATA

FLASH POINT (Test Method)	N/A	AUTOIGNITION TEMPERATURE	
FLAMMABLE LIMITS IN AIR, % BY VOLUME		LOWER:	UPPER:
EXTINGUISHING MEDIA	Use water fog, foam, dry chemical of CO ₂		
SPECIAL FIRE FIGHTING PROCEDURES	Do not enter confined fire space without proper protective equipment including a NIOSH approved self-contained breathing apparatus.		
UNUSUAL FIRE AND EXPLOSION HAZARD	Smoke produced from Parafilm "M" could generate Carbon Monoxide, Acrolein, Carbon Dioxide and unidentified organic compounds.		

V. HEALTH HAZARD INFORMATION

(REMARKS)

PRIMARY ROUTES OF EXPOSURE: SKIN CONTACT EYE CONTACT
 INHALATION SKIN ABSORPTION INGESTION

EFFECTS OF OVEREXPOSURE:

ACUTE EFFECTS: None

CHRONIC EFFECTS: None

Overexposure may result in the aggravation of existing conditions of the following:

Liver Skin Respiratory System
 Kidneys Eyes Central Nervous System

VI. EMERGENCY AND FIRST AID PROCEDURES

EYES:

SKIN:

INHALATION:

INGESTION:

NOTES TO PHYSICIAN:

MSDA: (Part 2)

VII. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY:

INCOMPATIBILITY:

HAZARDOUS DECOMPOSITION PRODUCTS:

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:

VIII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

NEUTRALIZING
CHEMICALS:

WASTE DISPOSAL METHODS:

NOTE: Disposal of all waste materials must be accomplished in accordance with applicable local, state and federal regulations.

IX. SPECIAL PROTECTION INFORMATION

VENTILATION REQUIREMENTS:

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY:

NOTE: This information is provided only as a general guideline to be utilized in conjunction with a full respiratory protection program.

EYE:

GLOVES:

OTHER:

X. SPECIAL PRECAUTIONS

PRECAUTIONARY
STATEMENTS:

OTHER HANDLING AND
STORAGE REQUIREMENTS

XI. ADDITIONAL REGULATORY CONCERNS

FEDERAL:

FDA

USDA

CPSC

TSCA

OTHER

STATE: