

MATERIAL SAFETY DATA SHEET

MC 8482ELG

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME	PARK TOOL POLYLUBE 1000 PPL-1 & PPL-2 MC 8482ELG
PRODUCT USE	Lubricating Grease
SUPPLIER	Chemtool Incorporated 8200 Ridgefield Road P.O. Box 538 Crystal Lake, IL 60039-0538 Tel: (815) 459-1250 Fax: (815) 459-1955
EMERGENCY TELEPHONE	Infotrac U.S. and Canada - (800) 535-5053 Outside the U.S. and Canada - 001-352-323-3500
CANADIAN PIN	N/A

2. COMPOSITION, INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	WEIGHT
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	64741-88-4	10-30 %
DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	30-50 %

COMPOSITION COMMENTS

Refer to section eight for exposure limits on ingredients.
Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Exposure to vapors generated at high temperatures, may cause respiratory irritation.

ACUTE EFFECTS

CHRONIC EFFECTS

SENSITIZATION

No known information.

CARCINOGENICITY

IARC: Not listed. OSHA: Not regulated. NTP: Not listed.
* NTP (National Toxicology Program)
* IARC (International Agency for Research on Cancer)
* OSHA (Occupational Safety and Health Administration)

TERATOGENICITY

No known information.

HEALTH WARNINGS

INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product. **SKIN CONTACT.** Repeated or prolonged contact can result in drying of the skin. **EYE CONTACT.** Irritating. **INGESTION.** Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

OTHER INFORMATION

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact. Ingestion.

MEDICAL SYMPTOMS

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not determined

4. FIRST AID MEASURES

INHALATION

Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product, immediately remove from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.

EYES

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Contact physician if discomfort continues.

SKIN

Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Get medical attention immediately!

5. FIRE FIGHTING MEASURES

FLASH POINT (°C)

246 Cd OC (Cleveland open cup).

FLAMMABILITY LIMIT - LOWER(%)

N/D

FLAMMABILITY LIMIT - UPPER(%)

N/D

EXTINGUISHING MEDIA

Use: Carbon dioxide (CO₂). Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Pressure will increase in over heated, closed containers.

HAZARDOUS COMBUSTION PRODUCTS

Oxides of: Carbon.

PROTECTIVE MEASURES IN CASE OF FIRE

Self-contained breathing equipment and chemical resistant clothing recommended.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Minimize skin contact.

PRECAUTIONS TO PROTECT THE ENVIRONMENT

Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.

SPILL CLEAN-UP PROCEDURES

Keep all sources of ignition and hot metal surfaces away from spill. Avoid contact with eyes or skin. Place leaking containers in well ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use absorbant material. Avoid discharge to natural water ways.

7. HANDLING AND STORAGE**HANDLING PRECAUTIONS**

Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. Avoid spilling, skin and eye contact. Eye wash and emergency shower must be available at the work place.

STORAGE PRECAUTIONS

Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.

STORAGE CRITERIA

Chemical storage.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

COMPONENT	STD	TWA	STEL	TWA	STEL
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	OSHA	5 mg/m ³	N/E		
	ACGIH	5 mg/m ³	10 mg/m ³		
DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC	OSHA	5 mg/m ³	N/E		
	ACGIH	5 mg/m ³	10 mg/m ³		

PROTECTIVE EQUIPMENT**ENGINEERING CONTROLS**

Use engineering controls to reduce air contamination to permissible exposure level.

VENTILATION

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

RESPIRATORS

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

PROTECTIVE GLOVES

Chemical resistant gloves recommended to prevent prolonged or repeated contact. Use protective gloves made of: Neoprene, nitrile, polyethylene or PVC.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

PROTECTIVE CLOTHING

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENIC WORK PRACTICES Wash at the end of each work shift and before eating, smoking and using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE	Grease:		
COLOR	Green.		
ODOR	Mild (or faint). Petroleum.		
SOLUBILITY DESCRIPTION	Insoluble in water.		
SOLUBILITY VALUE (g/100g H ₂ O 20°C)	< 0.1		
DENSITY/SPECIFIC GRAVITY (g/ml)	0.89	Temperature (°C)	16
VAPOR DENSITY (air=1)	> 5		
VAPOR PRESSURE	< 0.01 mmHg	Temperature (°C)	20
EVAPORATION RATE	< 0.01	Reference	BuAc=1
PH-VALUE, CONC. SOLUTION	N/A		

10. STABILITY AND REACTIVITY

STABILITY	Normally stable.
CONDITIONS TO AVOID	Avoid contact with acids and oxidizing substances.
HAZARDOUS POLYMERIZATION	Will not occur.
POLYMERIZATION DESCRIPTION	Not applicable
HAZARDOUS DECOMPOSITION PRODUCTS	Oxides of: Carbon.

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION No experimental toxicological data on the preparation as such is available.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION There is no ecological data on the product itself.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT HAZARD CLASS Not regulated.
IDENTIFICATION No. N/A
U.S. DOT HAZARD LABEL No DOT label requirement noted
SEA TRANSPORT NOTES Not regulated.
AIR TRANSPORT NOTES Not regulated.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

COMPONENT	SARA 302	CERCLA	SARA 313
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	N/A	N/A	N/A
DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC	N/A	N/A	N/A

REGULATORY STATUS

This Product or its components, if a mixture, is subject to following regulations (Not meant to be all inclusive - selected regulations represented):
TSCA: The ingredients of this product are on the TSCA Inventory.
SECTION 313: This product does not contain toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372. SARA 311 Categories: None.

CLEAN AIR ACT

US STATE REGULATIONS

STATE REGULATORY STATUS

This product or its components, if a mixture, is subject to following regulations (Not meant to be all inclusive - selected regulations represented):. **PROPOSITION 65:** This product does not contain chemicals considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 as causing cancer or reproductive toxicity, and for which warnings are now required.

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM - WHIMIS

CONTROLLED PRODUCT CLASSIFICATION

This product has been classified according to the hazard criteria of the Controlled Products Regulations, and the MSDS contains all required information.

INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
-----------	-----	----	----	-----	-----	-----	-----	------

DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	DSL	Yes	NAV	NAV	NAV	NAV	NAV	NAV	NAV
DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC	DSL	Yes	NAV	NAV	NAV	NAV	NAV	NAV	NAV

16. OTHER INFORMATION

HEALTH	Irritation, minor residual injury (1)
FLAMMABILITY	Burns only if pre-heated (1).
REACTIVITY	N/A (0).
SPECIAL HAZARD	N/A
NPCA HMIS HAZARD INDEX	Slight Hazard (1)
NPCA HMIS PERS. PROTECT. INDEX	B
PREPARED BY	Heather Holich
DATE	March 31, 2003
DISCLAIMER	While the information and recommendations set forth herein are believed to be accurate as of the date thereof, Chemtool Incorporated makes no warranty with respect thereto and disclaims all liability from reliance therein.