

JUN 20 1994

S.C. Johnson Wax  
 Racine, Wisconsin 53403-5011  
 Phone: (414) 631-2777  
 Emergency Phone: (800) 228-5635  
 Extension 092  
 International Emergency Phone:  
 Extension 092

4=Very High  
 3=High  
 2=Moderate  
 1=Slight  
 0=Insignificant

HAZARD RATING	
HMIS	NFPA
0 Health	
4 Flammability	
0 Reactivity	

# MATERIAL SAFETY DATA SHEET

## SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: PLEDGE WOOD RICH			PRODUCT CODE: 10390-3	
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 05/19/92	SUPERSEDES: 10/07/91	MSDS SECTIONS WITH CHANGES:	
			PREPARED BY: Terry A. Meyers Chemical Info. Adm.	

## SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Isoparaffinic Hydrocarbon Solvent (CAS# 64742-48-9)	10-20	300 PPM-EXXON RECOMMENDED
Mineral Oil (CAS# 8042-47-5)	30-35	5 mg/m3 OSHA PEL; 5 mg/m3 ACGIH TLV-TWA
Butane (CAS# 106-97-8)	3-5	800 ppm ACGIH/OSHA TWA
Propane (CAS# 74-98-6)	3-5	1000 ppm OSHA PEL
Water (CAS# 7732-18-5)	40-50	NA

## SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Dispensed as a spray mist with pleasant odor	SPECIFIC GRAVITY (H2O=1): 0.84
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Moderate	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): ND
pH: NA	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

## SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): under 20(TCC) (Propellant)
FLAMMABLE LIMITS: ND
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers.
UNUSUAL FIRE AND EXPLOSION HAZARDS: No special hazards known.

## SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Eye contact.
--------------------------------------

# MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

PLEDGE WOOD RICH  
Product Number: 10390  
Serial Number: 3

## SECTION V-HEALTH HAZARD DATA (cont.)

SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause irritation.

FIRST AID PROCEDURES: Flush eyes with water for 15-20 minutes. If irritation persists, seek medical aid. Treat symptomatically.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders may be more susceptible to irritating effects.

## SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

## SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Rinse affected area thoroughly with water.

WASTE DISPOSAL INFORMATION: Recycle empty aerosol can to nearest steel recycling center. Use up package or give to someone who can.

## SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: No special requirements under normal use conditions.

EYE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: NSR

## SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: DANGER: FLAMMABLE: Contents under pressure. Do not use near open fire, flames or heat. Do not store at temperatures above 120 degrees F. Do not puncture or incinerate. Do not spray or use on floors. Keep out of reach of children.

OTHER HANDLING AND STORAGE CONDITIONS: Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur.

## SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: NFPA 30B Level 2 aerosol

## SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: ORM-D.

# MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin 53403	PLEDGE WOOD RICH Product Number: 10390 Serial Number: 3
---	---

## SECTION XI-TRANSPORTATION INFORMATION (cont.)

DOT #: NA
SHIPPING NAME: Buffing or polishing compounds, NOI.
DOT NOTES: Consumer Commodity.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined  
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.  
R-106 (Rev 5 - 10/90)