

PP 541A/FAC-F

MAY 23 1994

Master Plumber

Material Safety Data Sheet NFPA RATING
HEALTH- 0
MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200. STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS. SPECIAL HAZARD-none
FLAMMABILITY- 1
REACTIVITY- 0

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List) Plumber's Putty
Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I
WILLIAM H. HARVEY COMPANY
4334 South 67th Street
Omaha, NE 68117-1019
Emergency Telephone Number (402) 331-1175
Telephone Number for Information (402) 331-1175
Date Prepared Revised July 1, 1986 - CURRENT AS OF 01/01/92
Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
None Known				

The formulation of this compound is proprietary information. A more complete disclosure will be provided to a physician or poison control center in the event of a medical emergency.

Section III - Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	2
Vapor Pressure (mm Hg.)	NA	Melting Point	NA
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	Negligible		
Appearance and Odor	Grey - putty with petroleum odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	650°F COC	Flammable Limits	NA	LEL	UEL
Extinguishing Media	CO ₂ , Foam and Dry Chemical				
Special Fire Fighting Procedures	Use water spray to cool fire exposed material and to protect personnel				
Unusual Fire and Explosion Hazards	None				

403-550 # 043015

403-568 # 043060

JUN 14 1993

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	Sources of Heat

Incompatibility (Materials to Avoid) None - Keep away from heat 250° or more and flame and strong oxidizing agents.

Hazardous Decomposition or Byproducts Partial burning would produce smoke or fumes.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic)

Appears to be no significant risk.

Carcinogenicity: NTP? IARC Monographs? OSHA Regulated?

Not considered to be carcinogenic

Signs and Symptoms of Exposure Inhalation: Possible light headedness or may cause headache.

Eyes: May cause irritation Ingestion: Has laxitive properties and may result in abdominal cramps and diarrhea.

Medical Conditions Generally Aggravated by Exposure None

Emergency and First Aid Procedures Remove victim to fresh air, seek medical attention if condition persists.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

No special precautions - Scoop up spilled material, it can be reused if it is not dirty or contaminated.

Waste Disposal Method Place in trash container and dispose of according to Federal, State and local regulations.

Precautions to Be Taken in Handling and Storing Store away from heat, keep container closed after use.

Other Precautions Keep out of reach of children and pets.

Section VIII — Control Measures

Respiratory Protection (Specify Type) No special requirements.

Ventilation	Local Exhaust	Open area is sufficient	Special	None required.
	Mechanical (General)	Not required	Other	None required.

Protective Gloves None required Eye Protection None required.

Other Protective Clothing or Equipment None

Work/Hygienic Practices Use normal good hygienic practices.