

MATERIAL SAFETY DATA SHEET
(MSDS)

4543

835

UO-04543

IDENTIFICATION NUMBER: 835 - PRO LINK CHEWING GUM REMOVER

IDENTITY (As Used On Label and List): PRO LINK CHEWING GUM REMOVER

CLC835.0193

Emergency Medical Telephone Number 8002285635X009

(24 HRS)

PRODUCT HAZARD RATINGS: - Health = 1, Fire = 4, Reactivity = 0, Protective Equipment = *B (HMIG)
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

Section I

PREFERRED DISTRIBUTORS, INC.
16607 BLANCO ROAD
SUITE 101
SAN ANTONIO
TX 78232

TELEPHONE NUMBER FOR INFORMATION:
5124931191

DATE PREPARED: 01/18/93
NAME OF PREPARER: Philip T. Miller

Section II - Hazardous Ingredients/Identity Information

Chemical Names	Exposure Limits (LD50-Oral Rat)	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
Chlorodifluoromethane (CAS#75-45-6)	NA	NA	1000ppm	1000ppm	35
Propane, 2-Methyl (CAS#75-28-5)	NA	NA	ND	ND	65

Identified ingredients are not considered hazardous under the Federal Hazard Communication Standard.
Components Listed As A Suspected Carcinogen: None

Section III - Physical Characteristics

Boiling Point: <-30F Vapor Pressure (psig): 179 @130F Specific Gravity (H2O=1): 0.6921
Solubility/Water: <0.20wt% at 25C(77F) Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: Colorless, slight ethereal

Section IV - Fire and Explosion Hazard Data

Aerosol Flammability: This product is considered to be flammable* as described in 16CFR 1500.45.
Flammable Limits - % Volume in Air (Propellant): N/A
Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: Do not spray near open flame or while smoking. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening container structure. * Blends with >6.4 wt% of Isobutane in DYMEL(R) 22 are flammable in air.

Section V - Reactivity Data

Stability: Stable Hazardous Polymerization: NA
Incompatibility (Materials to Avoid): Alkali or alkaline earth metals. Also avoid heat and open flame and phosgene. Additional toxic chemicals may be formed in small amounts.
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, hydrochloric and hydrofluoric acids and phosgene. Additional toxic chemicals may be formed in small amounts.
Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.