Racine, Wisconsin 53403-5011

Phone: (414) 631-2777

Man Sounds

Health 1
Flammability 4
Reactivity 0

MATERIAL SAFETY DATA SHEET SECTION L-PRODUCT IDENTIFICATION

NOV 21 1990

| Product Name: | | | Ргоdист Code: 11600-019 |
|--|--------------|-------------|--------------------------------|
| RAID YARD GUARD Chemical or Common Name: | Date Issued: | Supercedes: | Prepared by: Robert B. O'Brien |
| . NA | 04/01/88 | 10/30/87 | Chemical Info. Adm. |

SECTION IL INCREDIENT INFORMATION

| Ingredient | Weight % | Exposure Limit |
|--|----------|--|
| Propane\Isobutane\N-Butane (CAS #74-98-5, 75-28-5, 106-97-8) | 20-40 | 800 ppm ACGIH TLV-TWA; 100 ppm OSHA PEL |
| Water | 60-75 | NA |

SECTION III-PHYSICAL DATA

| ODC1101111111111111111111111111111111111 | | |
|--|--|--|
| APPEARANCE/ODOR: Dispensed as a spray with mild odor | SPECIFIC GRAVITY (H2O=1): 0.83 | |
| VAPOR PRESSURE (mm Hg): ND | PERCENT VOLATILE BY VOLUME (%): NA | |
| SOLUBILITY IN WATER: Appreciable | VAPOR DENSITY (AIR=1): ND | |
| FREEZING POINT (°F): about 32 | BOILING POINT (°F): ND | |
| pH: ND | EVAPORATION RATE (BUTYL ACETATE=1): NA | |

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (METHOD USED): under 20(TCC) (Propellant)

FLAMMABLE LIMITS: ND

EXTINGUISHING MEDIA: Foam , CO2 , Dry Chemical , Water Fog

SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers. Fire fighters should wear self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No special hazards known

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin Contact , Inhalation

SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause irritation. Direct contact of product with skin can cause irritation. Product may cause irritation and nausea if taken internally. Product vapors may cause irritation to nose, throat and lungs if inhaled.

FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. If product gets on skin, remove with soap and water. If product is swallowed, seek medical aid at once. If difficulty or discomfort in breathing is experienced, remove to fresh air and get medical attention.

XAW MOZNHOL

S.C. Johnson & Son, Inc.

1525 Howe Street

Racine, Wisconsin 53403

RAID YARD GUARD

Product Number: 11600

Page 2

Serial Number: 19

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Rinse affected area thoroughly with water.

WASTE DISPOSAL INFORMATION: Dispose of aerosol can by wrapping and placing in trash. Do not puncture or burn container. Dispose of spilled residues and multiple units in accordance with all Federal\State regulations and Local ordinances.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: For outdoor use only. Do not use indoors or in poorly ventilated areas.

PROTECTIVE GLOVES: If prolonged or repeated contact is possible: Any impervious material.

EYE PROTECTION: Chemical workers splash-proof goggles

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Where gross eye\skin contact may be a problem, wear\use appropriate protective equipment.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: CAUTION: Keep out of reach of children. Harmful if swallowed. Avoid inhalation of vapors. Avoid contact with skin, eyes or clothing. Flammable. Contents under pressure. Do not use or store near heat, sparks, or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130 F may cause container to burst.

OTHER HANDLING AND STORAGE CONDITIONS: Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur. Wash thoroughly after handling. Keep out of reach of children.

SECTION X-ADDITIONAL INFORMATION

For information on appropriate emergency procedures phone: 414-631-2000. ADDITIONAL INFORMATION: EPA Registration No. 4822-309. Factory Mutual Level 1 aerosol Factory Mutual Level 1 aerosol

JOHNSON WAX

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson & Son, Inc. 1525 Howe Street

Racine, Wisconsin 53403

RAID YARD GUARD

Product Number: 11600

Serial Number: 19

NA-Not Applicable, NSR-No Special Requirement, ND-Not Determined for this product
The information herein is given in good faith. No warranty, expressed or implied, is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations.
The information contained in this form is confidential and is submitted solely for your organization's internal use.