

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

MAR 25 1993



IDENTITY (As Used on Label and List)
RUST CURB Gloss White

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I 6-5155 # 419-4146N

Manufacturer's Name Chase Products Company	Emergency Telephone Number (708)865-1000	HMIS RATING or NFPA 704 HAZARD RATING 4 - Extreme 3 - High 2 - Moderate 1 - Slight 0 - Insignificant	HEALTH 2
	Telephone Number for Information (708)865-1000		FIRE 4
Address (Number, Street, City, State, and ZIP Code) P.O. Box 70 Maywood, IL 60153	Date Prepared		REACTIVITY 1
ORM-D Consumer Commodity ID# UN1954			

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; CAS Reg. No)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
*Toluene 108-88-3	100ppm	100ppm	NA	15-20%
*Acetone 67-64-1	750ppm	750ppm	NA	25-30%
*Xylene 1330-20-7	100ppm	100ppm	NA	5-10%
Titanium Dioxide 13463-67-7	**15mg/m ³	**10mg/m ³	NA	
Propane/n-Butane Propellant 74-98-6/ Blend 106-97-8	1000ppm 800ppm	NA 800ppm	NA NA	
* These chemicals are listed under SARA Section 313.				
** As nuisance dust.				

Section III — Physical/Chemical Characteristics

Boiling Point Acetone	0 133 F	Specific Gravity (H ₂ O = 1) Concentrate	0.967
Vapor Pressure (mm Hg.)	NA	Melting Point	NA
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	Faster than Butyl Acetate
Solubility in Water	Insoluble		
Appearance and Odor	Paint appearance with solvent odor.		

Section IV — Fire and Explosion Hazard Data

Flame Projection: Over 18in. with flashback	Flammable Limits NA	LEL NA	UEL NA
Extinguishing Media	Carbon dioxide, foam and Dry chemical.		
Special Fire Fighting Procedures	Water spray may be used to cool cans in the vicinity of fire or excessive heat.		
Unusual Fire and Explosion Hazards	Temperatures above 120°F may cause cans to burst.		

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	x	Temperatures above 120°F

Incompatibility (Materials to Avoid)
Strong oxidizing agents and open flame.

Hazardous Decomposition or Byproducts
Thermal decomposition may yield toxic gases like carbon monoxide and carbon dioxide.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	x	Temperatures above 120°F.

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? yes	Skin? yes	Ingestion? no
--------------------	--------------------	--------------	------------------

Health Hazards (Acute and Chronic)
Acute: Over inhalation of concentrate vapor or spray mist may cause headache, dizziness and nausea. Prolonged contact of this product with skin and eyes can cause irritation.

Chronic: Not known.

Carcinogenicity:	NTP? no	IARC Monographs? no	OSHA Regulated? no
------------------	------------	------------------------	-----------------------

Signs and Symptoms of Exposure
Over inhalation of concentrate vapor or spray mist may cause headache, dizziness and nausea. Prolonged contact of this product with skin and eyes can cause irritation.

Medical Conditions
Generally Aggravated by Exposure
Not known.

Emergency and First Aid Procedures
Move victim to fresh air, provide oxygen if breathing is difficult. Flush skin and eyes with plenty of water. Consult a physician if injury develops.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
Soak up spills with chemically inert, absorbant material.

Waste Disposal Method
Dispose cans in non-incinerated trash only.

Precautions to Be Taken in Handling and Storing
Handle as flammable material. Keep can away from heat and open flame.

Keep out of reach of children. **AEROSOL FIRE PROTECTION LEVEL III (NFPA 30B)**

Other Precautions
Do not inhale to much vapor or mist. Avoid repeated contact with skin and eyes.

Section VIII - Control Measures

Respiratory Protection (Specify Type)
None required if used with adequated ventilation.

Ventilation	Local Exhaust Preferred	Special None
	Mechanical (General) Optional	Other None

Protective Gloves
Rubber or vinyl

Eye Protection
Conventional eyeglasses to guard against unexpected splashing.

Other Protective Clothing or Equipment
None required.

Work/Hygienic Practices
Wash hands thoroughly after using this product.