

Skedde

more more room 107
Anderson - basement equip room
#1104

Carlson 1
1012A

MATERIAL SAFETY DATA SHEET
emergency telephone 414-332-8440

Name: Alliance Group Inc Address: 600 East Keefe Avenue
City: Milwaukee State: Wisconsin Zip: 53212
Product name: Rustoscale Custom #42
Product code: 0160

Section II - Hazardous Ingredient

CAS Number	Chemical Component	%	TLV (PPM)	Hazard Data
7664-93-9	Sulfuric Acid	15	1mg/m3	

Section III-Physical Data

Solid: Liquid: X Appearance: Water white
Specific Gravity: 1.2 Odor: Pungent odor
Solubility in water: Complete Freezing Point: 32°F.
% Volatiles: 0 pH: 1.0

Section IV - Fire and Explosive Data

Flash Point: N/A Flammable Limits lfl ufl
Extinguishing
Media: CO2, Water Fog, Dry Chemical, Foam
Special Fire Hazards and Equipment Required: Firefighters should wear self-contained breathing apparatus

Section V- Reactive Hazards

Product Hazardous will not
Stable: No Yes X Polymerization: OCCUR

Conditions to avoid: extreme heat, alkaline materials, most metals
Incompatability: alkaline products, strong oxidizers, sulfide wash, metallic powders, reactive chemicals
Hazardous Decomposition Products: hydrogen sulfide, sulfur trioxide

Section VI - Health Hazardsmsds0160

Eyes: irritation and possible burning

Skin: irritation and possible burns

Ingestion: can cause mucous membrane burns, abdominal pain, respiratory distress, shock, renal failure. Possible permanent damage to esophagus, stomach.

Inhalation: irritation of the airways. Possible bronchoconstriction and laryngeal spasm

Principal Routes of Exposure: topical

Acute effects of Overexposure: irritation, possible burns

Chronic Effects of Overexposure: irritation

First Aid Procedure—Never give fluids or induce vomiting if patient is unconscious or having convulsions.

CALL A PHYSICIAN

Eyes: Immediately flush with large amounts of cool water for 15 minutes. Seek immediate medical attention

Skin: Flush skin with plenty of cool water for 15 minutes. Remove contaminated clothing and clean before reuse. Discard contaminated footwear. If irritation persists call a physician.

Ingestion: Do not induce vomiting. Give large amounts of water.. Seek immediate medical attention.

Inhalation: remove victim to fresh air. If not breathing, resuscitate, then administer oxygen. Call physician immediately.

Section VII - Normal Handling Procedures

Precautions to be taken

in Handling and Storage: Store in a secure, cool, dry area. Keep container tightly closed when not in use. Protect from damage.

Protective Equipment:

Eyes: Chemical goggles, face shield

Gloves: Rubber

Other: impervious clothing, eye bath, safety shower

Ventilation Requirements: local exhaust ventilation

Corrosive Action on Materials: Moderate

Section VIII- Spill or Leak Control Procedures

msds0160

Steps to be taken in case of spills: Wear protective equipment (See Sec. VII) Contain spill, ventilate area. Neutralize slowly with soda ash or lime. Collect in labelled approved drums for disposal. Rinse area with plenty of water.

Waste disposal methods: Contact local environmental authorities.

The above information is believed to be accurate and discloses the known hazards for this product as of this date. No additional warranties are made. Date: March 26, 1986 By: D.C Miller
