

MATERIAL SAFETY DATA SHEET  
Essentially similar to OSHA Form #174

IDENTITY:

SATIN SHINE - JR 315

SECTION 1

MANUFACTURER'S NAME: Sysco Chemical  
STREET ADDRESS: 1390 Enclave Parkway

EMERGENCY PHONE NO.:  
(713) 584-1790

CITY, STATE, ZIP CODE: Houston, TX 77077

DATE PREPARED: 7-15-88

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENTS	* *	* PEL * PPM	* TLV * PPM	* TLV * MG/M3	* *	CAS Number
Aqua Ammonia	* 0.80	* 50	* 25	*	*	1336-21-6
Isobutane Propellant	* 5	* 1000	* 1000	*	*	75-28-5
Propane	* 5	* 1000	* 1000	*	*	74-98-6
	*	*	*	*	*	
	*	*	*	*	*	
	*	*	*	*	*	

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: Propellant below 0.0 F

SPECIFIC GRAVITY: 0.945

VAPOR PRESSURE (mm Hg.): NA

MELTING POINT: NA

VAPOR DENSITY (AIR = 1): Heavier than air

EVAPORATION RATE: Propellants  
faster than ether

SOLUBILITY IN WATER: Complete

APPEARANCE AND ODOR: White foam appearance, lemon fragrance

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): (T.O.C.) Propellant < 20 F

FLAMMABLE LIMITS: NA

LEL: NA

UEL: NA

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or foam

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective. Water may  
be used to keep fire exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not spray near open flame. Keep  
at room temperature as exposure to direct sunlight or other heat may  
cause bursting.

IDENTITY: SATIN SHINE - JR 315

Page: 2

SECTION 5 - REACTIVITY DATA

STABILITY: Stable: X Unstable:

CONDITIONS TO AVOID: Do not store above 120 F.

INCOMPATIBILITY (materials to avoid): NA

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: By open flame - carbon monoxide, carbon dioxide

HAZARDOUS POLYMERIZATION: May Occur: Will Not Occur: X

CONDITIONS TO AVOID: NA

SECTION 6 - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? yes SKIN? yes INGESTION? yes

HEALTH HAZARDS (acute & chronic): In a confined area, vapors in high concentration are anesthetic. Irritant to skin and upper respiratory system. Over-exposure may result in light-headedness, staggering gait, giddiness and possible nausea. Harmful or fatal if swallowed. Repro. have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage, also kidney and liver damage

CARCINOGENICITY: NTP? NA  
IARC MONOGRAPHS? NA  
OSHA REGULATED? NA

SIGNS & SYMPTOMS OF EXPOSURE: Slight dizziness due to propellant (Isobutane)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Aqua ammonia in this product contains vapors and mists that are extremely corrosive to the nose, throat, and mucous membranes. Bronchitis, pulmonary edema, and chemical pneumonitis may occur. Irritation, coughing, chest pain, and difficulty in breathing may occur with brief exposure while prolonged exposure may result in more severe irritation and tissue damage.

EMERGENCY AND FIRST AID PROCEDURES: Breathing - Remove patient to fresh air. Eyes - Flush with water for at least 15 minutes. Skin - Wash with soap and water. Swallowing - Call physician immediately. DO NOT induce vomiting.

IDENTITY: SATIN SHINE - JR 315

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate, avoid breathing vapors and remove with inert absorbent.

WASTE DISPOSAL METHOD: As prescribed by local, state, or federal regulations concerning chemical waste disposal.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING: Store between 35 and 120 to avoid rupture of container.

OTHER PRECAUTIONS: Keep out of reach of children.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION (specify type): Avoid breathing of vapor or spray mist.

VENTILATION:

LOCAL EXHAUST: yes  
MECHANICAL: NA  
SPECIAL: NA  
OTHER: NA

PROTECTIVE GLOVES: Neoprene

EYE PROTECTION: Eye Protection

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK/HYGIENIC PRACTICES: None

SECTION 9 - SPECIAL PRECAUTIONS

The above information is believed to be correct with respect to the ingredients contained herein falling within the definition of hazardous chemicals in accordance with the Occupational Safety and Health Administration's Hazard Standard Communications Act. Data, standards and regulations change, and since conditions of use and handling are beyond our control, no warranty, express or implied, is made as to the completeness or upcoming accuracy of this information.

Pursuant to Proposition 65: Certain raw materials used in making this product may contain small amounts of materials as impurities which are regulated by Proposition 65, in the state of California.