

*Her  
Saw  
Paint*

## MAUTZ V-104 SATIN WOOD FINISH

### MATERIAL SAFETY DATA

**MANUFACTURER:** Mautz Paint Co.

**ADDRESS:** 939 E. Washington Ave. Madison, WI.

**EMERGENCY TEL.** (608) 262-3702 or (608) 255-1661

**PRODUCT CLASS:** Solvent Based (Alkyd, Alkyd-Oil, Epoxy) Paint

**TRADE NAME:** Satin Wood Finish

**MFG. CODE ID.** V-104

#### HAZARDOUS INGREDIENTS

INGREDIENT	%WEIGHT	TLV-PPM	mg/m3
Mineral Spirits (CAS 8030-30-6)	18.3	Not established	

#### PHYSICAL DATA

**BOILING RANGE:** 313-391°F. **VAPOR DENSITY:** Heavier than air **EVAPORATION RATE:** Slower than ether **PERCENT VOLATILE BY VOLUME:** 60.6% **WEIGHT PER GALLON:** 7.25 lbs.

#### FIRE AND EXPLOSION HAZARD DATA

**DOT CATEGORY:** Combustible **FLASH POINT:** 105° F. **TCC EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, or Foam (NFPA Class B Extinguisher) **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers should be kept tightly closed. Keep away from heat, open flame, electrical equip., sparks. **SPECIAL FIRE FIGHTING PROCEDURES:** Water may be used to cool containers to reduce rate of burning and resist additional ignition or explosion.

#### HEALTH HAZARD DATA

**THRESHOLD LIMIT VALUE:** See Hazardous Ingredients **EFFECTS OF OVEREXPOSURE:** Inhalation: Irritation of eyes and respiratory tract; headache, dizziness and nausea. Skin; Irritant. Reports have shown repeated and prolonged occupational overexposure to solvents can result in permanent brain and skin damage. **EMERGENCY AND FIRST AID PROCEDURES:** Inhalation: Remove to fresh air. Restore breathing if necessary. Notify a physician. Eye Contact: Flush with water. Notify a physician. Skin Contact: Wash with soap and water. Contaminated clothing should be removed and washed prior to reuse.

#### REACTIVITY DATA

**STABILITY:** Stable **INCOMPATABILITY:** Avoid strong Oxidizers. **HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion will produce Carbon Monoxide & Carbon Dioxide **HAZARDOUS POLYMERIZATION:** Will not occur. **CONDITIONS TO AVOID:** Heat, Open Flame, Sparks.

#### SPILL OR LEAK PROCEDURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Eliminate ALL sources of ignition. Ventilate area. Soak up spill with absorbent material (sawdust). Remove with grounded (nonsparking) equipment. **WASTE DISPOSAL METHOD:** Incinerate under safe conditions. Disposal should be in accordance with local, state, and federal regulations.

#### SPECIAL PROTECTION INFORMATION

**RESPIRATORY PROTECTION:** Use NIOSH approved chemical cartridge respirator (TC23C) to remove solid airborne particles and solvent vapors from overspray during application. **VENTILATION:** Use local exhaust to maintain TLV of most hazardous ingredient (SEE HAZARDOUS INGREDIENTS) below acceptable limit. **PROTECTIVE GLOVES:** Yes **EYE PROTECTION:** Safety glasses designed to protect eyes from liquid splash. **OTHER PROTECTIVE EQUIPMENT:** Eye Bath/Safety Shower.

#### SPECIAL PRECAUTIONS

**PRECAUTIONS TO BE TAKEN WHEN HANDLING AND STORING:** Keep away from heat, open flame or sparks. Store in an area suitable for Flammable or combustible liquids. **OTHER PRECAUTIONS:** Not to be taken internally.