

S.C. Johnson Wax
 Racine, Wisconsin 53403-5011
 Phone: (414) 631-2777
 Emergency Phone: (800) 228-5635
 Extension 092
 International Emergency Phone:
 Extension 092

4=Very High
 3=High
 2=Moderate
 1=Slight
 0=Insignificant

HAZARD RATING	
HMIS	NFPA
0 Health	
4 Flammability	
0 Reactivity	

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: SHINE-UP (PRESSURIZED)			PRODUCT CODE: 14430-10 to 14434-10	
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 01/24/92	SUPERSEDES: 03/05/91	MSDS SECTIONS WITH CHANGES:	PREPARED BY: Terry A. Meyers Chemical Info. Adm.

SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Isoparaffinic Hydrocarbon Solvent (CAS# 64742-48-9)	10-20	400ppm (Supplier Recommended)
[PA,NJ,MA] Propane (CAS# 74-98-6)	3-5	1000 ppm OSHA PEL
Silicone Fluid (CAS# 63148-62-9)	1-5	NOT ESTABLISHED
Water (CAS# 7732-18-5)	70-80	NA
[PA,NJ,MA] Butane (CAS# 106-97-8)	3-5	800 ppm ACGIH/OSHA TWA
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Dispensed as creamy spray with mild odor	SPECIFIC GRAVITY (H2O=1): 0.9
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Negligible	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): NA
pH: NA	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): under 20 (TCC) (Propellant)
FLAMMABLE LIMITS: ND
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers.

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax SHINE-UP (PRESSURIZED)
 1525 Howe Street Product Number: 14430
 Racine, Wisconsin 53403 Serial Number: 10

SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may burst in heat of fire.

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact.

SIGNS AND SYMPTOMS: No effects except under extreme exposure conditions.

FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. If irritation persists, seek medical aid.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

WASTE DISPOSAL INFORMATION: Recycle empty aerosol can to nearest steel recycling center. Use up package or give to someone who can.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: No special requirements under normal use conditions.

EYE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: CAUTION: Do not use near fire, flame or pilot light. Do not set on stove or radiator or keep where temperature exceeds 120 F as container may burst. Do not puncture or throw in fire. Keep out of reach of children. Never use on floors or surfaces that are walked on as the product's ingredients could make them slippery. Avoid overspray.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax SHINE-UP (PRESSURIZED)
 1525 Howe Street Product Number: 14430
 Racine, Wisconsin 53403 Serial Number: 10

SECTION IX-SPECIAL PRECAUTIONS (cont.)

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Keep from freezing. Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: NFPA 30B Level 1

EPA REGISTRATION #: NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Non Regulated.

DOT #: NA

SHIPPING NAME: Buffing or polishing compounds, NOI.

SECTION XII-REGULATORY INFORMATION

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NJ - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

MA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined
 The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.
 R-106 (Rev 5 - 10/90)