

S.C. Johnson Wax
 Racine, Wisconsin 53403-5011
 Phone: (414) 631-2777
 Emergency Phone: (800) 228-5635
 Extension 092
 International Emergency Phone:
 Extension 092

4=Very High
 3=High
 2=Moderate
 1=Slight
 0=Insignificant

HAZARD RATING	
HMIS	NFPA
1 Health	
2 Flammability	
0 Reactivity	

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: SNAPBACK LIQUID				PRODUCT CODE: 14110-8 to 14114-8	
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 07/02/92	SUPERSEDES: 09/11/91	MSDS SECTIONS WITH CHANGES: V	PREPARED BY: Terry A. Meyers Chemical Info. Adm.	

SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Isoparaffinic Hydrocarbon solvent (CAS# 64742-48-9)	10-15	300 PPM-EXXON RECOMMENDED
Diethylene Glycol Monoethyl Ether (CAS# 111-90-0CAS)	under 2	NOT ESTABLISHED
Alkylphenoxy polyethoxyethanol (CAS# 26027-38-3)	1-4	NOT ESTABLISHED
Water (CAS# 7732-18-5CAS)	65-85	NA
Acrylic Polymers (CAS# N/ACAS)	2-4	NE
[PA,MA] Triethanolamine (CAS# 102-71-6)	0.4-0.8	NOT ESTABLISHED
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Milky, thin liquid with mild odor	SPECIFIC GRAVITY (H2O=1): 1.0
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Complete	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): 200
pH: 7.9-8.8	EVAPORATION RATE (Butyl Acetate=1): ND
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): 152 (TCC)
FLAMMABLE LIMITS: ND
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

SNAPBACK LIQUID
Product Number: 14110
Serial Number: 8

SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)

SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors may accumulate in confined spaces (e.g., pits, sumps, sewers) and inadequately ventilated areas.

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Ingestion.

SIGNS AND SYMPTOMS: If taken internally, aspiration of liquid product can cause chemical pneumonitis.

FIRST AID PROCEDURES: If product is swallowed, do not induce vomiting. Seek medical aid at once.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: None known to S.C. Johnson Wax

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Do not let spilled or leaking material enter watercourse. May be toxic to aquatic life. Eliminate all ignition sources. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

WASTE DISPOSAL INFORMATION: No special method. Observe all applicable Federal/State regulations and Local ordinances regarding disposal of non-hazardous materials. Waste from normal product use may be sewerer to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: No special requirements under label recommended use directions.

EYE PROTECTION: No special requirements under label recommended use directions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Launder contaminated clothing/equipment before reuse.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

SNAPBACK LIQUID
Product Number: 14110
Serial Number: 8

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: CAUTION: Keep away from open flame or spark. Keep out of reach of children. Contains naphtha; if swallowed, do not induce vomiting, call a hospital emergency room or a doctor at once.

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Wash thoroughly after handling. Keep from freezing. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: NA

EPA REGISTRATION #: NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Non hazardous

DOT #: NA

SHIPPING NAME: Buffing or polishing compounds, NOI.

SECTION XII-REGULATORY INFORMATION

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

NA-Not Applicable, NE-Not Established, MSR-No Special Requirement, ND-Not Determined
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.
R-106 (Rev 5 - 10/90)