

S.C. Johnson Wax  
 Racine, Wisconsin 53403-5011  
 Phone: (414) 631-2777  
 Emergency Phone: (800) 228-5635  
 Extension 092  
 International Emergency Phone:  
 Extension 092

4=Very High  
 3=High  
 2=Moderate  
 1=Slight  
 0=Insignificant

HAZARD RATING	
HMTS	NFPA
0 Health	0
4 Flammability	4
0 Reactivity	0

## MATERIAL SAFETY DATA SHEET

### SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: SNAPBACK PRESSURIZED			PRODUCT CODE: 14115-10 to 14119-10		
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 01/13/93	SUPERSEDES: 04/10/92	MSDS SECTIONS WITH CHANGES: V	PREPARED BY: Terry A. Meyers Chemical Info. Adm.	

### SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Isoparaffinic Hydrocarbon Solvent (CAS# 64742-48-9)	10-15	300 PPM-EXXON RECOMMENDED
Diethylene Glycol Monoethyl Ether (CAS# 111-90-0CAS)	1-3	NOT ESTABLISHED
[PA,NJ,MA] Isobutane (CAS# 75-28-5)	1-3	NOT ESTABLISHED
Water (CAS# 7732-18-5CAS)	70-80	NA
Acrylic Polymers (CAS# N/ACAS)	2-4	NE
[PA,MA] Triethanolamine (CAS# 102-71-6)	0.4-0.6	NOT ESTABLISHED
[PA,NJ,MA] N-Butane (CAS# 106-97-8)	1-5	800 PPM ACGIH/OSHA TWA
[PA,NJ,MA] Propane (CAS# 74-98-6)	1-3	1000 PPM OSHA PEL
See Regulatory Information (Section XII) for explanation of bracketed information.		

### SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Milky mist with mild odor	SPECIFIC GRAVITY (H2O=1): 0.9
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Complete	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): ND
PH: ND	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

### SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used):	under 20 (TCC) (Propellant)
---------------------------------	-----------------------------

**MATERIAL SAFETY DATA SHEET**

Page 2

S.C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

SNAPBACK PRESSURIZED  
Product Number: 14115  
Serial Number: 10

**SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)**

FLAMMABLE LIMITS: 1.8-9.5% (Propellant)

EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.

SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may burst in heat of fire. Vapors may accumulate in confined spaces (e.g., pits, sumps, sewers) and inadequately ventilated areas.

**SECTION V-HEALTH HAZARD DATA**

PRIMARY ROUTE OF ENTRY: Ingestion.

SIGNS AND SYMPTOMS: If taken internally, aspiration of liquid product can cause chemical pneumonitis.

FIRST AID PROCEDURES: If product is swallowed, do not induce vomiting. Seek medical aid at once. Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. If product gets on skin, remove with soap and water.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: None known to S.C. Johnson Wax

**SECTION VI-REACTIVITY DATA**

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

**SECTION VII-SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

WASTE DISPOSAL INFORMATION: Recycle empty aerosol can to nearest steel recycling center. Use up package or give to someone who can.

**SECTION VIII-SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: No special requirements under normal use conditions.

**MATERIAL SAFETY DATA SHEET**

Page 3

S.C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

SNAPBACK PRESSURIZED  
Product Number: 14115  
Serial Number: 10

**SECTION VIII-SPECIAL PROTECTION INFORMATION (cont.)**

EYE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Launder contaminated clothing/equipment before reuse.

**SECTION IX-SPECIAL PRECAUTIONS**

PRECAUTIONARY LABELING: CAUTION: Keep out of reach of children. Do not set on stove or radiator or keep where temperature will exceed 120 F as container may burst. Do not puncture or throw in fire.

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Wash thoroughly after handling. Keep from freezing. Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur.

**SECTION X-ADDITIONAL INFORMATION**

ADDITIONAL INFORMATION: NFPA 30B Level 1

EPA REGISTRATION #: NA

**SECTION XI-TRANSPORTATION INFORMATION**

DOT CLASS: ORM-D.

DOT #: NA

SHIPPING NAME: Buffing or polishing compounds, NOI.

**SECTION XII-REGULATORY INFORMATION**

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NJ - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined  
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.  
2-106 (Rev 5-10/90)