

S C JOHNSON WAX -- SNAPBACK SPRAY BUFF PRESSURIZED, 14119-10
MATERIAL SAFETY DATA SHEET
NSN: 793000N061256
Manufacturer's CAGE: 32204
Part No. Indicator: A
Part Number/Trade Name: SNAPBACK SPRAY BUFF PRESSURIZED, 14119-10

=====
General Information
=====

Company's Name: S C JOHNSON WAX
Company's Street: 1524 HOWE STREET
Company's City: RACINE
Company's State: WI
Company's Country: US
Company's Zip Code: 53403-5011
Company's Emerg Ph #: 800-228-5635
Company's Info Ph #: 414-631-2777
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SMJ
Date MSDS Prepared: 08JAN94
Safety Data Review Date: 05JUL95
MSDS Preparer's Name: TERRY A MEYERS
Preparer's Company: SAME
MSDS Serial Number: BXZTM

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: MINERAL SPIRITS; (ISOPARAFFINIC HYDROCARBON SOLVENT)
Ingredient Sequence Number: 01
Percent: 10-15
NIOSH (RTECS) Number: PY8240000
CAS Number: 64475-85-0
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Proprietary: NO
Ingredient: ETHANOL, 2-(2-ETHOXYETHOXY)-; (DIETHYLENE GLYCOL MONOETHYL ETHER)
Ingredient Sequence Number: 02
Percent: 1-3
NIOSH (RTECS) Number: KK8750000
CAS Number: 111-90-0
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Proprietary: NO
Ingredient: PROPANE, 2-METHYL-; (ISOBUTANE)
Ingredient Sequence Number: 03
Percent: 1-3
NIOSH (RTECS) Number: TZ4300000
CAS Number: 75-28-5
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Proprietary: NO
Ingredient: WATER
Ingredient Sequence Number: 04
Percent: 70-80
NIOSH (RTECS) Number: ZC0110000
CAS Number: 7732-18-5
OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

Proprietary: NO
Ingredient: ACRYLIC POLYMERS
Ingredient Sequence Number: 06
Percent: 2-4
NIOSH (RTECS) Number: 1001265AP
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Proprietary: NO
Ingredient: PROPANE
Ingredient Sequence Number: 07
Percent: 1-3
NIOSH (RTECS) Number: TX2275000
CAS Number: 74-98-6
OSHA PEL: 1000 PPM
ACGIH TLV: ASPHYXIAN

=====

Physical/Chemical Characteristics

=====

Appearance And Odor: MILKY MIST W/MILD ODOR.
Specific Gravity: 0.9 (H*20=1)
Evaporation Rate And Ref: N/A
Solubility In Water: COMPLETE

=====

Fire and Explosion Hazard Data

=====

Flash Point: <20F, <-7C
Flash Point Method: TCC
Lower Explosive Limit: 1.8%
Upper Explosive Limit: 9.5%
Extinguishing Media: FOAM, CO*2, DRY CHEMICAL, WATER FOG.
Special Fire Fighting Proc: WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT
EQUIP(FP N). NORM FIRE FIGHTING PROCS MAY BE USED. FIGHT FIRE FROM MAX
DISTANCE/PROT AREA. COOL & USE CAUTION(SUPDAT)
Unusual Fire And Expl Hazrds: CONTAINER MAY BURST IN HEAT OF FIRE. VAPORS
MAY ACCUMULATE IN CONFINED SPACES(E.G., PITS, SUMPS, SEWERS) AND
INADEQUATELY VENTILATED AREAS.

=====

Reactivity Data

=====

Stability: YES
Cond To Avoid (Stability): NONE KNOWN.
Materials To Avoid: NONE KNOWN.
Hazardous Decomp Products: WHEN EXPOSED TO FIRE, PRODUCES NORMAL PRODUCTS
OF COMBUSTION.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT.

=====

Health Hazard Data

=====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: NO
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: IF TAKEN INTERNALLY, ASPIRATION OF LIQUID
PRODUCT CAN CAUSE CHEMICAL PNEUMONITIS.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NOT RELEVANT.
Signs/Symptoms Of Overexp: SEE HEALTH HAZARDS.

Med Cond Aggravated By Exp: NONE KNOWN TO SC JOHNSON WAX.
Emergency/First Aid Proc: INGEST: IF SWALLOWED, DO NOT INDUCE VOMITING.
SEEK MED AID AT ONCE. EYES: FLUSH W/WATER FOR AT LEAST 15-20 MINUTES. IF
IRRIT PERSISTS, SEEK MED AID. SKIN: REMOVE W/SOAP & WATER. INHAL: REMOVE TO
FRESH AIR. SUPPORT BREATHING(GIVE O*2/ARTF RESP)(FP N).

Precautions for Safe Handling and Use

Steps If Matl Released/Spill: ELIMNATE ALL IGNITION SOURCES. ABSORB W/OIL-
DRI OR SIMILAR INERT MATERIAL. SWEEP OR SCRAPE UP AND CONTAINERIZE.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
Waste Disposal Method: RECYCLE EMPTY AEROSOL CAN TO NEAREST STEEL
RECYCLING CENTER. USE UP PACKAGE OR GIVE TO SOMEONE WHO CAN. DISPOSE OF IN
ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS(FP N).
Precautions-Handling/Storing: DO NOT SET ON RADIATOR OR KEEP WHERE
TEMPERATURE WILL EXCEED 120F AS CONTAINER MAY BURST. STORE IN COOL, DRY
PLACE W/ADEQ VENT. KEEP FROM FREEZING.
Other Precautions: CAUTION: KEEP OUT OF REACH OF CHILDREN. DO NOT PUNCTURE
OR THROW IN FIRE. DO NOT PRESSURIZE, CUT, HEAT, WELD OR EXPOSE CONTAINER TO
FLAME; EXPLOSION COULD OCCUR.

Control Measures

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN(FP N).
Ventilation: GENERAL ROOM VENTILATION ADEQUATE.
Protective Gloves: IMPERVIOUS GLOVES(FP N).
Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS(FP N).
Other Protective Equipment: EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI
DESIGN CRITERIA(FP N).
Work Hygienic Practices: USE GOOD PERSONAL HYGIENE PRACTICES. LAUNDER
CONTAMD CLTHG/EQUIPMENT BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.
Suppl. Safety & Health Data: FIRE FIGHT PROC: WHEN APPROACHING/HANDLING
FIRE-EXPOSED CONTAINERS.

Transportation Data

Disposal Data

Label Data

Label Required: YES
Technical Review Date: 05JUL95
Label Date: 05JUL95
Label Status: B
Common Name: SNAPBACK SPRAY BUFF PRESSURIZED, 14119-10
Chronic Hazard: NO
Signal Word: DANGER!
Acute Health Hazard-Slight: X
Contact Hazard-Slight: X
Fire Hazard-Severe: X
Reactivity Hazard-None: X
Special Hazard Precautions: EXTREMELY FLAMMABLE AEROSOL. ACUTE: IF TAKEN
INTERNALLY, ASPIRATION OF LIQUID PRODUCT CAN CAUSE CHEMICAL PNEUMONITIS.
CHRONIC: NONE SPECIFIED BY MANUFACTURER.
Protect Eye: X
Protect Skin: X
Protect Respiratory: X
Label Name: S C JOHNSON WAX
Label Street: 1524 HOWE STREET
Label City: RACINE

Label State: WI
Label Zip Code: 53403-5011
Label Country: US
Label Emergency Number: 800-228-5635

=====
URL for this msds <http://siri.org>. If you wish to change, add to, or
delete information in this archive please send updates to dan@siri.org.