

ATTN: SAFETY DIRECTOR
UNIV OF WISCONSIN - WHITEWATER
PURCHASING OFFICE
800 W MAIN ST
WHITEWATER WI 53190-1705

EMERGENCY PHONE 1-314-771-5765

DATE 01/18/99 CUST#: 0-495-04629 PO#: QH5212

MATERIAL SAFETY DATA SHEET PAGE ECTION 1. CHEMICAL IDENTIFICATION-S0751 SODIUM PHOSPHATE MONOBASIC ANHYDROUS MINIMUM 99.0% CATALOG #: NAME: ECTION 2. - COMPOSITION/INFORMATION ON INGREDIENTS #: /5 H2NAO4P 231-449-2 SYNONYMS
MONOSODIUM DIHYDROGEN PHOSPHATE * MONOSODIUM PHOSPHATE * MONOSORB XP4 * PRIMARY SODIUM PHOSPHATE * SODIUM ACID PHOSPHATE * SODIUM
BIPHOSPHATE * SODIUM BIPHOSPHATE ANHYDROUS * SODIUM PHOSPHATE,
MONOBASIC * ECTION 3. - - - - - - - - HAZARDS IDENTIFICATION -LABEL PRECAUTIONARY STATEMENTS
IRRITANT
IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF
WATER AND SEEK MEDICAL ADVICE.
WEAR SUITABLE PROTECTIVE CLOTHING. - - FIRST-AID MEASURES- -ECTION 4. - -IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.
IN CASE OF CONTACT, IMMEDIATELY WASH SKIN WITH SOAP AND COPIOUS AMOUNTS OF WATER.
IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.
IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CALL A PHYSICIAN. WASH CONTAMINATED CLOTHING BEFORE REUSE. ECTION 5. - FIRE FIGHTING MEASURES

SPECIAL FIREFIGHTING PROCEDURES
WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO
PREVENT CONTACT WITH SKIN AND EYES.
UNUSUAL FIRE AND EXPLOSIONS HAZARDS

CONTINUED ON NEXT PAGE

ŪŠĒ ĒXTĪNGŪĪSHĪNG MEDIA APPROPRIATE TO SURROUNDING FIRE CONDITIONS.

7901

We are Committed to the Success of our Customers through Science, Technology and Service.



EXTINGUISHING MEDIA NONCOMBUSTIBLE.











CUST#: 0-495-04629 PO#: QH5212

2

MATERIAL SAFETY DATA SHEET PAGE S0751 SODIUM PHOSPHATE MONOBASIC ANHYDROUS EMITS TOXIC FUMES UNDER FIRE CONDITIONS. SECTION 6. - - -- - ACCIDENTAL RELEASE MEASURES- -WEAR RESPIRATOR, CHEMICAL SAFETY GOGGLES, RUBBER BOOTS AND HEAVY RUBBER GLOVES. SWEEP UP, PLACE IN A BAG AND HOLD FOR WASTE DISPOSAL. AVOID RAISING DUST. VENTILATE AREA AND WASH SPILL SITE AFTER MATERIAL PICKUP IS COMPLETE. SECTION 7. - - - -- - - HANDLING AND STORAGE- -REFER TO SECTION 8. ECTION 8. - - - - - EXPOSURE CONTROLS/PERSONAL PROTECTION - -WEAR APPROPRIATE NIOSH/MSHA-APPROVED RESPIRATOR, CHEMICAL-RESISTANT GLOVES, SAFETY GOGGLES, OTHER PROTECTIVE CLOTHING.
SAFETY SHOWER AND EYE BATH.
MECHANICAL EXHAUST REQUIRED.
DO NOT BREATHE DUST.
AVOID CONTACT WITH EYES, SKIN AND CLOTHING.
AVOID PROLONGED OR REPEATED EXPOSURE.
WASH THOROUGHLY AFTER HANDLING.
KEEP TIGHTLY CLOSED.
STORE IN A COOL DRY PLACE. ECTION 9. - - - -- - PHYSICAL AND CHEMICAL PROPERTIES -APPEARANCE AND ODOR WHITE POWDER ECTION 10. - - --STABILITY AND REACTIVITY -INCOMPATIBILITIES STRONG ACIDS PROTECT FROM MOISTURE. HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS NATURE OF DECOMPOSITION PRODUCTS NOT KNOWN. HAZARDOUS POLYMERIZATION WILL NOT OCCUR. TOXICOLOGICAL INFORMATION -ACUTE EFFECTS
MAY BE HARMFUL BY INHALATION, INGESTION, OR SKIN ABSORPTION.

CONTINUED ON NEXT PAGE

CATALOG #: NAME:

STABILITY STABLE.

ECTION 11. -



CUST#: 0-495-04629 PO#: QH5212

MATERIAL SAFETY DATA SHEET

PAGE 3

CATALOG #: NAME:

S0751 SODIUM PHOSPHATE MONOBASIC ANHYDROUS MINIMUM 99.0%

CAUSES EYE AND SKIN IRRITATION.
MATERIAL IS IRRITATING TO MUCOUS MEMBRANES AND UPPER
RESPIRATORY TRACT.
TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND
TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

ECS #: WA1900000 SODIUM DIHYDROGEN PHOSPHATE (1:2:1)

IRRITATION DATA EYE-HMN 50 MG MLD EYE-RBT 150 MG MLD

ARZNAD 9,349,1959 ARZNAD 9,349,1959

TOXICITY DATA ORL-RAT LD50:8290 MG/KG IMS-RAT LD50:250 MG/KG

28ZPAK -,16,1972 EMSUA8 4,223,1946

ADDITIONAL INFORMATION
ORL-RAT LD50:7100 MG/KG
SKN-RBT LD50:>7940 MG/KG
ONLY SELECTED REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES
(RTECS) DATA IS PRESENTED HERE. SEE ACTUAL ENTRY IN RTECS FOR COMPLETE INFORMATION.

ECTION 12. - - - - ECOLOGICAL INFORMATION

DATA NOT YET AVAILABLE.

ECTION 13. -DISPOSAL CONSIDERATIONS

FOR SMALL QUANTITIES: CAUTIOUSLY ADD TO A LARGE STIRRED EXCESS OF WATER. ADJUST THE PH TO NEUTRAL, SEPARATE ANY INSOLUBLE SOLIDS OR LIQUIDS AND PACKAGE THEM FOR HAZARDOUS-WASTE DISPOSAL. FLUSH THE AQUEOUS SOLUTION DOWN THE DRAIN WITH PLENTY OF WATER. THE HYDROLYSIS AND NEUTRALIZATION REACTIONS MAY GENERATE HEAT AND FUMES WHICH CAN BE CONTROLLED BY THE RATE OF ADDITION.
OBSERVE ALL FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

ECTION 14. - - TRANSPORT INFORMATION - -

CONTACT SIGMA CHEMICAL COMPANY FOR TRANSPORTATION INFORMATION.

ECTION 15. - REGULATORY INFORMATION

EUROPEAN INFORMATION IRRITANT R 36/37/38 IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

ĬN ČASE OF CONTACT WITH EYES, WATER AND SEEK MEDICAL ADVICE. RINSE IMMEDIATELY WITH PLENTY OF

CONTINUED ON NEXT PAGE

7903

We are Committed to the Success of our Customers through Science, Technology and Service.













CUST#: 0-495-04629 PO#: QH5212

MATERIAL SAFETY DATA SHEET

PAGE

CATALOG #:

S0751 SODIUM PHOSPHATE MONOBASIC ANHYDROUS MINIMUM 99.0%

S 36 WEAR SUITABLE PROTECTIVE CLOTHING.

REVIEWS, STANDARDS, AND REGULATIONS

OEL=MAK
EPA FIFRA 1988 PESTICIDE SUBJECT TO REGISTRATION OR RE-REGISTRATION FEREAC 54,7740,1989
NOHS 1974: HZD 83818; NIS 107; TNF 9820; NOS 77; TNE 49018
NOES 1983: HZD 83818; NIS 123; TNF 13232; NOS 104; TNE 289281; TFE 145939
EPA TSCA SECTION 8(B) CHEMICAL INVENTORY

SECTION 16. - - - - - - - - OTHER INFORMATION- - - -

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SIGMA SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT. SEE REVERSE SIDE OF INVOICE OR PACKING SLIP FOR ADDITIONAL TERMS AND CONDITIONS OF SALE.

COPYRIGHT 1998 SIGMA-ALDRICH CO. LICENSE GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.

MATERIAL WAS SHIPPED TO THIS ADDRESS:
UNIV OF WISCONSIN - WHITEWATER
MIKE WOLLER
UPHAM HALL
RM 316
800 W MAIN ST
WHITEWATER
WH 53190