

1-27-06

(MSDS)

ITEM NUMBER: 063 - SOLVENT CLEANER & DEGREASER

VERSION 2 EFFECTIVE DATE: 09/21/01 SUPERCEDES: 04/22/98 PREPARED BY: Ron Cepa

Section(s) Revised: HMIS, II, III, IV, VI, VIII, IX

IDENTITY (As Used On Label and List): SOLVENT CLEANER & DEGREASER

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS): - Health = 1\*, Fire = 1, Reactivity = 0, Protective Equipment = B

(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, \* = Chronic Hazard)

\*\*\*\*\* SECTION I \*\*\*\*\*

SPRAYWAY, INC.

TELEPHONE NUMBER FOR INFORMATION : 1-800-332-9000

484 VISTA AVE.

ADDISON

DATE PRINTED : 10/10/01 NAME OF PREPARER : Ron Cepa

IL 60101

\*\*\*\*\* SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION \*\*\*\*\*

Chemical Names	CAS #	SARA	ACGIH	OSHA	% By Wt.
	SEC 313	TLV-TWA/STEL	PEL-TWA/STEL		

Trichloroethylene 79-01-6 Yes 50 ppm/100 ppm 50 ppm/200 ppm 80-100

Carbon dioxide 124-38-9 No 5000 ppm/30,000 ppm 5000 ppm/ NE 1-5

\*\*\*\*\* SECTION III - PHYSICAL CHARACTERISTICS \*\*\*\*\*

Boiling Point: NA Vapor Pressure (psig): 100 @ 130F Specific Gravity (H2O=1): 1.456 pH: NA

Solubility/Water: Negligible Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND

Appearance and Odor: Aerosol spray with characteristic odor.

\*\*\*\*\* SECTION IV - FIRE AND EXPLOSION HAZARD DATA \*\*\*\*\*

Aerosol Flammability: Product is not required to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45.

Flashpoint: <0F (Propellant); None (Concentrate)

Flammable Limits - % Volume In Air (Trichloroethylene): LEL: 7.8 UEL: 52.0

Extinguishing Media: Carbon dioxide, water spray or dry chemical.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

\*\*\*\*\* SECTION V - REACTIVITY DATA \*\*\*\*\*

Stability: Stable

Hazardous Polymerization: NA



