

M A T E R I A L   S A F E T Y   D A T A   S H E E T

SPRAY LACQUER GLOSS CLEAR

Page: 1

PRODUCT NAME: SPRAY LACQUER GLOSS CLEAR  
 PRODUCT CODE: 0917WZ

HMIS CODES: H F R P

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: ZYNOLYTE PRODUCTS COMPANY OCT 11 1995  
 ADDRESS : 2320 E. DOMINGUEZ  
           P.O. BOX 6244  
           CARSON, CA 90749  
 EMERGENCY PHONE : 303-623-5716 COLLECT DATE PRINTED : 10/04/95  
 INFORMATION PHONE : 310-513-0700 NAME OF PREPARER : John R. Kordosh  
 TRANSPORTATION EMERGENCIES: Chemtrec @ (800)-424-9300 (24 hrs)

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
2-PROPANONE OSHA PEL: 750 PPM, ACGIH TLV: 750 PPM, DuPONT TLV: 1000 STEL	67-64-1	184	68	27
* TOLUENE OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM, DuPONT TLV: 300 PPM	108-88-3	22	68	16
PROPANE OSHA PEL: 1000 PPM, ACGIH TLV: 1000 PPM, DuPONT TLV: 1000 PPM	74-98-6	200	100	14
ALIPHATIC PETROLEUM DISTILLATE BR 240-285 F OSHA PEL: 300 PPM, ACGIH TLV: 300 PPM, DuPONT TLV: 100 PPM	64742-89-8	15	100	14
N-BUTANE OSHA PEL: 1000 PPM, ACGIH TLV: 800 PPM, DuPONT TLV: 800 PPM	106-97-8	37	100	10
ISOBUTANE OSHA PEL: 1000 PPM, ACGIH TLV: 800 PPM, DuPONT TLV: 800 PPM	75-28-5	72	100	4
* 2-BUTANONE OSHA PEL: 200 PPM, ACGIH TLV: 200 PPM, DuPONT TLV: NE	78-93-3	78	68	4
* 4-METHYL-2-PENTANONE OSHA PEL: 50 PPM, ACGIH TLV: 50 PPM, DuPONT TLV: NE	108-10-1	15	68	4

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.  
 \*\*\* This MSDS complies with the OSHA Hazard Communication Standard. \*\*\* NE - None established

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING RANGE: -43 deg F - 241 deg F      SPECIFIC GRAVITY (H2O=1): 0.71  
 VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
 COATING V.O.C.: 5.54 lb/gl      MATERIAL V.O.C.: 5.54 lb/gl  
 SOLUBILITY IN WATER: Not applicable.  
 APPEARANCE AND ODOR: Aerosol can.

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: -256 deg F      METHOD USED: TCC  
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1      UPPER: 13

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

**SPECIAL FIREFIGHTING PROCEDURES**

Avoid confined spaces. Firefighters should be equiped with full protective equipment including a positive pressure NIOSH-approved self-contained breathing apparatus. Water may be unsuitable as an extinguishing medium.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Vapors are heavier than air and may accumulate in low areas of poor ventilation or travel along the ground to remote ignition sites. Contents are under pressure. Keep cool. Exposure to heat or sunlight may cause cans to burst and propell contents. Water from fog nozzles may be helpful in cooling unruptured containers to prevent pressure build-up.

=====**SECTION V - REACTIVITY DATA**=====

**STABILITY: STABLE  
CONDITIONS TO AVOID**

None reasonably foreseeable.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Strong oxidizing agents, strong acids and bases, selected amines.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

May emit fumes when heated to decomposition. May emit carbon monoxide, carbon dioxide, unidentified organic compounds.

**HAZARDOUS POLYMERIZATION: Will not occur.**

=====**SECTION VI - HEALTH HAZARD DATA**=====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: Headache, Dizziness, Nausea, Staggering gait, Lassitude, Loss of Coordination, Confusion, Unconsciousness.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. Eye watering, headaches, nausea, dizziness, etc. are signs that solvent levels are too high.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

See inhalation. Organic solvents are easily absorbed. Dry skin, redness, or dermatitis due to the defatting action of solvents are signs of exposure.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

See inhalation. May also result in gastro-intestinal distress. There is a danger of petroleum distillates entering the lungs if swallowed or vomited and causing inflammation, damage, or even death.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Reports have associated repeated and prolonged overexposure to solvent with permanent brain and nervous system damage. Laboratory studies with rats have shown that petroleum distillates cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No**

Detectable amounts of a chemical known to the State of California to cause cancer and/or reproductive harm may be present in this product.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Preeexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product.

**EMERGENCY AND FIRST AID PROCEDURES**

Inhalation: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth, call doctor. Eye: In case of eye contact, immediatly flush with plenty of water for at least 15 minutes; call a physician. Skin: In case of skin contact, wash skin with soap and water. If irritation occurs, contact a physician. Ingestion: For ingestion, call physician immediately, have names of hazardous ingredients ready, do not induce vomiting, keep head lower than waist. Aspiration of vomitus may result in chemical pneumonitis and/or pulmonary edema.

=====  
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE  
=====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Ventilate area. Remove sources of ignition, including hot metal surfaces. Wear appropriate clothing and gear. Prevent skin contact and avoid breathing of vapor. Confine immediately and remove with inert absorbant such as clay or sand.

**WASTE DISPOSAL METHOD**

Do not allow material to contaminate ground water systems. Place in non-leaking containers. Dispose of absorbed material in accordance with all Federal, State, and local requirements. Do not incinerate in closed containers.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Observe label precautions. Keep away from heat, sparks, and open flame (i.e. all ignition sources). Cap container after each use. Wash thoroughly after handling and before eating or smoking. Do not store above 120 degrees F. Store in dry, well ventilated place. Do not expose to direct sunlight to avoid bursting. Do not spray near fire or flame.

**OTHER PRECAUTIONS**

Avoid unnecessary contact. Do not take internally. Do not puncture containers. Use with adequate ventilation - do not inhale vapors. Intentional misuse by deliberately concentrating and inhaling vapors of this product may be harmful or fatal. Do not sand, flame cut, braze, or weld dry coating without a NIOSH/MSHA approved respirator or sufficient ventilation.

=====  
SECTION VIII - CONTROL MEASURES  
=====

**RESPIRATORY PROTECTION**

Do not breath vapors or mists. If the TLV, PEL, or other limits are exceeded then wear a properly fitted vapor and particulate or positive pressure air supplied respirator approved by NIOSH/MSHA for use with paints during application and until all vapors and spray mists are exhausted. Follow the respirator manufacturer's directions for proper use.

**VENTILATION**

Provide sufficient ventilation in volume and pattern to keep contaminants below applicable OSHA requirements or other suggested exposure limits. Use only explosion proof equipment with flammable materials.

**PROTECTIVE GLOVES**

Use Neoprene gloves or better. Protective creams are not recommended for protection but may be used for ease of cleanup.

**EYE PROTECTION**

Goggles are best to prevent eye irritation. When using safety glasses add splash guard, side shields, or face shield.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Apron, coveralls, or work clothes. Change clothes and shoes in case of spill, splash, or excessive overspray. Do not reuse clothing or shoes while solvent odor is retained in them. Eye washes and safety showers could also be provided.

**WORK/HYGIENIC PRACTICES**

As with all chemical products, use care in handling. Do not smoke or eat without first washing your hands.

=====  
SECTION IX - DISCLAIMER  
=====

The information in this MSDS was obtained from sources which are believed to be reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or correctness. It relates only to the material designated herein and does not relate to use in combination with any other material or process.



# Zynolyte® Products Company

*Manufacturer of Quality Paint Products*

A Member of Grow Group, Inc.

*Spray Lacquer Gloss Clear*

Date \_\_\_\_\_

*Dear Sir/Madam:*

*Enclosed you will find the Material Safety Data Sheets you recently requested. Zynolyte manufacturers a wide variety of product categories. If your request included multiple colors within the same line, you will notice that only one color is included. The only difference between colors within the same line is the pigment, a non-hazardous ingredient.*

*By taking these measures, we are able to expedite your request in a more timely manner. However, if you find it necessary to have a copy of a particular color not enclosed, please feel free to contact our Customer Service Department.*

*Thank you,*

*Customer Service  
Zynolyte Products Company*