

ITEM: 3KB54 - Stabilizer Fuel 8 Oz

MAR 30 2010

ISDS: B3268

ORDER: 0053099631

LP NUMBER: U991111422

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

SAFETY DATA SHEET - B3268

Associated Grainger Items B54

C(R\*)

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: STOR-X(R\*) FUEL STABILIZER

PRODUCT NUMBER (S): 402815

MANUFACTURED BY: CRC INDUSTRIES, INC. 5 LOUIS DRIVE W. MINSTER, PA 18974 W.CRCINDUSTRIES.COM

GENERAL INFORMATION: (215) 674-4300

TECHNICAL ASSISTANCE: (800) 521-3168

CUSTOMER SERVICE: (800) 272-8963

24-HR EMERGENCY (CHEMTREC): (800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

APPEARANCE & ODOR: RED LIQUID, PETROLEUM SOLVENT ODOR

HAZARD: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED.

AS DEFINED BY OSHA'S HAZARD COMMUNICATION STANDARD, THIS PRODUCT IS HAZARDOUS.

POTENTIAL HEALTH EFFECTS:

EYE: MAY CAUSE MILD EYE IRRITATION. SYMPTOMS INCLUDE STINGING, TEARING AND REDNESS.

SKIN: MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN.

INGESTION: MAY INCLUDE REDNESS, BURNING, DRYING AND CRACKING OF THE SKIN, OTHER SKIN DAMAGE. PASSAGE OF THIS MATERIAL INTO THE BODY THROUGH THE GASTROINTESTINAL TRACT IS POSSIBLE, BUT IT IS UNLIKELY THAT THIS WOULD RESULT IN HARMFUL EFFECTS DURING NORMAL USE.

INHALATION: BREATHING SMALL AMOUNTS OF THIS MATERIAL DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS. BREATHING LARGE AMOUNTS MAY BE HARMFUL. SYMPTOMS INCLUDE IRRITATION OF THE NOSE, THROAT AND AIRWAYS. EXTENDED EXPOSURE MAY LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION, INCLUDING DROWSINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND UNCONSCIOUSNESS.

INGESTION: INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCE, INCLUDING IRRITATION, NAUSEA, VOMITING AND DIARRHEA. THE MAJOR HEALTH THREAT OF INGESTIONS OCCURS FROM THE DANGER OF ASPIRATION OF LIQUID DROPS INTO THE LUNGS, PARTICULARLY FROM VOMITING. ASPIRATION MAY RESULT IN CHEMICAL PNEUMONIA, SEVERE LUNG DAMAGE AND EVEN DEATH.

CHRONIC EFFECTS: PROLONGED OR REPEATED EXPOSURE TO VAPORS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS.

REPRODUCTIVE ORGANS: EXPOSURE TO THIS MATERIAL (OR A COMPONENT) HAS BEEN FOUND TO CAUSE KIDNEY DAMAGE IN MALE RATS. THE MECHANISM BY WHICH THIS TOXICITY OCCURS IS SPECIFIC TO THE MALL RAT AND THE KIDNEY EFFECTS ARE NOT EXPECTED TO OCCUR IN HUMANS.

SEE SECTION 11 FOR TOXICOLOGY AND CARCINOGENICITY INFORMATION ON PRODUCT INGREDIENTS.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Table with 3 columns: COMPONENT, CAS NUMBER, % BY WT. Rows include STODDARD SOLVENT (90-98%), DROXYETHYLATED AMINOETHYLAMIDE (3-6%), and 2-BUTOXYETHANOL (1.0%).

SECTION 4: FIRST AID MEASURES

IF CONTACT: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. CALL A PHYSICIAN IF IRRITATION PERSISTS.

IF IN CONTACT: REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP AND WATER. IF SKIN IS DAMAGED, SEEK IMMEDIATE MEDICAL ATTENTION. IF SKIN IS NOT DAMAGED, WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK IMMEDIATE MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING PRIOR TO RE-USE.

IF INHALATION: MOVE PERSON TO FRESH AIR. KEEP PERSON CALM. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT GIVE OXYGEN. CALL A PHYSICIAN.

PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING. DO NOT GIVE LIQUIDS. OBTAIN IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, LEAN VICTIM FORWARD TO REDUCE THE RISK OF ASPIRATION. MONITOR FOR BREATHING DIFFICULTIES. MOUTH CAN BE RINSED TO DISSIPATE THE TASTE.

NOTE TO PHYSICIANS: TREAT SYMPTOMATICALLY. THIS PRODUCT CONTAINS 2-BUTOXYETHANOL WHICH, IF INGESTED IN SIGNIFICANT QUANTITIES, MAY RESULT IN RED BLOOD CELL HEMOLYSIS.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE PROPERTIES: IN ACCORDANCE WITH OSHA DEFINITIONS, THIS PRODUCT IS A CLASS II COMBUSTIBLE LIQUID.

FLASH POINT: 104 F (TCC)

AUTOIGNITION TEMPERATURE: 500 F

UPPER EXPLOSIVE LIMIT: 6.0 LOWER EXPLOSIVE LIMIT: 1.0

SUITABLE EXTINGUISHING MEDIA: USE EXTINGUISHERS RATED FOR CLASS B FIRES, SUCH AS DRY CHEMICAL, HALON, FIRE FIGHTING FOAM OR CO2.

PRODUCTS OF COMBUSTION: OXIDES OF CARBON

PROTECTION OF FIRE-FIGHTERS: FIREFIGHTERS SHOULD WEAR SELF-CONTAINED, NIOSH-APPROVED BREATHING APPARATUS FOR PROTECTION AGAINST SUFFOCATION AND POSSIBLE TOXIC DECOMPOSITION PRODUCTS. PROPER EYE AND SKIN PROTECTION SHOULD BE PROVIDED. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL AND TO KNOCK DOWN VAPORS WHICH MAY RESULT FROM PRODUCT DECOMPOSITION.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: USE PERSONAL PROTECTION RECOMMENDED IN SECTION 8.

ENVIRONMENTAL PRECAUTIONS: TAKE PRECAUTIONS TO PREVENT CONTAMINATION OF GROUND AND SURFACE WATERS. DO NOT FLUSH INTO SEWERS OR STORM DRAINS.

METHODS FOR CONTAINMENT & CLEAN-UP: REMOVE ALL SOURCES OF IGNITION. DIKE AREA TO CONTAIN SPILL. VENTILATE THE AREA WITH FRESH AIR. IF IN CONFINED SPACE OR LIMITED AIR CIRCULATION AREA, CLEAN-UP WORKERS SHOULD WEAR APPROPRIATE RESPIRATORY PROTECTION. RECOVER OR ABSORB SPILLED MATERIAL USING AN ABSORBENT DESIGNED FOR CHEMICAL SPILLS. PLACE USED ABSORBENTS INTO PROPER WASTE CONTAINERS.

SECTION 7: HANDLING AND STORAGE

HANDLING PROCEDURES: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. BOND AND GROUND CONTAINERS DURING PRODUCT TRANSFER TO REDUCE THE POSSIBILITY OF STATIC-INITIATED FIRE OR EXPLOSION. PROVIDE ADEQUATE VENTILATION DURING USE. DO NOT BREATHE VAPORS. WASH HANDS AFTER USE.

STORAGE PROCEDURES: STORE IN A COOL DRY AREA OUT OF DIRECT SUNLIGHT. STORE IN A WELL VENTILATED AREA. KEEP OUT OF REACH OF CHILDREN.

AEROSOL STORAGE LEVEL: NA

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Table with 7 columns: COMPONENT, TWA, OSHA STEL, TWA, ACGIH STEL, TWA, SOURCE, OTHER UNIT. Rows include STODDARD SOLVENT, HYDROXYETHYLATED AMINOETHYLAMIDE, and 2-BUTOXYETHANOL.

N.E. - NOT ESTABLISHED (C) - CEILING (S) - SKIN (V) - VACATED

ENGINEERING CONTROLS: AREA SHOULD HAVE VENTILATION TO PROVIDE FRESH AIR. USE LOCAL EXHAUST TO PREVENT ACCUMULATION OF VAPORS. USE MECHANICAL MEANS IF NECESSARY TO MAINTAIN VAPOR LEVELS BELOW THE EXPOSURE GUIDELINES. IF WORKING IN A CONFINED SPACE, FOLLOW APPLICABLE OSHA REGULATIONS

RESPIRATORY PROTECTION: NONE REQUIRED FOR NORMAL WORK WHERE ADEQUATE VENTILATION IS PROVIDED. USE NIOSH-APPROVED SELF-CONTAINED POSITIVE PRESSURE RESPIRATORS IN LOW CIRCULATION AREAS AND FOR EMERGENCIES.

EYE/FACE PROTECTION: FOR NORMAL CONDITIONS, WEAR SAFETY GLASSES. WHERE THERE IS REASONABLE PROBABILITY OF LIQUID CONTACT, WEAR SPLASH-PROOF GOGGLES.

SKIN PROTECTION: USE PROTECTIVE GLOVES SUCH AS NITRILE, NBDPRENE OR PVC. ALSO, USE FULL PROTECTIVE CLOTHING IF THERE IS PROLONGED OR REPEATED CONTACT OF LIQUID WITH SKIN.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: LIQUID  
 COLOR: RED  
 SOURCE: PETROLEUM SOLVENT  
 SPECIFIC GRAVITY: 0.768  
 VIT DILUTION POINT: >300 F  
 FREEZING POINT: ND  
 VAPOR PRESSURE: APPROX. 0.6 MMHg @ 68F  
 VAPOR DENSITY: >4 (AIR = 1)  
 EVAPORATION RATE: <1 (ETHER = 1)  
 SOLUBILITY: NEGLIGIBLE IN WATER  
 I: NA  
 VOLATILE ORGANIC COMPOUNDS:  
 %: 97.6  
 %L: 749.6  
 %S./GAL: 6.25

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE  
 CONDITIONS TO AVOID: TEMPERATURE EXTREMES, SOURCES OF IGNITION  
 INCOMPATIBLE MATERIALS: STRONG OXIDIZERS  
 HAZARDOUS DECOMPOSITION PRODUCTS:  
 CARBON MONOXIDE, CARBON DIOXIDE, VARIOUS HYDROCARBONS  
 POSSIBILITY OF HAZARDOUS REACTIONS: NO

SECTION 11: TOXICOLOGICAL INFORMATION

LONG-TERM TOXICOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT. THE FOLLOWING INFORMATION IS AVAILABLE FOR COMPONENTS OF THIS PRODUCT.

ACUTE EFFECTS:

COMPONENT	TEST	RESULT	ROUTE	SPECIES
BUTOXYETHANOL	LC50	450 PPM/4H	INHALATION	RAT
BUTOXYETHANOL	LD50	470 MG/KG	ORAL	RAT
BUTOXYETHANOL	LD50	220 MG/KG	DERMAL	RABBIT

CHRONIC EFFECTS:

MUTAGENICITY:

COMPONENT	RESULT
SHA	NONE LISTED
MRC	NONE LISTED
TP	NONE LISTED

MUTAGENICITY: NO INFORMATION AVAILABLE

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT. THE FOLLOWING INFORMATION IS AVAILABLE FOR COMPONENTS OF THIS PRODUCT.

TOXICITY:

BUTOXYETHANOL:  
 5 HR LC50, BLUEGILL SUNFISH: 1490 MG/L  
 1 HR LC50, DAPHNIA: 1720 MG/L

PERSISTENCE / DEGRADABILITY: NO INFORMATION AVAILABLE

BIOACCUMULATION / ACCUMULATION: NO INFORMATION AVAILABLE

BIODEGRADABILITY IN ENVIRONMENT: NO INFORMATION AVAILABLE

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL:  
 THIS PRODUCT IS A RCRA HAZARDOUS WASTE FOR THE IGNITABILITY AND TOXICITY CHARACTERISTICS. WASTE CODES INCLUDE D001 & D018 (0.6 PPM BENZENE). (SEE 40 CFR PART 261.20 - 261.33)

ALL DISPOSAL ACTIVITIES MUST COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS. LOCAL REGULATIONS MAY BE MORE STRINGENT THAN STATE OR NATIONAL REQUIREMENTS.

SECTION 14: TRANSPORT INFORMATION

PROPER SHIPPING DESCRIPTION:

DOT (GROUND): NOT REGULATED

SPECIAL PROVISIONS:

THIS PRODUCT IS RECLASSIFIED AS COMBUSTIBLE, BUT NO MARKINGS OR PLACARDING IS REQUIRED PER 49 CFR 173.150(F) (2).

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL:

TOXIC SUBSTANCES CONTROL ACT (TSCA):

ALL INGREDIENTS ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE EXEMPT.

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA):

REPORTABLE QUANTITIES (RQ'S) EXIST FOR THE FOLLOWING INGREDIENTS: NONE

SPILLS OR RELEASES RESULTING IN THE LOSS OF ANY INGREDIENT AT OR ABOVE ITS RQ REQUIRE IMMEDIATE NOTIFICATION TO THE NATIONAL RESPONSE CENTER (800-424-8802) AND TO YOUR LOCAL EMERGENCY PLANNING COMMITTEE.

SUPERFUND AMENDMENTS REAUTHORIZATION ACT (SARA) TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (EHS): NONE

SECTION 311/312 HAZARD CATEGORIES:

FIRE HAZARD: YES  
 REACTIVE HAZARD: NO  
 RELEASE OF PRESSURE: NO  
 ACUTE HEALTH HAZARD: YES  
 CHRONIC HEALTH HAZARD: YES

SECTION 313 TOXIC CHEMICALS:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:  
 2-BUTOXYETHANOL (GLYCOL ETHERS CATEGORY): 1%

CLEAN AIR ACT:

SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPS): NONE

STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROP 65): THIS PRODUCT MAY CONTAIN THE FOLLOWING CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NAPHTHALENE (0.016%), BENZENE (0.6 PPM)

STATE RIGHT TO KNOW:

NEW JERSEY: 800967-5341P, 800967-5548P, 8052-41-3, 111-76-2  
 PENNSYLVANIA: 8052-41-3, 111-76-2  
 MASSACHUSETTS: 8052-41-3, 111-76-2  
 RHODE ISLAND: 8052-41-3, 111-76-2

ADDITIONAL REGULATORY INFORMATION:

THIS DIESEL FUEL ADDITIVE COMPLIES WITH THE FEDERAL ULTRA-LOW SULFUR CONTENT REQUIREMENTS FOR USE IN ALL DIESEL MOTOR VEHICLES AND NON-ROAD ENGINES.

SECTION 16: OTHER INFORMATION

NFPA:  
 HEALTH 2  
 FLAMMABILITY 2  
 REACTIVITY 0

HMS:  
 HEALTH 2  
 FLAMMABILITY 2  
 REACTIVITY 0  
 PPE B

PREPARED BY: MICHELLE RUDNICK

CRC #: 587G

REVISION DATE: 12/08/2006

CHANGES SINCE LAST REVISION:

FORMULA CHANGE TO COMPLY WITH 15 PPM SULFUR STANDARD.

THE INFORMATION CONTAINED IN THIS DOCUMENT APPLIES TO THIS SPECIFIC MATERIAL AS SUPPLIED. IT MAY NOT BE VALID FOR THIS MATERIAL IF IT IS USED IN COMBINATION WITH ANY OTHER MATERIALS. THIS INFORMATION IS ACCURATE TO THE BEST OF CRC INDUSTRIES' KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY CRC TO BE ACCURATE. BEFORE USING ANY PRODUCT, READ ALL WARNINGS AND DIRECTIONS ON THE LABEL.

CAS: CHEMICAL ABSTRACT SERVICE

PPM: PARTS PER MILLION

TCC: TAG CLOSED CUP

EMCC: PENSKY-MARTENS CLOSED CUP

PPE: PERSONAL PROTECTION EQUIPMENT

TWA: TIME WEIGHTED AVERAGE

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

ACGIH: AMERICAN ASSOCIATION OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

NIOSH: NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY & HEALTH

NA: NOT APPLICABLE

ND: NOT DETERMINED

NE: NOT ESTABLISHED

G/L: GRAMS PER LITER

LBS./GAL: POUNDS PER GALLON

STEL: SHORT TERM EXPOSURE LIMIT