

MATERIAL SAFETY DATA SHEET

JAN 20 1992
JAN 20 1992

STEEL BLUE DX-100

ITW Devcon, 8501 Delport Drive, St. Louis, Missouri 63114
Emergency Telephone No.: (800) 424-9300 (CHEMTREC); Other calls: (314) 423-0100

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM RATINGS:

HEALTH: 2*
FLAMMABILITY: 3
REACTIVITY: 1
DYTSB

REVISED: December 20, 1990

SECTION 1. PRODUCT IDENTITY

TRADENAME: STEEL BLUE DX-100
CHEMICAL FAMILY: Solvent based dye.

OTHER PRODUCT INFORMATION: Brush on layout fluid.

SECTION 2. HAZARDOUS INGREDIENTS

INGREDIENT(S)	WEIGHT PCT.	CAS NO.	TLV-TWA ^{1,2}	Notes
Denatured ethyl alcohol Moderate eye irritant; severe skin irritant; flammable	40-60	64175	1000 ppm	
n-Butyl acetate Moderate skin irritant; severe eye irritant; flammable	30-60	123864	150 ppm	
n-Butyl alcohol Moderate skin irritant; severe eye irritant; flammable	1-5	71363	50 ppm	TC
Cellulose, nitrate Flammable	1-5	9004700	n/e	
Isopropyl alcohol Flammable; skin and eye irritant	1-5	67630	n/e	

- "TLV" means the Threshold Limit Value exposure (8-hour time-weighted average, unless otherwise noted) established by ACGIH. "OSHA PEL" refers to the Permissible Exposure Limits for airborne contaminants as specified in 29 CFR 1900.1000.
- "N/E" indicates that neither TLV nor OSHA Permissible Exposure Limit has been established.

NOTES: A1--human carcinogen. A2--suspect carcinogen. C--ceiling limit (not a TWA). D--the TLV applies to dusts; this ingredient is not a dust as sold in our product. S--absorption through skin may be a significant route of exposure. "TC" indicates a "Toxic Chemical" subject to the reporting requirements of SARA Section 313 (40 CFR Sec. 372).

SECTION 3. PHYSICAL PROPERTIES

BOILING POINT (F): 160
MELTING POINT (F): n/d
PERCENT SOLIDS BY WEIGHT: <5
PH (5% by weight in water): n/d
VAPOR DENSITY (Air=1): >1
SPECIFIC GRAVITY: .86
APPEARANCE AND ODOR: Intense blue liquid with sweet solvent odor.

EVAPORATION RATE (BuAc=1): >1
SOLUBILITY IN WATER: Appreciable
VAPOR PRESSURE (mmHg): 36 at 68 F

VOLATILE ORGANIC COMPOUNDS (VOC): 6.8 lbs/gal (EPA Reference Method 24)

NOTE: "n/d" = "not determined".

SECTION 4. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 57 F; METHOD: TCC

EXPLOSIVE LIMITS IN AIR: Lower--1.4;
Upper--11.2

EXTINGUISHING MEDIA: Water CO2 Foam Alcohol foam
no yes yes no

SPECIAL FIREFIGHTING PROCEDURES: Fire fighters should wear self contained breathing apparatus. Water may be used to cool fire exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along ground, or be moved by ventilation and be ignited by ignition source.

SECTION 5. HEALTH HAZARD DATA

EMERGENCY AND FIRST AID PROCEDURES--

EYES: Flush with water for 15 minutes. Contact a physician.

SKIN: Wash affected area with soap and water. If irritation persists contact a physician.

INHALATION: Remove patient to fresh air. If breathing is difficult, administer oxygen.

INGESTION: Do not induce vomiting. If vomiting occurs, keep patient's head below hips. Give plenty of water or milk. Call a physician.

SECTION 5. HEALTH HAZARD DATA (cont'd)

TOXICITY DATA--Oral LD50 (rat): In mg/kg: 7060 (EtOH); 14000 (BuAc); 790 (BuOH); 5840 (IsoPr)
 Dermal LD50 (rabbit): In mg/kg: 3400 (BuOH); 13000 (Isopropyl)
 Inhalation LC50 (rat): 8000 ppm (BuAc); Exposure time: 4 hours

SYMPTOMS OF ACUTE OVEREXPOSURE--

EYES: Moderate irritant
 SKIN: Moderate irritant
 INHALATION: High concentrations of vapors may produce irritation of the respiratory tract, headache, dizziness, and nausea.
 INGESTION: Similar to inhalation.

EFFECTS OF CHRONIC OVEREXPOSURE: Prolonged repeated overexposure to this product may lead to skin sensitization or dermatitis.

MEDICAL CONDITIONS WHICH EXPOSURE MAY AGGRAVATE: Respiratory conditions; skin disorders.

CARCINOGENICITY--OSHA regulated? no
 National Toxicology Program? no
 Ingredient(s) listed: None
 ACGIH? no
 International Agency for Research on Cancer? no

SECTION 6. REACTIVITY DATA

STABILITY: Chemically stable
 Conditions to avoid: Heat, sparks, and open flames.
 Materials to avoid: Strong oxidizing agents.
 Hazardous decomposition products: Oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: will not occur.
 Conditions to avoid: None

SECTION 7. SPILL OR LEAK PROCEDURES

SPILL CONTROL: Remove all ignition sources and ventilate the area. Wear personal protective equipment. Use absorbent material such as sand or vermiculite. Place waste in sealed containers and remove to a federal or state approved disposal facility.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

Applicable CERCLA/RCRA Hazardous Waste Codes: D001 (ignitability); U031 (Butyl alcohol)
 Reportable Quantity under CERCLA, in pounds: 100

SECTION 8. PROTECTIVE EQUIPMENT

EYES: Safety glasses or goggles.
 SKIN: Chemical resistant rubber gloves and long sleeved clothing.
 RESPIRATORY: None required for normal use with adequate ventilation. In poorly ventilated areas, use NIOSH approved organic vapor respirator.
 VENTILATION: General mechanical ventilation is adequate for normal use. Local exhaust may be required if vapor concentrations above the TLV are generated.

SECTION 9. PRECAUTIONS FOR STORAGE, HANDLING, ETC.

---Keep away from heat, sparks, and open flames.
 ---Use with adequate ventilation.

PROPER SHIPPING NAME: Paint (Containers < 1 pint are ORM-D) 1263
 D.O.T. HAZARD CLASS: Flammable liquid

ITW Devcon bases the information and recommendations in this document on data believed to be correct. No warranty of any kind, however, is made as to the information in this document.