

2 Copies

Return to Halman Lindsay Paints
MATERIAL SAFETY DATA SHEET

Rec'd 3/14/08
RM + S
1/25/08

STRIPE KOTE WHITE

Page: 1
9/27/2005

PRODUCT NAME: STRIPE KOTE WHITE
PRODUCT CODE: 305N

HMS CODES: H F R
1 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: HALLMAN/LINDSAY PAINTS
ADDRESS: P.O. BOX 109
SUN PRAIRIE, WI 53590

DATE PRINTED: 9/27/2005
NAME OF PREPARER: MICHAEL MC NULTY
INFORMATION PHONE: (608) 834-8844
EMERGENCY PHONE: 1-800-688-4005

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
TITANIUM DIOXIDE	13463-67-7		

OSHA PEL: 10 MG/M3, ACGIH TLV: 10 MG/M3, STEL TLV: N/A
*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
Sanding the cured product may produce a nuisance dust. Observe a TLV of 10 mg/m3 for total dust containing no asbestos and <1% silica. Observe a TLV of 5mg/m3 for respirable dust.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 490
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C.: 14 g/l
COATING V.O.C.: 0.12 lb/gl
SOLUBILITY IN WATER: N/A
APPEARANCE AND ODOR: LIQUID COATING WITH MILD ODOR
SPECIFIC GRAVITY (H2O=1): 1.35
EVAPORATION RATE: SLOWER THAN ETHER
DENSITY: 11.25 lb/gl

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 246
METHOD USED: seta flash
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .6 UPPER: 4.2
EXTINGUISHING MEDIA:
WATER FOG, DRY CHEMICAL, CARBON DIOXIDESPECIAL FIREFIGHTING PROCEDURES
Water spray may cool containers. Normal firefighting procedures may be used. UNUSUAL FIRE AND EXPLOSION HAZARDS
Closed containers may burst when exposed to extreme heat.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID
Keep from freezing. INCOMPATIBILITY (MATERIALS TO AVOID)
Strong oxidizing agents. HAZARDOUS DECOMPOSITION OR BYPRODUCTS
Under heat, Carbon Dioxide and Carbon Monoxide may be produced. HAZARDOUS POLYMERIZATION: Will Not Occur

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
May irritate respiratory tract (nose, throat, lungs) SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
EYE CONTACT: Short term liquid or vapor contact may result in slight irritation. Prolonged or repeated contact may be more irritating. SKIN CONTACT: May cause mild irritation to skin. Prolonged and repeated contact with skin can cause defatting and drying of the skin which may result in skin irritation and dermatitis.
SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
Can dry and defat skin causing cracks, irritation, and dermatitis. INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
DO NOT TAKE INTERNALLY HEALTH HAZARDS (ACUTE AND CHRONIC)
EFFECTS OF ACUTE EXPOSURE
EYE CONTACT.....May cause: Mild eye irritation.
SKIN.....May cause: Mild skin irritation.
INHALATION.....None known.

M A T E R I A L S A F E T Y D A T A S H E E T

STRIPE KOTE WHITE

Page: 2
9/27/2005

INGESTION.....May cause:Nausea.

CARCINOGENICITY: NTP CARCINOGEN: N/A IARC MONOGRAPHS: N/A OSHA REGULATED: N/A

CARCINOGEN CONTENT

None of the ingrediants in this product are listed as a potential carcinogen by the NTP, IARC, or OSHA

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Skin Disorders

EMERGENCY AND FIRST AID PROCEDURES

INHALATION OVEREXPOSURE-Move person to fresh air.

INGESTION-Give two glasses of water to drink. Call a physician. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SKIN CONTACT- Wash thoroughly with soap and water.

EYE CONTACT- Flush with large quantities of water for 15 minutes

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill to minimize contamination. Absorb with inert material. Collect in containers. Keep spill out of waterways.

Dispose of material in accordance with Federal, State and Local regulations.PRECAUTIONS TO BE TAKEN IN HANDLING AND STO

Avoid prolonged contact with liquid and/or vapor. KEEP FROM FREEZING.OTHER PRECAUTIONS

Never take internally. Wash thoroughly after use.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

When spraying this material use a NIOSH approved cartridge respirator to keep airborne mists and vapor concentrations below TLV values.

VENTILATION

MECHANICAL-(GENERAL)

Adequate

PROTECTIVE GLOVES

Impervious gloves

EYE PROTECTION

Safety glasses recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye WashWORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended. Wash hands thoroughly with soap and water after applying product.

===== SECTION IX - DISCLAIMER =====

This M.S.D.S. is furnished without charge to responsible persons who use it at their discretion and risk. Although the information and suggestions contained herein have been compiled, as of the issue date above, from sources believed to be reliable, there is no warranty of any kind, express or implied, as to the completeness and accuracy thereof.