

J.T.BAKER INC. 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865
M A T E R I A L S A F E T Y D A T A S H E E T
24-HOUR EMERGENCY TELEPHONE -- (201) 859-2151
CHEMTREC # (800) 424-9300 -- NATIONAL RESPONSE CENTER # (800) 424-8802

34 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 1
ISSUED: 05/17/89

J.T.BAKER INC., 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865

=====

SECTION I - PRODUCT IDENTIFICATION

=====

PRODUCT NAME: ~~SULFURIC ACID~~ Sulfuric Acid
COMMON SYNONYMS: OIL OF VITRIOL; HYDROGEN SULFATE; SULPHURIC ACID
CHEMICAL FAMILY: INORGANIC ACIDS
FORMULA: H2SO4
FORMULA WT.: 98.08
CAS NO.: 7664-93-9
NIOSH/RTECS NO.: WS5600000
PRODUCT USE: LABORATORY REAGENT
PRODUCT CODES: 9674,9685,5137,5374,9673,5030,9680,9675,9688,9686,4802,5643
9683,9679,9687,5340,9691,9684,9694,5432,9681,9681

=====

PRECAUTIONARY LABELING

=====

BAKER SAF-T-DATA* SYSTEM

HEALTH	-	3	SEVERE (POISON)
FLAMMABILITY	-	0	NONE
REACTIVITY	-	3	SEVERE (WATER REACTIVE)
CONTACT	-	4	EXTREME (CORROSIVE)

LABORATORY PROTECTIVE EQUIPMENT

GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

U.S. PRECAUTIONARY LABELING

POISON DANGER
CAUSES SEVERE BURNS. REACTS VIOLENTLY WITH WATER. HARMFUL IF SWALLOWED OR INHALED. CONTACT WITH OTHER MATERIALS MAY CAUSE FIRE.
DO NOT GET IN EYES, ON SKIN, ON CLOTHING. DO NOT BREATHE VAPOR. KEEP IN TIGHTLY CLOSED CONTAINER. LOOSEN CLOSURE CAUTIOUSLY. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. IN CASE OF SPILL NEUTRALIZE WITH SODA ASH OR LIME AND PLACE IN DRY CONTAINER.

INTERNATIONAL LABELING

AVOID CONTACT WITH EYES. AFTER CONTACT WITH SKIN, WASH IMMEDIATELY WITH PLENTY OF WATER. KEEP CONTAINER TIGHTLY CLOSED.

CONTINUED ON PAGE: 2

34 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 2
ISSUED: 05/17/89

=====

PRECAUTIONARY LABELING (CONTINUED)

=====

SAF-T-DATA* STORAGE COLOR CODE: WHITE (CORROSIVE)

=====

SECTION II - COMPONENTS

=====

COMPONENT	CAS NO.	WEIGHT %	OSHA/PEL	ACGIH/TLV
SULFURIC ACID	7664-93-9	90-98	1 MG/M3	1 MG/M3
WATER	7732-18-5	2-10	N/E	N/E

=====

SECTION III - PHYSICAL DATA

=====

BOILING POINT: 327 C (620 F) (AT 760 MM HG)	VAPOR PRESSURE (MMHG): <0.3 (20 C)
MELTING POINT: -2 C (28 F) (AT 760 MM HG)	VAPOR DENSITY (AIR=1): 3.4
SPECIFIC GRAVITY: 1.84 (H2O=1)	EVAPORATION RATE: <1 (BUTYL ACETATE = 1)
SOLUBILITY(H2O): COMPLETE (100%)	% VOLATILES BY VOLUME: N/A (21 C)
PH: 1.0 (0.1M SOLUTION)	
ODOR THRESHOLD (P.P.M.): N/A	PHYSICAL STATE: LIQUID
COEFFICIENT WATER/OIL DISTRIBUTION: N/A	
APPEARANCE & ODOR: CLEAR, COLORLESS TO YELLOW VISCOUS LIQUID. ODORLESS.	

=====

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

=====

FLASH POINT (CLOSED CUP): N/A	NFPA 704M RATING: 3-0-2 w
AUTOIGNITION TEMPERATURE: N/A	

CONTINUED ON PAGE: 3

J.T.BAKER INC. 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865
M A T E R I A L S A F E T Y D A T A S H E E T
24-HOUR EMERGENCY TELEPHONE -- (201) 859-2151
CHEMTREC # (800) 424-9300 -- NATIONAL RESPONSE CENTER # (800) 424-8802

234 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 3
ISSUED: 05/17/89

=====

SECTION IV - FIRE AND EXPLOSION HAZARD DATA (CONTINUED)

=====

FLAMMABLE LIMITS: UPPER - N/A LOWER - N/A

FIRE EXTINGUISHING MEDIA
USE DRY CHEMICAL OR CARBON DIOXIDE. DO NOT USE WATER.

SPECIAL FIRE-FIGHTING PROCEDURES
FIREFIGHTERS SHOULD WEAR PROPER PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE. DO NOT GET WATER INSIDE CONTAINERS.

UNUSUAL FIRE & EXPLOSION HAZARDS
REACTS WITH MOST METALS TO PRODUCE HYDROGEN GAS, WHICH CAN FORM AN EXPLOSIVE MIXTURE WITH AIR. A VIOLENT EXOTHERMIC REACTION OCCURS WITH WATER. SUFFICIENT HEAT MAY BE PRODUCED TO IGNITE COMBUSTIBLE MATERIALS.

TOXIC GASES PRODUCED
SULFUR DIOXIDE, HYDROGEN

EXPLOSION DATA-SENSITIVITY TO MECHANICAL IMPACT
NONE IDENTIFIED.

EXPLOSION DATA-SENSITIVITY TO STATIC DISCHARGE
NONE IDENTIFIED.

=====

SECTION V - HEALTH HAZARD DATA

=====

THRESHOLD LIMIT VALUE (TLV/TWA): 1 MG/M3

SHORT-TERM EXPOSURE LIMIT (STEL): NOT ESTABLISHED

PERMISSIBLE EXPOSURE LIMIT (PEL): 1 MG/M3

TOXICITY OF COMPONENTS

ORAL RAT LD50 FOR SULFURIC ACID	2140 MG/KG
INHALATION-2HR MOUSE LC50 FOR SULFURIC ACID	320 MG/M3
INHALATION-2HR RAT LC50 FOR SULFURIC ACID	510 MG/M3
INTRAPERITONEAL MOUSE LD50 FOR WATER	190 G/KG
INTRAVENOUS MOUSE LD50 FOR WATER	25 G/KG

CONTINUED ON PAGE: 4

34 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 4
ISSUED: 05/17/89

=====

SECTION V - HEALTH HAZARD DATA (CONTINUED)

=====

CARCINOGENICITY: NTP: NO IARC: NO Z LIST: NO OSHA REG: NO

CARCINOGENICITY
NONE IDENTIFIED.

REPRODUCTIVE EFFECTS
NONE IDENTIFIED.

EFFECTS OF OVEREXPOSURE

INHALATION: SEVERE IRRITATION OR BURNS OF RESPIRATORY SYSTEM,
PULMONARY EDEMA, LUNG INFLAMMATION

SKIN CONTACT: SEVERE BURNS

EYE CONTACT: SEVERE BURNS

SKIN ABSORPTION: NONE IDENTIFIED

INGESTION: NAUSEA, VOMITING, SEVERE BURNS TO MOUTH, THROAT, AND
STOMACH, KIDNEY DYSFUNCTION

CHRONIC EFFECTS: LUNG DAMAGE

TARGET ORGANS
RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, TEETH, KIDNEYS

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
RESPIRATORY SYSTEM DISEASE

PRIMARY ROUTES OF ENTRY
INHALATION, INGESTION, EYE CONTACT, SKIN CONTACT

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: CALL A PHYSICIAN. IF SWALLOWED, DO NOT INDUCE VOMITING. IF
CONSCIOUS, GIVE LARGE AMOUNTS OF WATER.

INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE
ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE
OXYGEN.

CONTINUED ON PAGE: 5

J.T.BAKER INC. 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865
M A T E R I A L S A F E T Y D A T A S H E E T
24-HOUR EMERGENCY TELEPHONE -- (201) 859-2151
CHEMTREC # (800) 424-9300 -- NATIONAL RESPONSE CENTER # (800) 424-8802

234 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 5
ISSUED: 05/17/89

=====

SECTION V - HEALTH HAZARD DATA (CONTINUED)

=====

SKIN CONTACT: IN CASE OF CONTACT, IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. WASH CLOTHING BEFORE RE-USE.

EYE CONTACT: IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.

SARA/TITLE III HAZARD CATEGORIES AND LISTS

ACUTE: YES CHRONIC: YES FLAMMABILITY: NO PRESSURE: NO REACTIVITY: YES
EXTREMELY HAZARDOUS SUBSTANCE: YES CONTAINS SULFUR ACID (RQ = 1,000 LBS, TPO = 1,000 LBS)
CERCLA HAZARDOUS SUBSTANCE: YES CONTAINS SULFURIC ACID (RQ = 1000 LBS)
TOXIC CHEMICALS: YES CONTAINS SULFURIC ACID
GENERIC CLASS: C16
TSCA INVENTORY: YES

=====

SECTION VI - REACTIVITY DATA

=====

STABILITY: STABLE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: MOISTURE, HEAT
INCOMPATIBLES: WATER, MOST COMMON METALS, ORGANIC MATERIALS, STRONG REDUCING AGENTS, COMBUSTIBLE MATERIALS, STRONG BASES, CARBONATES, SULFIDES, CYANIDES, STRONG OXIDIZING AGENTS, CARBIDES

DECOMPOSITION PRODUCTS: OXIDES OF SULFUR, HYDROGEN

=====

SECTION VII - SPILL & DISPOSAL PROCEDURES

=====

STEPS TO BE TAKEN IN THE EVENT OF A SPILL OR DISCHARGE
WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DO NOT USE WATER.
NEUTRALIZE SPILL AND/OR WASHINGS WITH SODA ASH OR LIME.

CONTINUED ON PAGE: 6

34 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 6
ISSUED: 05/17/89

=====
SECTION VII - SPILL & DISPOSAL PROCEDURES (CONTINUED)
=====

WITH CLEAN SHOVEL, PLACE MATERIAL INTO CLEAN, DRY CONTAINER AND COVER.
MOVE CONTAINER(S) FROM SPILL AREA.

J. T. BAKER NEUTRASORB(R) OR TEAM* 'LOW NA+' ACID NEUTRALIZERS ARE RECOMMENDED FOR SPILLS OF THIS PRODUCT.

DISPOSAL PROCEDURE
DISPOSE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS.

EPA HAZARDOUS WASTE NUMBER: D002, D003 (CORROSIVE, REACTIVE WASTE)

=====
SECTION VIII - INDUSTRIAL PROTECTIVE EQUIPMENT
=====

VENTILATION: USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

RESPIRATORY PROTECTION: NONE REQUIRED WHERE ADEQUATE VENTILATION CONDITIONS EXIST. IF AIRBORNE CONCENTRATION EXCEEDS TLV, A SELF-CONTAINED BREATHING APPARATUS IS ADVISED.

EYE/SKIN PROTECTION: SAFETY GOGGLES AND FACE SHIELD, UNIFORM, PROTECTIVE SUIT, RUBBER GLOVES ARE RECOMMENDED.

=====
SECTION IX - STORAGE AND HANDLING PRECAUTIONS
=====

SAF-T-DATA* STORAGE COLOR CODE: WHITE (CORROSIVE)

STORAGE REQUIREMENTS
KEEP CONTAINER TIGHTLY CLOSED. STORE IN CORROSION-PROOF AREA. KEEP CONTAINERS OUT OF SUN AND AWAY FROM HEAT. ISOLATE FROM INCOMPATIBLE MATERIALS.

CONTINUED ON PAGE: 7

J.T.BAKER INC. 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865
M A T E R I A L S A F E T Y D A T A S H E E T
24-HOUR EMERGENCY TELEPHONE -- (201) 859-2151
CHEMTREC # (800) 424-9300 -- NATIONAL RESPONSE CENTER # (800) 424-8802

34 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 7
ISSUED: 05/17/89

=====
SECTION X - TRANSPORTATION DATA AND ADDITIONAL INFORMATION
=====

DOMESTIC (D.O.T.)

PROPER SHIPPING NAME: SULFURIC ACID
HAZARD CLASS: CORROSIVE MATERIAL (LIQUID)
UN/NA: UN1830 REPORTABLE QUANTITY: 1000 LBS.
LABELS: CORROSIVE
REGULATORY REFERENCES: 49CFR 172.101; 173.272

INTERNATIONAL (I.M.O.)

PROPER SHIPPING NAME: SULPHURIC ACID
HAZARD CLASS: 8 I.M.O. PAGE: 8220
UN: UN1830 MARINE POLLUTANTS: NO PACKAGING GROUP: II
LABELS: CORROSIVE
REGULATORY REFERENCES: 49CFR 172.102; PART 176; IMO

AIR (I.C.A.O.)

PROPER SHIPPING NAME: SULPHURIC ACID
HAZARD CLASS: 8
UN: UN1830 PACKAGING GROUP: II
LABELS: CORROSIVE
REGULATORY REFERENCES: 49CFR 172.101; 173.6; PART 175; ICAO/IATA

U.S. CUSTOMS HARMONIZATION NUMBER: 28070000001

=====
N/A = NOT APPLICABLE OR NOT AVAILABLE
N/E = NOT ESTABLISHED

THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET MEETS THE REQUIREMENTS OF THE UNITED STATES OCCUPATIONAL SAFETY AND HEALTH ACT AND REGULATIONS PROMULGATED THEREUNDER (29 CFR 1910.1200 ET. SEQ.) AND THE CANADIAN WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PERSON TRAINED IN, OR SUPERVISED BY A PERSON TRAINED IN, CHEMICAL HANDLING. THE USER IS RESPONSIBLE FOR DETERMINING THE PRECAUTIONS AND DANGERS OF THIS CHEMICAL FOR HIS OR HER PARTICULAR APPLICATION. DEPENDING ON USAGE, PROTECTIVE CLOTHING INCLUDING EYE AND FACE GUARDS AND RESPIRATORS MUST BE USED TO AVOID CONTACT WITH MATERIAL OR BREATHING CHEMICAL VAPORS/FUMES.

EXPOSURE TO THIS PRODUCT MAY HAVE SERIOUS ADVERSE HEALTH EFFECTS. THIS CHEMICAL MAY INTERACT WITH OTHER SUBSTANCES. SINCE THE POTENTIAL USES

CONTINUED ON PAGE: 8

J.T.BAKER INC. 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865
M A T E R I A L S A F E T Y D A T A S H E E T
24-HOUR EMERGENCY TELEPHONE -- (201) 859-2151
CHEMTREC # (800) 424-9300 -- NATIONAL RESPONSE CENTER # (800) 424-8802

30234 D04
EFFECTIVE: 05/01/89

SULFURIC ACID

PAGE: 8
ISSUED: 05/17/89

=====

ARE SO VARIED, BAKER CANNOT WARN OF ALL OF THE POTENTIAL DANGERS OF USE OR INTERACTION WITH OTHER CHEMICALS OR MATERIALS. BAKER WARRANTS THAT THE CHEMICAL MEETS THE SPECIFICATIONS SET FORTH ON THE LABEL. BAKER DISCLAIMS ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED WITH REGARD TO THE PRODUCT SUPPLIED HEREUNDER, ITS MERCHANTABILITY OR ITS FITNESS FOR A PARTICULAR PURPOSE. THE USER SHOULD RECOGNIZE THAT THIS PRODUCT CAN CAUSE SEVERE INJURY AND EVEN DEATH, ESPECIALLY IF IMPROPERLY HANDLED OR THE KNOWN DANGERS OF USE ARE NOT HEDED. READ ALL PRECAUTIONARY INFORMATION. AS NEW DOCUMENTED GENERAL SAFETY INFORMATION BECOMES AVAILABLE, BAKER WILL PERIODICALLY REVISE THIS MATERIAL SAFETY DATA SHEET. IF YOU HAVE ANY QUESTIONS, PLEASE CALL CUSTOMER SERVICE (1-800-JTBAKER) FOR ASSISTANCE.

COPYRIGHT 1989 J.T.BAKER INC.
* TRADEMARKS OF J.T.BAKER INC.

===
APPROVED BY QUALITY ASSURANCE DEPARTMENT.

-- LAST PAGE --