


APR 10 1995



SYNCO CHEMICAL CORPORATION



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SUPER LUBE AEROSOL WITH HEPTANE

-----SECTION I - MANUFACTURER IDENTIFICATION-----

MANUFACTURER'S NAME: SYNCO CHEMICAL CORPORATION
ADDRESS: 24 DaVINCI DRIVE, BOHEMIA, NY 11716
EMERGENCY PHONE: 516-567-5300 INFORMATION PHONE 516-567-5300
DATE PREPARED: 02-13-92
DATE ISSUED: 04-08-94
REASON REVISED: UPDATE

-----SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION-----

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	WEIGHT PERCENT
Synthetic Hydrocarbon			
Polyalphaolefin Base Fluid	68037-01-4	5 MG/M ³	31
Fumed Silica	68611-44-9	10 MG/M ³	3
Polytetrafluoroethylene	9002-84-0		2
Heptane	142-82-5	400 PPM	61
Carbon Dioxide	124-38-9	10000 PPM	3

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

-----SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS-----

BOILING POINT: Not Applicable/Is not a liquid
SPECIFIC GRAVITY (H₂O=1): Not Determinable
VAPOR DENSITY: Heavier than air
EVAPORATION RATE: Slower than Ether
SOLUBILITY IN WATER: NIL
APPEARANCE AND ODOR: AEROSOL PRODUCT
NFPA RATING - Level 3

-----SECTION IV - FIRE AND EXPLOSION HAZARD DATA-----

FLASH POINT: Not Determinable METHOD USED: None
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/D UPPER: N/D

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Water spray may be ineffective. Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. If water is used, fog nozzles preferred. Wear goggles and self-contained breathing apparatus.



**Super
Lube®**

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapor accumulation can flash or explode is ignited. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention.

-----SECTION V - REACTIVITY DATA-----

STABILITY: STABLE

CONDITIONS TO AVOID

Application to hot surfaces. Storage above 120 Deg F. Exposure to open flame.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May product fumes when heated to decomposition. Fumes may contain carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur

-----SECTION VI - HEALTH HAZARD DATA-----

INHALATION HEALTH RISKS AND SYMPTONS OF EXPOSURE

Respiratory irritation, Headache, Nausea, Fatigue, Drowsiness, Impaired Co-ordination.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTONS OF EXPOSURE

SKIN: Contact may dry the skin; Prolonged contact may cause moderate irritation.

EYES: Liquid or vapor can cause moderate to severe irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTONS OF EXPOSURE

Not easily absorbed. Solvent action can dry and defat the skin causing the skin to crack, leading to dermatitis.

INGESTION HEALTH RISKS AND SYMPTONS OF EXPOSURE

Not a likely route of exposure. If swallowed, do not induce vomiting. Seek immediate medical advice and/or attention.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: Eye irritant. Possible skin irritant

CHRONIC: None Known

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

None known.



**Super
Lube®**

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

SKIN: Wipe off with towel. Wash with soap and water. Get medical attention if irritation persists.

EYES: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

-----SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Avoid breathing vapors. Ventilate area. Remove all sources of ignition. Clean up area with absorbent material and place in closed containers for disposal.

WASTE DISPOSAL METHOD

Dispose of in accordance with Local, State and Federal Regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store and use in cool, dry, well-ventilated areas. Do not store above 120 Def F. Do not puncture or incinerate (burn) cans. Do not stick pin, nail or any other sharp object into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

OTHER PRECAUTIONS

Small pressurized containers of flammable products may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation except that they should not be stored in basements.

-----SECTION VIII - CONTROL MEASURES-----

RESPIRATORY PROTECTION

None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV Limits.

VENTILATION

Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.

PROTECTIVE GLOVES

None under normal use. Solvent resistant required for prolonged or repeated contact.



**Super
Lube®**

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

None under normal use; however, use of safety glasses with splash guards or full face shield is recommended.

WORK/HYGENIC PRACTICES

Eye washes and safety showers in the work place are recommended.

-----SECTION IX -

DISCLAIMER-----

DISCLAIMER

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.