

MATERIAL SAFETY DATA SHEET

TASKI P44		92007-US			
PRODUCT INFORMATION					
Product Type:	Cleans and Restores Resilient Floor	Emergency Phone Number: 1-800-228-5635, ext. 072			
Manufactured By:	Lever Industrial Inc. 1151 Green Valley Rd. London, Ontario N6A 4C2 (519) 668-6211	Distributed By:	Lever Industrial Co., 7450 Industry Drive, North Charleston, SC 29418-8431 1-800-827-5487		
PREPARATION INFORMATION					
Prepared On:	07/17/92	Supersedes:	09/05/91		
Prepared By:	Technical Department, Lever Industrial Inc.	The information here is presented in good faith, but no warranty, expressed or implied is given.			
NAV = Not Available		NAP = Not Applicable			
DOT = Department of Transportation					
HAZARDOUS INGREDIENTS					
<u>Ingredient</u>	<u>CAS #</u>	<u>% Optional</u>	<u>OSHA:PEL</u>	<u>OSHA:STEL</u>	<u>ACGIH:TWA</u>
Isopropyl Alcohol	67-63-0*	2%	400 ppm	500 ppm	400 ppm
Petroleum Distillates	64742-47-8	> 1%	NAV	NAV	NAV
* Material reportable under SARA Title III, Section 313.					
PHYSICAL DATA					
Physical State:	Liquid	Specific Gravity:	0.917		
Vapor Pressure:	NAV	Coeff. of Water/Oil Dist.:	NAV		
Vapor Density:	NAV	Evaporation Rate:	NAV		
Boiling Point:	208.4°F (98°C)	Freezing Point:	NAV		
pH:	9.0 - 10.0	Solubility in Water:	Miscible		
Appearance & Odor:	Milky white liquid; perfumed.				
FIRE AND EXPLOSION HAZARD DATA					
Flash Point:	105.8°F (41°C)	Upper Explosion Limit:	NAV		
Lower Explosion Limit:	NAV	Hazardous Combustion Products:	Carbon dioxide, carbon monoxide		
Exinction Media:	Carbon dioxide, dry chemical, foam				
Conditions to Avoid:	Heat, open flames, sources of ignition				
Special Fire Fighting Procedures:	Wear a self-contained breathing apparatus.				
Unusual Fire and Explosion Hazards:	May flash back. Treat as oil fire.				
TOXICOLOGICAL PROPERTIES					
Route of Entry:	Eye contact, skin contact, ingestion, inhalation.				
Effects of Acute Exposure:	Eyes: irritation. Skin: no irritation expected. Ingestion: gastrointestinal irritation. Inhalation: respiratory irritation.				
Effects of Chronic Exposure:	Prolonged and repeated contact may cause irritation				
Carcinogenicity:					
NTP?:	No				
IARC Monographs?:	No				
OSHA Regulated?:	No				
Signs and Symptoms of Exposure:					
Eyes:	Irritation				
Skin:	Irritation				
Ingestion:	May result in vomiting.				
Inhalation:	Headache, dizziness				
Medical Conditions Generally Aggravated by Exposure:	None known				

FIRST AID MEASURES

Eye Contact: Rinse immediately with water, remove contact lenses if any, continue rinsing with water for at least 15 minutes while holding eyelids open. Contact a physician immediately.

Skin Contact: Wash with water. If irritation persists contact a physician.

Ingestion: Do not induce vomiting. If conscious, give large amounts of water. Never give anything by mouth if person is unconscious. Contact a physician immediately.

Inhalation: Move person to fresh air. If severe contact a physician.

PREVENTIVE MEASURES

Engineering Controls: Use local exhaust ventilation.

Protective Equipment:

Respiratory: Wear a self-contained breathing apparatus in high use concentration.

Eye: Safety goggles

Gloves: Rubber, Neoprene, Plastic, if necessary

Footwear: Boots, if necessary

Clothing: Apron, coveralls, if necessary

Other: Eye wash fountains and safety showers are recommended

Handling Procedures: Avoid ingestion and inhalation. Wear appropriate protective equipment to avoid eye and skin contact. Avoid generating airborne mists.

Storage Requirements: Store in original container in a cool, dry place away from incompatible products. Do not store below 41°F (5°C).

Leak and Spill Procedure: Confine spilled product to prevent environmental contamination. Keep out of storm sewers or surface waters. Small amount should be swept or mopped up and used for related cleaning tasks where possible. Larger amounts should be absorbed on vermiculite, clay, etc., and disposed of as industrial waste. If spilled material has been discharged into the natural environment, notify municipal, state and federal agencies as required by law.

Waste Disposal: Waste cleaning products are classed as industrial waste. Dispose in accordance with local/state and federal regulations. Registration of wastes is generally required by law prior to transportation or disposal. Consult a licensed waste disposal service.

REACTIVITY DATA

Conditions of Instability: Stable

Incompatible Materials: Strong oxidizing agents, heat, open flames, sources of ignition

Conditions of Reactivity: Vapors are flammable.

Hazardous Decomposition Products: None

SPECIAL SHIPPING INFORMATION

<u>DOT</u>	<u>DOT Shipping Name</u>	<u>DOT Hazard Class</u>	<u>DOT Label</u>	<u>ID #</u>
Yes	COMBUSTIBLE LIQUID, N.O.S. (Isopropyl Alcohol, Petroleum Distillates)	Combustible Liquid	None	NA 1993

TASKI P44**92007-US**