

MATERIAL SAFETY DATA SHEET

TASKI PROFI

92009, 92023, 92029-US

PRODUCT INFORMATION

Product Use: Oil and Grease Remover Emergency Phone Number: 1-800-228-5635 ext. 072

Supplied By: Lever Industrial Inc. Distributed By: Lever Industrial Co.
 1151 Green Valley Road 7450 Industry Drive
 London, Ontario N6A 4C2 North Charleston, SC 29418-8431
 (519) 668-6211 1-800-827-5487

PREPARATION INFORMATION

Prepared On: 07/17/92 Supersedes: 08/22/91

Prepared By: Technical Department, The information here is presented in good faith, but no warranty, expressed or implied
 Lever Industrial Inc. is given.

NAV = Not Available NAP = Not Applicable DOT = Department of Transportation

HAZARDOUS INGREDIENTS

Ingredient	CAS #	% Optional	OSHA:PEL	OSHA:STEL	ACGIH:TWA
Nonyl Phenol Polyethylene Glycol Ether	9016-45-9	> 1	NAV	NAV	NAV

PHYSICAL DATA

Physical State:	Liquid	Specific Gravity:	1.042
Vapor Pressure:	NAV	Coeff. of Water/Oil Dist.:	NAV
Vapor Density:	NAV	Evaporation Rate:	NAV
Boiling Point:	212°F (100°C)	Freezing Point:	NAV
pH:	8.6 - 9.0	Solubility in Water:	Miscible
Appearance & Odor:	Milky white liquid; perfumed.		

FIRE AND EXPLOSION HAZARD DATA

Flash Point:	NAV	Upper Explosion Limit:	NAV
Lower Explosion Limit:	NAV	Hazardous Combustion Products:	Carbon dioxide, carbon monoxide
Exinction Media:	Carbon dioxide, dry chemical, foam, water		
Conditions to Avoid:	None		
Special Fire Fighting Procedures:	Wear a self-contained breathing apparatus and full protective-equipment.		
Unusual Fire and Explosion Hazards:	NAV		

TOXICOLOGICAL PROPERTIES

Route of Entry: Eye contact, skin contact, ingestion, inhalation.

Effects of Acute Exposure: Eye: mild irritant. Skin: no irritation expected. Ingestion: gastrointestinal irritant. Inhalation: possible irritant of respiratory tract.

Effects of Chronic Exposure: Prolonged and repeated exposure on skin may cause irritation.

Carcinogenicity:

NTP?: No

IARC Monographs?: No

OSHA Regulated?: No

Signs and Symptoms of Exposure:

Eyes: Causes mild irritation.

Skin: Prolonged and repeated exposure may cause irritation.

Ingestion: Causes gastrointestinal irritation, nausea, vomiting and diarrhea.

Inhalation: May cause nasal and respiratory irritation.

Medical Conditions Generally Aggravated by Exposure: None known

FIRST AID MEASURES

Eye Contact: Rinse immediately with water. Remove contact lenses if any, and continue rinsing with water for 15 minutes while holding eyelids open. Contact a physician immediately.

Skin Contact: Wash with water. If irritation persists, contact a physician.

Ingestion: Do not induce vomiting. Give large amounts of water. Contact a physician immediately.

Inhalation: Move person to fresh air. If severe, contact a physician.

PREVENTIVE MEASURES

Engineering Controls: General ventilation should be adequate. Local exhaust where dusts exist.

Protective Equipment:

Respiratory: None required

Eye: Safety goggles

Gloves: Impervious, Rubber, Neoprene, Plastic, if necessary

Footwear: Boots, if necessary

Clothing: Apron, coveralls, if necessary

Other: Eye wash fountains and safety showers are recommended

Handling Procedures: Avoid ingestion and inhalation. Wear appropriate protective equipment to avoid eye and skin contact. Avoid generating airborne mists.

Storage Requirements: Store in original container in a cool, dry place away from incompatible products. Do not store below 50°F (10°C).

Leak & Spill Procedure: Confine spilled product to prevent environmental contamination. Keep out of storm sewers or surface waters. Small amount should be swept or mopped up and used for related cleaning tasks where possible. Larger amounts should be absorbed on vermiculite, clay, etc., and disposed of as industrial waste. If spilled material has been discharged into the natural environment, notify municipal, state and federal agencies as required by law.

REACTIVITY DATA

Conditions of Instability: Stable

Incompatible Materials: None

Conditions of Reactivity: None

Hazardous Decomposition Products: None

SPECIAL SHIPPING INFORMATION

<u>DOT</u>	<u>DOT Shipping Name</u>	<u>DOT Label</u>	<u>DOT Hazard Class</u>	<u>I.D. #</u>
No	NAP	NAP	NAP	NAP

TASKI PROF1

92009, 92023, 92029-US