

S.C. Johnson Wax
 Racine, Wisconsin 53403-5011
 Phone: (414) 631-2777
 Emergency Phone: (800) 228-5635
 Extension 092
 International Emergency Phone:
 Extension 092

4=Very High
 3=High
 2=Moderate
 1=Slight
 0=Insignificant

HAZARD RATING		
HMIS	NFPA	
0 Health	0	0
0 Flammability	0	0
0 Reactivity	0	0

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: TECHNIQUE BASE COAT				PRODUCT CODE: 14140-3-4 to 14144-3-4	
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 01/13/93	SUPERSEDES: 01/23/92	MSDS SECTIONS WITH CHANGES: V	PREPARED BY: Terry A. Meyers Chemical Info. Adm.	

SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Styrene\Acrylic Polymers (CAS# N/ACAS)	10-20	ND
Tributoxyethyl Phosphate (CAS# 78-51-3)	1-3	NOT ESTABLISHED
Diethylene Glycol Monoethyl Ether (CAS# 111-90-0CAS)	3-6	30 ppm (Supplier Recommended)
Water (CAS# 7732-18-5CAS)	70-80	NA
[SARA, PA, NJ, MA] Zinc Oxide (CAS# 1314-13-2)	0.2-0.6	5 MG/M3 ACGIH/OSHA TWA (ZINC OXIDE FUME), 10 MG/M3 ACGIH/OSHA STEL (ZINC OXIDE FUME), 10 MG/M3 ACGIH/OSHA TWA (TOTAL DUST), 5 MG/M3 OSHA TWA (RESPIRABLE DUST)
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Milky-white, opaque liquid with mild odor	SPECIFIC GRAVITY (H2O=1): 1.05
VAPOR PRESSURE (mm Hg): Same as water	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Complete	VAPOR DENSITY (Air=1): Same as water
FREEZING POINT (°F): 32	BOILING POINT (°F): above 200
pH: 8.4- 9.2	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): Glycol Ether (CAS 111-90-0)	THEORETICAL VOC (lb/gal): ND

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): NA

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin 53403	TECHNIQUE BASE COAT Product Number: 14140 Serial Number: 3-4
---	--

SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)

FLAMMABLE LIMITS:	NA
EXTINGUISHING MEDIA:	Foam, CO2, Dry Chemical, Water Fog.
SPECIAL FIREFIGHTING PROCEDURES:	Normal fire fighting procedures may be used.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	No special hazards known.

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY:	Skin contact.
SIGNS AND SYMPTOMS:	Prolonged or repeated contact of undiluted product with skin may cause minor irritation.
FIRST AID PROCEDURES:	Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. Wash skin with plenty of water. If irritation persists, seek medical aid. If product is swallowed, drink large amounts of water or milk and seek medical aid.
MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:	None known to S.C. Johnson Wax

SECTION VI-REACTIVITY DATA

STABILITY:	Stable
STABILITY-CONDITIONS TO AVOID:	None known
INCOMPATIBILITY:	None known
HAZARDOUS DECOMPOSITION PRODUCTS:	When exposed to fire, produces normal products of combustion.
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID:	None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:	Contains ammonia and zinc. Do not let spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.
WASTE DISPOSAL INFORMATION:	No special method. Observe all applicable Federal/State regulations and Local ordinances regarding disposal of non-hazardous materials. Waste from normal product use may be sewerred to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	No special requirements under normal use conditions.
VENTILATION:	General room ventilation adequate.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin 53403	TECHNIQUE BASE COAT Product Number: 14140 Serial Number: 3-4
---	--

SECTION VIII-SPECIAL PROTECTION INFORMATION (cont.)

PROTECTIVE GLOVES:	If prolonged or repeated contact is possible: Any impervious material.
EYE PROTECTION:	No special requirements under normal use conditions.
OTHER PROTECTIVE MEASURES:	Use good personal hygiene practices.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING:	NA
OTHER HANDLING AND STORAGE CONDITIONS:	Store in a cool, dry place with adequate ventilation. Keep from freezing.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION:	NA
EPA REGISTRATION #:	NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS:	Non Regulated.
DOT #:	NA
SHIPPING NAME:	Buffing or polishing compounds, NOI.

SECTION XII-REGULATORY INFORMATION

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NJ - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

SARA - These ingredients are subject to the reporting requirements under the Superfund Amendments and Reauthorization Act of 1986 Title III, Section 313 and 40 CFR Part 372.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.
R-106 (Rev 5 - 10/90)