

TRU-TEST MANUFACTURING -- 015 TRU-TEST SUPREME WOODSMAN SANDING SEALER - CLEAR SANDI  
MATERIAL SAFETY DATA SHEET  
NSN: 801000F021258  
Manufacturer's CAGE: TRUTE  
Part No. Indicator: A  
Part Number/Trade Name: 015 TRU-TEST SUPREME WOODSMAN SANDING SEALER

=====  
General Information  
=====

Item Name: CLEAR SANDING SEALER  
Company's Name: TRU-TEST MANUFACTURING CO  
Company's Street: 201 JANDUS RD  
Company's City: CARY  
Company's State: IL  
Company's Zip Code: 60013  
Company's Emerg Ph #: (800) 228-5635  
Company's Info Ph #: (708) 639-5383  
Record No. For Safety Entry: 001  
Tot Safety Entries This Stk#: 001  
Date MSDS Prepared: 25JUL90  
Safety Data Review Date: 06FEB92  
Preparer's Company: TRU-TEST MANUFACTURING CO  
Preparer's St Or P. O. Box: 201 JANDUS RD  
Preparer's City: CARY  
Preparer's State: IL  
Preparer's Zip Code: 60013  
MSDS Serial Number: BMLKK

=====  
Ingredients/Identity Information  
=====

Proprietary: NO  
Ingredient: KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE,  
HYDROTREATED  
Ingredient Sequence Number: 01  
Percent: 30-35%  
NIOSH (RTECS) Number: OA5504000  
CAS Number: 64742-47-8  
OSHA PEL: 500 PPM  
ACGIH TLV: 100 PPM

Proprietary: NO  
Ingredient: V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS  
Ingredient Sequence Number: 02  
Percent: 30-35%  
NIOSH (RTECS) Number: OI6180000  
CAS Number: 8032-32-4  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM  
Other Recommended Limit: STEL 400 PPM

Proprietary: NO  
Ingredient: ZINC STEARATE, STEARIC ACID ZINC SALT, OCTADECANOIC ACID ZINC  
SALT  
Ingredient Sequence Number: 03  
Percent: 1-5%  
NIOSH (RTECS) Number: ZH5200000  
CAS Number: 557-05-1  
OSHA PEL: 15 MG/M3 TDUST  
ACGIH TLV: 10 MG/M3 TDUST; 9293

Proprietary: NO  
Ingredient: VOL ORGANIC CMPD: <550 GM/L  
Ingredient Sequence Number: 04  
NIOSH (RTECS) Number: 9999999VO

Proprietary: NO  
Ingredient: WEIGHT PER GALLON IN POUNDS: 7  
Ingredient Sequence Number: 05  
NIOSH (RTECS) Number: 9999999WG

---

---

Physical/Chemical Characteristics

---

---

Appearance And Odor: CLEAR  
Boiling Point: SEE SUPP.  
Vapor Density (Air=1): >AIR  
Evaporation Rate And Ref: SLOWER THAN ETHER  
Percent Volatiles By Volume: 72%

---

---

Fire and Explosion Hazard Data

---

---

Flash Point: 105F  
Lower Explosive Limit: 0.9%  
Extinguishing Media: FOAM, CO2, DRY CHEMICAL, OR WATER FOG  
Special Fire Fighting Proc: TREAT AS A VOLATILE LIQUID FIRE. WATER SPRAY  
MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.  
Unusual Fire And Expl Hazrds: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED  
TO EXTREME HEAT. COMBUSTIBLE LIQUID.

---

---

Reactivity Data

---

---

Stability: YES  
Cond To Avoid (Stability): HEAT, SPARKS, OPEN FLAMES  
Materials To Avoid: STRONG OXIDIZING AGENTS  
Hazardous Poly Occur: NO

---

---

Health Hazard Data

---

---

Route Of Entry - Inhalation: YES  
Route Of Entry - Skin: YES  
Route Of Entry - Ingestion: NO  
HEADACHE, DIZZINESS, & NAUSEA.  
Carcinogenicity - NTP: NO  
Carcinogenicity - IARC: NO  
Carcinogenicity - OSHA: NO  
Explanation Carcinogenicity: NONE  
HEADACHE, DIZZINESS, & NAUSEA.  
Emergency/First Aid Proc: EYES: FLUSH W/FRESH WATER. SKIN: WASH W/WARM  
WATER & SOAP. INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION  
IF BREATHING STOPS. INGESTION: DON'T INDUCE VOMITING. KEEP WARM & QUIET.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

---

---

Precautions for Safe Handling and Use

---

---

Steps If Matl Released/Spill: ELMINATE IGNITION SOURCES. CONTAIN SPILL,  
ABSORB LIQUID W/CLAY, SAND OR FLOOR ABSORBENT. PREVENT RUN-OFF TO SEWERS,  
STREAMS OR OTHER BODIES OF WATER.  
Waste Disposal Method: CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A  
LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. COMBUSTIBLE  
LIQUID.  
Precautions-Handling/Storing: CONTAINERS SHOULD BE GROUNDED WHEN POURING.  
AVOID FREE FALL OF MORE THAN 2-3 INCHES WHEN POURING.  
Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN.

---

---

Control Measures

---

---

Respiratory Protection: USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IF  
>TLV. APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES OF  
OVERSPRAY DURING APPLICATION.  
Ventilation: MECHANICAL/GENERAL OR LOCAL EXHAUST TO KEEP <TLV.  
Protective Gloves: RECOMMENDED

Eye Protection: SAFETY GLASSES  
Other Protective Equipment: IMPERVIOUS CLOTHING & BOOTS  
Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING  
BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.  
Suppl. Safety & Health Data: BOILING RANGE: 244-350F.

=====  
Transportation Data  
=====

=====  
Disposal Data  
=====

=====  
Label Data  
=====

Label Required: YES  
Label Status: G  
Common Name: 015 TRU-TEST SUPREME WOODSMAN SANDING SEALER  
HEADACHE, DIZZINESS, & NAUSEA.  
Label Name: TRU-TEST MANUFACTURING CO  
Label Street: 201 JANDUS RD  
Label City: CARY  
Label State: IL  
Label Zip Code: 60013  
Label Emergency Number: 800) 228-5635