MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTR	RIBUTO	R'S INFORMATION					
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0		S Rating: Health-2;	Flammabi	lity-2; Reactiv	ity-0; Persor	nal Protection-B	
Manufactured For: Lagasse Brothers, Inc.	DO	DOT Hazard Classification: ORM-D					
Address: 1525 Kuebel Street	lde	Identity (trade name as used on label):					
Address: New Orleans, LA 70123	l'	Woods Etc. Furniture/Polish Bravo2030					
Phone: 800-989-7487	MS	S Number: 136 Revision- 3					
		Date Prepared: 04/12/93 Prepared By: ES/KD					
		Information Calls: (770)422-2071					
SECTION 1 - MATERIAL IDEN	NTIFIC	ATION AND INFORM	IATION			*	
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **	
PETROLEUM DISTILLATE		8052-41-3	No	100	100	d	
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.980							
		apor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
por Density (Air = 1): N/E		vaporation Rate (= 1): N/E					
		Vater Reactive: No					
Appearance and Odor: Cream color, with lemon fragrance.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:							
(aerosols) 12-16 Inch Flame Extension N/E % LEL: N/E % UEL: N/E							
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						OCCUR	
Incompatibility (Mat. to avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful amd may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Slight irritation. Skin Contact: Slight irritation.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Petroleum distillate has caused kidney injury in laboratory animals. Stomach and intestine irritant.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Latex, if skin easily irritated. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT							
FLUSH TO SEWER. Wasta Disposal Mathade: Acrosol cans when vented to atmospheric pressure through normal use, nose no disposal hazard							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions & for Special Hazards: KEEP OUT OF PEACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.							

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only