

* * * * *
 * M S D S *
 *
 * Canadian Centre for Occupational Health and Safety *
 * * * * * (February, 2002) *

*** IDENTIFICATION ***

MSDS RECORD NUMBER : 2930340
 PRODUCT NAME(S) : ZOOM SPOUT
 PRODUCT IDENTIFICATION : PRODUCT NUMBER 64066
 DATE OF MSDS : 2000-03-13
 CURRENCY NOTE : This MSDS was provided to CCOHS in electronic form on 2001-11-01

*** MANUFACTURER INFORMATION ***

MANUFACTURER : Lawson Products, Inc
 ADDRESS : 1666 East Touhy Avenue
 Des Plaines Illinois
 U.S.A. 60018
 Telephone: 847-827-9666
 EMERGENCY TELEPHONE NO. : 303-623-5716 (Rocky Mountain Poison and Drug Center)

*** SUPPLIER/DISTRIBUTOR INFORMATION ***

SUPPLIER/DISTRIBUTOR : Lawson Products, Inc
 ADDRESS : 1666 East Touhy Avenue
 Des Plaines Illinois
 U.S.A. 60018
 Telephone: 847-827-9666
 EMERGENCY TELEPHONE NO. : 303-623-5716 (Rocky Mountain Poison and Drug Center)

*** MATERIAL SAFETY DATA ***

64066

MATERIAL SAFETY DATA SHEET
 ESSENTIALLY SIMILAR TO OSHA FORM 174

---- RATINGS -----	HMIS	NFPA	-- HAZARD INDEX --	----	PERSONAL PROTECTION	-----
HEALTH	1	0	SEVERE HAZARD 4	A	GLASSES	
FLAMMABILITY	1	0	SERIOUS HAZARD 3	B	GLASSES & GLOVES	
REACTIVITY	0	0	MODERATE HAZARD 2	C	GLASSES, GLOVES & APRON	
PERSONAL PROTECTION A			SLIGHT HAZARD 1	D	FACE SHIELD, GLOVES & APRON	
			MINIMAL HAZARD 0	E	GLASSES, GLOVES & RESP.	

MANUFACTURED FOR:
 Lawson Products, Inc.
 1666 East Touhy Avenue
 Des Plaines, Illinois 60018

EMERGENCY TELEPHONE NUMBER:
 Rocky Mountain Poison and Drug Center
 (303) 623-5716

REVISION DATE:
 03/13/00

INFORMATION TELEPHONE NUMBER:
 (847) 827-9666

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER 64066
 PRODUCT NAME Zoom Spout
 PRODUCT CLASS Oils

SECTION II - HAZARDOUS INGREDIENTS

ACGIH OSHA OSHA OSHA
 TLV PEL PEL TLV

INGREDIENT	CAS NUMBER	%	TWA		STEL	
			PPM	PPM	MG/M ³	MG/M ³

=====

SECTION III - PHYSICAL DATA

=====

BOILING POINT (degrees F): 550.0
 VAPOR DENSITY: Heavier than air.
 EVAPORATION RATE: Slower than ether.
 PERCENT VOLATILE (By Volume): 0.0 WEIGHT PER GALLON (LBS): N/A
 ODOR AND APPEARANCE: Mild odor, yellow color.

=====

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

=====

FLAMMABILITY CLASSIFICATION: U.N. CLASSIFICATION:
 OSHA CLASS N/A PER DOT
 DOT CLASS N/A PER IMCO
 IMCO CLASSIFICATION NUMBER: IATA CLASSIFICATION:

FLASH POINT (Degrees F): 365 METHOD: Clev Closed Cup
 LEL: N/A UEL: N/A
 NFPA FIRE PROTECTION LEVEL: VOLATILE ORGANIC COMPOUNDS: N/A
 EXTINGUISHING MEDIA:

FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors or other ignition sources at locations distant from material handling point.

SPECIAL FIREFIGHTING PROCEDURES:

Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

=====

SECTION V - HEALTH HAZARD DATA

=====

EFFECTS OF OVEREXPOSURE:

Irritates eyes. Prolonged or repeated contact may irritate skin.
 Nose and throat irritant.

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT EYE CONTACT INGESTION

MEDICAL CONDITIONS PRONE TO OVEREXPOSURE:

Skin disorders.

TARGET ORGANS AFFECTED:

N/A

CARCINOGENICITY:

None of the components in this chemical are listed by IARC, NTP or OSHA as a carcinogen.

EMERGENCY AND FIRST AID PROCEDURES:

Ingestion: NONE. Inhalation: Move person to fresh air.

Skin: Remove completely with dry cloth or paper towel before washing with detergent and water.

Eyes: Immediately flush eyes with water for at least 15 minutes and get medical attention if irritation persists.

=====

SECTION VI - REACTIVITY DATA

=====

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:

Combustion can yield aldehydes and carbon, nitrogen and sulfur oxides.
 Thermal decomposition may produce hydrogen sulfide and other sulfur gasses at temperatures above 150F.

CONDITIONS TO AVOID:

Do not store in temperatures above 80 degrees Fahrenheit.

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong oxidizers, strong bases.

=====

SECTION VII - SPILL OR LEAK PROCEDURES

=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition, ventilate. Avoid breathing vapors and remove with inert absorbent.

WASTE DISPOSAL METHOD:

Dispose of product in accordance with local, county, state, and federal regulations. Do not puncture or incinerate container.

=====

SECTION VIII - SAFE HANDLING AND USE INFORMATION

=====

RESPIRATORY PROTECTION:

If airborne concentrations exceed recommended exposure limits, a suitable NIOSH respirator should be worn.

VENTILATION:

If current ventilation practices are not adequate in maintaining airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required.

PROTECTIVE GLOVES:

Required for prolonged or repeated contact.

EYE PROTECTION:

Safety Glasses.

OTHER PROTECTIVE EQUIPMENT:

Eye wash station and safety showers should be available.

HYGENIC PRACTICES:

Wash Hands before eating or using the washroom.
Smoke in SMOKING AREAS O N L Y .

=====

SECTION IX - SPECIAL PRECAUTIONS

=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Read Entire Label Before Using.

OTHER PRECAUTIONS:

FOR INDUSTRIAL USE ONLY.
DO NOT TAKE INTERNALLY.

Date of Preparation 03/04/00

RESPONSIBLE PARTY:

Engineering Department
Lawson Products, Inc.
1666 East Touhy Avenue
Des Plaines, Illinois 60018
(847) 827-9666

"Final determination of suitability of the chemical(s) is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS."

PPM	Parts Per Million	CAS	Chemical Abstract Service
CNS	Central Nervous System	DOT	Department of Transportation
TLV	Threshold Limit Value	UEL	Upper Explosive Level
LEL	Lower Explosive Level	MG/M ³	Milligrams per Cubic Meter
N/A	Not Currently Available	NFPA	National Fire Protection Agency
NTP	National Toxicology Program	PEL	Permissible Exposure Levels
STEL	Short Term Exposure Limit	TWA	Time Weighted Average

HMIS Hazardous Materials Identification System
IATA International Air Transport Association