

MATERIAL SAFETY DATA SHEET

PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER (800) 424-9300 (24 Hours) CHEMTREC

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION 1.

PRODUCT NAME:

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

APPLICATION:

INDICATOR LIQUID

COMPANY IDENTIFICATION:

ONDEO Nalco Company ONDEO Nalco Center Naperville, Illinois 60563-1198

EMERGENCY TELEPHONE NUMBER:

(800) 424-9300 (24 Hours) CHEMTREC

NFPA 704M/HMIS RATING

HEALTH: 1/2

FLAMMABILITY:

3/3

REACTIVITY:

0/0

OTHER:

0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme

COMPOSITION/INFORMATION ON INGREDIENTS

Our hazard evaluation has identified the following chemical substance(s) as hazardous. Consult Section 15 for the nature of the hazard(s).

Hazardous Substance(s)

CAS NO

% (w/w)

Isopropanol Methanol

67-63-0

60.0 - 100.0

67-56-1

1.0 - 5.0

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING

Flammable. Irritating to eyes and skin. Contains methanol. Methanol may cause central nervous system effects or permanent vision damage if inhaled, swallowed or absorbed through the skin in large amounts.

Do not get in eyes, on skin, on clothing. Do not take internally. Avoid breathing vapor. Use with adequate ventilation. Keep container tightly closed. Keep away from heat. Keep away from sources of ignition - No smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water.

Wear suitable protective clothing, gloves and eye/face protection.

May evolve oxides of carbon (COx) under fire conditions. Flammable Liquid; may release vapors that form flammable mixtures at or above the flash point. Empty product containers may contain product residue. Do not pressurize, cut, heat, weld, or expose containers to flame or other sources of ignition.

PRIMARY ROUTES OF EXPOSURE:

Eve. Skin, Inhalation



PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

JUN 0 6 2002

EMERGENCY TELEPHONE NUMBER
(800) 424-9300 (24 Hours) CHEMTREC

HUMAN HEALTH HAZARDS - ACUTE:

EYE CONTACT:

Can cause moderate irritation.

SKIN CONTACT:

Can cause moderate irritation. Methanol may be absorbed through the skin and cause central nervous system effects which may result in permanent visual changes including blindness.

INGESTION

Not a likely route of exposure. There may be irritation to the gastro-intestinal tract with nausea and vomiting. Can cause blindness.

INHALATION:

Repeated or prolonged exposure may irritate the respiratory tract.

SYMPTOMS OF EXPOSURE:

Acute:

A review of available data does not identify any symptoms from exposure not previously mentioned.

Chronic:

A review of available data does not identify any symptoms from exposure not previously mentioned.

AGGRAVATION OF EXISTING CONDITIONS:

A review of available data does not identify any worsening of existing conditions.

4. FIRST AID MEASURES

EYE CONTACT:

Immediately flush eye with water for at least 15 minutes while holding eyelids open. If irritation persists, repeat flushing. Get immediate medical attention.

SKIN CONTACT:

Immediately flush with plenty of water for at least 15 minutes. If symptoms persist, call a physician.

INGESTION:

Do not induce vomiting without medical advice. If conscious, washout mouth and give water to drink. If reflexive vomiting occurs, rinse mouth and repeat administration of water. Get medical attention.

INHALATION:

Remove to fresh air, treat symptomatically. Get medical attention.

NOTE TO PHYSICIAN:

Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.



MATERIAL SAFETY DATA SHEET

PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER

(800) 424-9300 (24 Hours) CHEMTREC

5. FIRE FIGHTING MEASURES

FLASH POINT:

54 °F / 12 °C (TCC)

LOWER EXPLOSION LIMIT:

2.0 V%

UPPER EXPLOSION LIMIT:

12 V%

EXTINGUISHING MEDIA:

Alcohol foam, Carbon dioxide, Dry powder, Other extinguishing agent suitable for Class B fires

FIRE AND EXPLOSION HAZARD:

May evolve oxides of carbon (COx) under fire conditions. Flammable Liquid; may release vapors that form flammable mixtures at or above the flash point. Empty product containers may contain product residue. Do not pressurize, cut, heat, weld, or expose containers to flame or other sources of ignition.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTING:

In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Restrict access to area as appropriate until clean-up operations are complete. Ensure clean-up is conducted by trained personnel only. Ventilate spill area if possible. Do not touch spilled material. Remove sources of ignition. Stop or reduce any leaks if it is safe to do so. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection). Notify appropriate government, occupational health and safety and environmental authorities.

METHODS FOR CLEANING UP:

SMALL SPILLS: Soak up spill with absorbent material. Place residues in a suitable, covered, properly labeled container. Wash affected area. Wash site of spillage thoroughly with water.

ENVIRONMENTAL PRECAUTIONS:

Prevent material from entering sewers or waterways.

7. HANDLING AND STORAGE

HANDLING:

Avoid eye and skin contact. Do not take internally. Do not breathe vapors/gases/dust. Do not get in eyes, on skin, on clothing. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Ensure all containers are labelled. Keep the containers closed when not in use. Use with adequate ventilation. Do not use in locations where vapor is likely to travel to welding flames or arcs or to other hot surfaces. Vapors are much heavier than air, this can result in uneven distribution.

STORAGE CONDITIONS:

Store the containers tightly closed. Store in suitable labelled containers. Store away from heat and sources of ignition. Store separately from oxidizers. Have appropriate fire extinguishers available in and near the storage area. Connections must be grounded to avoid electrical charges.



MATERIAL SAFETY DATA SHEET

PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER (800) 424-9300 (24 Hours) CHEMTREC

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS:

Exposure guidelines have not been established for this product. Available exposure limits for the substance(s) are shown below.

ACGIH/TLV:

Substance(s)

Isopropanol

TWA: 400 ppm , 983 mg/m3

STEL: 500 ppm, 1,230 mg/m3

Methanol

TWA: 200 ppm , 262 mg/m3 (Skin)

STEL: 250 ppm, 328 mg/m3 (Skin)

OSHA/PEL:

Substance(s)

Isopropanol

TWA: 400 ppm, 980 mg/m3

STEL: 500 ppm, 1,225 mg/m3

Methanol

TWA: 200 ppm , 260 mg/m3 (Skin)

STEL: 250 ppm, 325 mg/m3 (Skin)

ENGINEERING MEASURES:

General ventilation is recommended.

RESPIRATORY PROTECTION:

Respiratory protection is not normally needed. If significant mists, vapors or aerosols are generated an approved respirator is recommended. An organic vapor cartridge with dust/mist prefilter or supplied air may be used.

HAND PROTECTION:

PVC gloves, Neoprene gloves

SKIN PROTECTION:

Wear standard protective clothing.

EYE PROTECTION:

Wear chemical splash goggles.

HYGIENE RECOMMENDATIONS:

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse. Keep an eye wash fountain available. Keep a safety shower available.

HUMAN EXPOSURE CHARACTERIZATION:

Based on our recommended product application and personal protective equipment, the potential human exposure is: Low



PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

JUN 0 6 2005

EMERGENCY TELEPHONE NUMBER
(800) 424-9300 (24 Hours) CHEMTREC

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE

Liquid

APPEARANCE

Clear Amber Orange

ODOR

Alcoholic

SPECIFIC GRAVITY

0.79 @ 60 °F / 16 °C

SOLUBILITY IN WATER

Complete

BOILING POINT

180 °F / 82 °C

10. STABILITY AND REACTIVITY

STABILITY:

Stable under normal conditions.

HAZARDOUS POLYMERIZATION:

Hazardous polymerization will not occur.

CONDITIONS TO AVOID:

Heat and sources of ignition including static discharges.

MATERIALS TO AVOID:

Contact with strong oxidizers (e.g. chlorine, peroxides, chromates, nitric acid, perchlorate, concentrated oxygen, permanganate) may generate heat, fires, explosions and/or toxic vapors.

HAZARDOUS DECOMPOSITION PRODUCTS:

Under fire conditions:

Oxides of carbon

11. TOXICOLOGICAL INFORMATION

The following results are for the hazardous components.

ACUTE ORAL TOXICITY:

Species LD50

Tested Substance

Rat

> 5,000 mg/kg

Isopropanol

Rating: Non-Hazardous

ACUTE DERMAL TOXICITY:

Species

LD50

Tested Substance

Rabbit

13,000 mg/kg

Isopropanol

Rating: Non-Hazardous

ACUTE INHALATION TOXICITY:

Species

LC50

Tested Substance

Rat

12,000 mg/l (8 hrs)

Isopropanol



MATERIAL SAFETY DATA SHEET

PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER

(800) 424-9300 (24 Hours) CHEMTREC

Rating: Non-Hazardous

CARCINOGENICITY:

None of the substances in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the American Conference of Governmental Industrial Hygienists (ACGIH).

HUMAN HAZARD CHARACTERIZATION:

Based on our hazard characterization, the potential human hazard is: High

12. | ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL EFFECTS:

No toxicity studies have been conducted on this product.

ENVIRONMENTAL HAZARD AND EXPOSURE CHARACTERIZATION

Based on our hazard characterization, the potential environmental hazard is: Low

Based on our recommended product application and the product's characteristics, the potential environmental exposure is: Low

If released into the environment, see CERCLA/SUPERFUND in Section 15.

13. DISPOSAL CONSIDERATIONS

If this product becomes a waste, it could meet the criteria of a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Before disposal, it should be determined if the waste meets the criteria of a hazardous waste.

Hazardous Waste: D001

Hazardous wastes must be transported by a licensed hazardous waste transporter and disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal regulations for specific requirements.

14. TRANSPORT INFORMATION

The information in this section is for reference only and should not take the place of a shipping paper (bill of lading) specific to an order. Please note that the proper Shipping Name / Hazard Class may vary by packaging, properties, and mode of transportation. Typical Proper Shipping Names for this product are:

LAND TRANSPORT:

Proper Shipping Name:

FLAMMABLE LIQUID, N.O.S.

Technical Name(s):

ISOPROPANOL, METHANOL UN 1993

UN/ID No : Hazard Class - Primary :

3

Packing Group:

11



MATERIAL SAFETY DATA SHEET

PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER (800) 424-9300 (24 Hours) CHEMTREC

FLAMMABLE LIQUID, N.O.S.

ISOPROPANOL, METHANOL

Flash Point:

12 °C / 54 °F

AIR TRANSPORT (ICAO/IATA):

Proper Shipping Name:

Technical Name(s):

UN/ID No:

Hazard Class - Primary: Packing Group:

IATA Cargo Packing Instructions:

IATA Cargo Aircraft Limit:

П 307

3

UN 1993

60 L (Max net quantity per package)

MARINE TRANSPORT (IMDG/IMO):

Proper Shipping Name: Technical Name(s):

UN/ID No:

Hazard Class - Primary:

Packing Group:

FLAMMABLE LIQUID, N.O.S. ISOPROPANOL, METHANOL

UN 1993

3.2 11

15. REGULATORY INFORMATION

NATIONAL REGULATIONS, USA:

OSHA HAZARD COMMUNICATION RULE, 29 CFR 1910.1200 :

Based on our hazard evaluation, the following substance(s) in this product is/are hazardous and the reason(s) is/are shown below.

Isopropanol: Flammable, Eye irritant

Methanol: Flammable, Target Organ Effect - Eve

CERCLA/SUPERFUND, 40 CFR 117, 302:

Notification of spills of this product is not required.

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (TITLE III) - SECTIONS 302, 311, 312, AND 313:

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):

This product does not contain substances listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 AND 312 - MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370):

Our hazard evaluation has found this product to be hazardous. The product should be reported under the following EPA hazard categories:

Х Immediate (Acute) Health Hazard

Delayed (Chronic) Health Hazard

Х Fire Hazard

Sudden Release of Pressure Hazard



PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER

(800) 424-9300 (24 Hours) CHEMTREC

Reactive Hazard

Under SARA 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are: 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SECTION 313 - LIST OF TOXIC CHEMICALS (40 CFR 372):

This product contains the following substance(s), (with CAS # and % range) which appear(s) on the List of Toxic Chemicals

Hazardous Substance(s)

CAS NO

% (w/w)

Methanol

67-56-1

TOXIC SUBSTANCES CONTROL ACT (TSCA):

The chemical substances in this product are on the TSCA 8(b) Inventory (40 CFR 710).

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15 / formerly Sec. 307, 40 CFR / formerly Sec. 311:

None of the substances are specifically listed in the regulation.

CLEAN AIR ACT, Sec. 111 (40 CFR 60, Volatile Organic Compounds), Sec. 112 (40 CFR 61, Hazardous Air Pollutants), Sec. 602 (40 CFR 82, Class I and II Ozone Depleting Substances): This product contains the following substances listed in the regulation:

Substance(s)

Citations

Isopropanol:

Sec. 111

Methanoi:

Sec. 111, Sec. 112

CALIFORNIA PROPOSITION 65:

This product does not contain substances which require warning under California Proposition 65.

MICHIGAN CRITICAL MATERIALS:

None of the substances are specifically listed in the regulation.

STATE RIGHT TO KNOW LAWS:

The following substances are disclosed for compliance with State Right to Know Laws:

Isopropanol

67-63-0

Methanol

67-56-1

NATIONAL REGULATIONS, CANADA:

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS):

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS CLASSIFICATION:

B2 - Flammable Liquids, D2B - Materials Causing Other Toxic Effects - Toxic Material



MATERIAL SAFETY DATA SHEET

PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

EMERGENCY TELEPHONE NUMBER (800) 424-9300 (24 Hours) CHEMTREC

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):

All substances in this product are listed on the Domestic Substances List (DSL), are exempt, or have been reported in accordance with the New Substances Notification Regulations.

16. OTHER INFORMATION

Due to our commitment to Product Stewardship, we have evaluated the human and environmental hazards and exposures of this product. Based on our recommended use of this product, we have characterized the product's general risk. This information should provide assistance for your own risk management practices. We have evaluated our product's risk as follows:

- * The human risk is: Low
- * The environmental risk is: Low

Any use inconsistent with our recommendations may affect the risk characterization. Our sales representative will assist you to determine if your product application is consistent with our recommendations. Together we can implement an appropriate risk management process.

This product material safety data sheet provides health and safety information. The product is to be used in applications consistent with our product literature. Individuals handling this product should be informed of the recommended safety precautions and should have access to this information. For any other uses, exposures should be evaluated so that appropriate handling practices and training programs can be established to insure safe workplace operations. Please consult your local sales representative for any further information.

REFERENCES

Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices, American Conference of Governmental Industrial Hygienists, OH., (Ariel Insight# CD-ROM Version), Ariel Research Corp., Bethesda. MD.

Hazardous Substances Data Bank, National Library of Medicine, Bethesda, Maryland (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, Co.

IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man, Geneva: World Health Organization, International Agency for Research on Cancer.

Integrated Risk Information System, U.S. Environmental Protection Agency, Washington, D.C. (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO.

Annual Report on Carcinogens, National Toxicology Program, U.S. Department of Health and Human Services, Public Health Service.

Title 29 Code of Federal Regulations, Part 1910, Subpart Z, Toxic and Hazardous Substances, Occupational Safety and Health Administration (OSHA), (Ariel Insight# CD-ROM Version), Ariel Research Corp., Bethesda MD.

Registry of Toxic Effects of Chemical Substances, National Institute for Occupational Safety and Health, Cincinnati, OH, (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO.



PRODUCT

460-S0260 SOLN Special Indicator (M Indicator), Form Liquid

JUN 0 6 2002

EMERGENCY TELEPHONE NUMBER
(800) 424-9300 (24 Hours) CHEMTREC

Ariel Insight# (An integrated guide to industrial chemicals covered under major regulatory and advisory programs), North American Module, Western European Module, Chemical Inventories Module and the Generics Module (Ariel Insight# CD-ROM Version), Ariel Research Corp., Bethesda, MD.

The Teratogen Information System, University of Washington, Seattle, WA (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO

Prepared By: Product Safety Department

Date issued: 06/17/2001 Replaces: 02/05/1998