

UNITED COATINGS -- WALMART SPRAY ENAMEL GLOSS BLACK-20008
MATERIAL SAFETY DATA SHEET
NSN: 801000F048115
Manufacturer's CAGE: UNITD
Part No. Indicator: A
Part Number/Trade Name: WALMART SPRAY ENAMEL GLOSS BLACK-20008

=====
General Information
=====

Company's Name: UNITED COATINGS INC
Company's Street: 2850 FESTIVAL DR
Company's City: KANKAKEE
Company's State: IL
Company's Country: US
Company's Zip Code: 60901
Company's Emerg Ph #: 800-621-1000
Company's Info Ph #: 800-782-7889
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SE
Date MSDS Prepared: 28APR93
Safety Data Review Date: 30MAY96
Preparer's Company: UNITED COATINGS INC
Preparer's St Or P. O. Box: 2850 FESTIVAL DR
Preparer's City: KANKAKEE
Preparer's State: IL
Preparer's Zip Code: 60901
MSDS Serial Number: BZDXW

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: PROPANE (DIMETHYLMETHANE) *96-1*
Ingredient Sequence Number: 01
Percent: 15
NIOSH (RTECS) Number: TX2275000
CAS Number: 74-98-6
OSHA PEL: 1000 PPM
ACGIH TLV: SIMPLE ASPHYXIAN
Other Recommended Limit: 1800 MG/CUM

Proprietary: NO
Ingredient: BUTANE, N-BUTANE
Ingredient Sequence Number: 02
Percent: 15
NIOSH (RTECS) Number: EJ4200000
CAS Number: 106-97-8
OSHA PEL: 800 PPM
ACGIH TLV: 1900 MG/CUM
Other Recommended Limit: 800 PPM

Proprietary: NO
Ingredient: LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE
Ingredient Sequence Number: 03
Percent: 5
NIOSH (RTECS) Number: 1002250AN
CAS Number: 64742-89-8

Proprietary: NO
Ingredient: SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH
AROMATIC NAPHTHA, C8&10 AROMATIC HYDROCARBON *96-1*
Ingredient Sequence Number: 04
Percent: <5
NIOSH (RTECS) Number: WF3400000
CAS Number: 64742-95-6

OSHA PEL: 400 PPM
ACGIH TLV: 50 PPM

Proprietary: NO
Ingredient: TRIMETHYL BENZENE
Ingredient Sequence Number: 05
Percent: <5
NIOSH (RTECS) Number: DC3220000
CAS Number: 25551-13-7
OSHA PEL: 25 PPM
ACGIH TLV: 123 MG/CUM
Other Recommended Limit: 25 PPM

Proprietary: NO
Ingredient: TOLUENE (IARC CARC- GROUP 3) *96-1*
Ingredient Sequence Number: 06
Percent: 15
NIOSH (RTECS) Number: XS5250000
CAS Number: 108-88-3
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 375 MG/CUM

Proprietary: NO
Ingredient: ACETONE; DIMETHYL KETONE; 2-PROPANONE
Ingredient Sequence Number: 07
Percent: <5
NIOSH (RTECS) Number: AL3150000
CAS Number: 67-64-1
OSHA PEL: 1000 MG/CUM
ACGIH TLV: 750 PPM

Proprietary: NO
Ingredient: PROPYLENE GLYCOL T-BUTYL ETHER, PROPANOL, (1,1-DIMETHYLETHOXY)
- *96-1*
Ingredient Sequence Number: 08
Percent: <5
NIOSH (RTECS) Number: UB3772000
CAS Number: 57018-52-7
=====

Physical/Chemical Characteristics

=====

Appearance And Odor: LIQUID W/TYPICAL SOLVENT ODOR
Boiling Point: 271.4F
Vapor Pressure (MM Hg/70 F): 2.62
Specific Gravity: 0.827
=====

Fire and Explosion Hazard Data

=====

Flash Point: 40F
Flash Point Method: TCC
Extinguishing Media: CO2, ALCOHOL FOAM, DRY CHEMICAL
Special Fire Fighting Proc: WEAR SCBA FOR ENCLOSED AREAS. WATER SPRAY MAY
BE USED TO COOL CONTAINERS & PROTECT PERSONNEL. IN ADVANCED FIRES, MAINTAIN
A SAFE DISTANCE FROM SEALED CONTAINERS
Unusual Fire And Expl Hazrds: EXTREMELY FLAMMABLE, MATERIAL WILL READILY
IGNITE AT AMBIENT TEMPS. FLAMMABLE LIQUID CAN RELEASE VAPORS AT TEMPS AT/
ABOVE THE FLASHPOINT.
=====

Reactivity Data

=====

Stability: YES
Cond To Avoid (Stability): HEAT, SPARKS, OPEN FLAMES, AMBIENT TEMPS.
Materials To Avoid: STRONG OXIDIZERS
Hazardous Decomp Products: OXIDES OF CARBON, CO, CO2
=====

Hazardous Poly Occur: NO

=====
Health Hazard Data
=====

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: YES
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: EYES: IRRITATION. SKIN: IRRITATION &
DERMATITIS. INHALATION: EXCESSIVE VAPOR WILL LEAD TO CNS DEPRESSION.
INGESTION: HARMFUL/FATAL. ASPIRATION OF MATERIAL INTO THE LUNGS FROM
VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: IRRITATION, DEFATTING, HEADACHE, DIZZINESS,
INTOXICATION, LOSS OF CONSCIOUSNESS, NERVOUS SYSTEM COLLAPSE.
Med Cond Aggravated By Exp: EXISTING DERMATITIS.
Emergency/First Aid Proc: EYES: FLUSH W/CLEAN, LUKEWARM WATER FOR 15 MINS.
SKIN: WASH AREAS THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH
AIR. GIVE CPR/OXYGEN IF NECESSARY. INGESTION: ASPIRATION HAZARD. KEEP WARM
& QUIET. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: STOP AT THE SOURCE, DIKE AREA & CONTAIN THE
FLOW. MOP UP/ABSORB & PLACE IN SUITABLE CONTAINER.
Waste Disposal Method: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.
Precautions-Handling/Storing: GROUND CONTAINERS WHEN POURING. STORE & USE
BELOW 120F & AWAY FROM DIRECT HEAT & OPEN FLAME. VENTILATE AREA.
Other Precautions: AVOID CONTACT W/SKIN/EYES. AVOID CONTACT W/
COMBUSTIBLES. AVOID BREATHING VAPOR/SPRAY MITS.

=====
Control Measures
=====

Respiratory Protection: USE ORGANIC CARTRIDGE TYPE RESPIRATOR IF
VENTILATION/OTHER MECHANICAL MEANS CAN'T KEEP AIR BELOW THE TLV.
Ventilation: LOCAL EXHAUST: PREFERABLE. MECHANICAL (GENERAL): ACCEPTABLE.
Protective Gloves: CHEMICAL RESISTANT
Eye Protection: CHEMICAL GOGGLES
Other Protective Equipment: APRON, EYE WASH & SAFETY SHOWER.

=====
Transportation Data
=====

=====
Disposal Data
=====

=====
Label Data
=====

Label Required: YES
Label Status: G
Common Name: WALMART SPRAY ENAMEL GLOSS BLACK-20008
Special Hazard Precautions: EYES: IRRITATION &
DERMATITIS. INHALATION: EXCESSIVE VAPOR WILL LEAD TO CNS DEPRESSION.
INGESTION: HARMFUL/FATAL. ASPIRATION OF MATERIAL INTO THE LUNGS FROM
VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. IRRITATION,
DEFATTING, HEADACHE, DIZZINESS, INTOXICATION, LOSS OF CONSCIOUSNESS,
NERVOUS SYSTEM COLLAPSE.
Label Name: UNITED COATINGS INC
Label Street: 2850 FESTIVAL DR
Label City: KANKAKEE
Label State: IL
Label Zip Code: 60901
Label Country: US

Label Emergency Number: 800-621-1000